

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 2 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21001

Gary L. Langlitz, Doug. Co. Surveyors
Mike Tompkins
Sept. 13, 1976
C.S. 59/24

155

1/4 Corner for Secs. 34 and 35.
Found - 1 1/2" I. Pipe, firmly set with Alum. cap attached stamped
U.S.P.C. Property cor. T27S R2W 1/4 34 35 RE 4287.
This monument is unrecorded as noted in Ren. #151
In order to verify this unrecorded monument, we open what is indicated to
be the orig. SW BT,
An Orig. 24" now 28" Hemlock stump with rescribing "1/4 S34 BT"
visible on an unhealed blaze. We open this stump and find at
approx. 60 years by ring count, an old face and plain scribing
"S 34"; Bears S.54°40'W., 41.6 ft. from the cor. monument.
(Record S.54°40'W., 41.6 ft.)
We find no trace of the orig. SE bearing tree.
We note the following bearing object:
A bridge spike, driven in the top center of a 58" Fir stump, stamped
"34" bears N.17°W., 54.4 ft.
The lookout tower on Red Butte bears S.63°E. This corner is located in a
clearcut area.

9/13/76

156

1/4 Corner for Secs. 12 and 1.
Found - Brass cap. Ren. #60
A 10" D. Fir snag S.9°W., 15.4 ft. (good scar)
A 16" W. Fir N.78°W., 6.3 ft. (good scar)
A 16" W. Fir N.39°W., 4.5 ft. (opened face)
New BT - A 12" Maple bears S.45°E., 17.0 ft. scribed "1/4 S12 BT" with
washer in BT face.

RE-RENEWED, SEE CORNER NO. #227

3/77

BHW Engineering &
Surveying - Romano
E. Ware
For: U.S. Forest Ser.
March 1977
M 65 - 13

157

Section corner for 1 and 12 only.
Found - 3/4" Iron pipe. Ren. #10
A 30" Hemlock snag, S.50°E., 11.2 ft. scribing visible.
A 30" D. Fir snag, S.52°W., 23.8 ft. scribing visible.
A 12" Fir, N.31°W., 22.4 ft. good face.
A 42" D. Fir, N.73°W., 13.2 ft. No scar or scribe visible.
New BT - A 16" D. Fir bears S.30°W., 104.5 ft. (scribed "T27S R2W S12 BT"
washer set in face.

RE-RENEWED, SEE CORNER NO. #169

3/77

158

Closing Corner for Secs. 13 and 14 only.
Found - 1957 County Surveyors Office Brass cap with fence post alongside.
Ren. #5 and Ren. #102
24" Fir stump bears S.35°E., 47.5 ft. visible scribing
40" Hemlock stump bears S.37 1/2°W., 33.0 ft. visible scribing
70" Fir stump bears S.88°W., 67.0 ft. visible scribing
New BT's - 6" Fir bears S.11°E., 44.8 ft. scribed "T27S R2W CC S13 BT".
7" Fir bears S.67°W., 61.5 ft. scribed "T27S R2W CC S14 BT".

159

1/4 Corner for Secs. 13 and 14.
Found - 2 1/2" Alum. cap on 3/4" I. Rod. Ren. #33 stamped U.S. Plywood
Property Cor. T27S R2W 13 14 R.E. 4287.
14" Cedar bears N.22°E., 18.5 ft. visible scribing
14" Cedar tob bears N.65°W., 15.4 ft. visible scribing.
New BT's - 18" Cedar bears N.10°W., 28.0 ft. scribed 1/4 S14 BT.
Rescribed 14" Cedar bears N.22°E., 18.5 ft. scribed 1/4 S13 BT.

160

Section Corner for Secs. 13, 14, 23 and 24.
Found - 1957 County Surveyors Office brass cap properly stamped. Ren. #3
28" Cedar bears N.32°E., 98.4 ft. scribing visible.
12" Hemlock down.
New BT's - A 6" D. Fir bears S.63°W., 18.0 ft. scribed T27S R2W S23 BT.
A 8" Alder bears N.32°W., 45.8 ft. scribed T27S R2W S14 BT.
A 6" D. Fir bears S.53°E., 21.6 ft. scribed T27S R2W S24 BT.

FD. OK. 6/80 R.L.S. #1654 SEE M 79-44

161

North 1/4 Corner for Sec. 13 only.
Found - Alum cap on rod. Unrecorded
Set - Re-proportion and set 2 1/2" I.P. with brass cap 0.86 ft. East of
unrecorded alum. cap Brass cap stamped T27S R2W 1/4 S13 1977
L.S. 1005.

RE-RENEWED, SEE CORNER NO. 222

Romanso E. Ware
For: U.S. Forest Service
May, 1977
M 65 - 20