

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 2 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21981

161

CONT.

New BT's- 8" Alder bears S.34°E., 15 ft. scribed "1/4 S13 BT"
12" Hemlock bears S.88°W., 38.1 ft. scribed "1/4 S13 BT"
Trees with washers in BT face.

Center 1/4 Cor. for Sec. 13

Set - 2 1/2" I.P. with brass cap in rock mound. Cap stamped T27S R2W
C 1/4 S13 L.S. 1005 1977.

New BT's- 10" Hemlock bears N.69°E., 35.2 ft. scribed "C 1/4 S13 BT".
24" Hemlock bears S.32°W., 28.7 ft. scribed "C 1/4 S13 BT".

RE-RENEWED, SEE CORNER NO. #221

162

1/4 Corner for Sec. 13 only. East boundary.

Set - 2 1/2" I.P. with brass cap in rock mound stamped T27S R2W 1/4
S13 R1W 1977 LS 1005.

New BT's- 6" W. Fir bears N.61°W., 7.7 ft. scribed "1/4 S13 BT"
6" W. Fir bears S.29°W., 45.1 ft. scribed "1/4 S13 BT".

163

Sec. Corner for Secs. 18 & 19 only, T27-1.

Found - 1968 County Surveyors Office Brass cap restamped BLM 1971 on a
1" I.Pipe with 3/4" I. Rod bears 0.5 ft. West. Ren. #100
32" Fir stump bears N.34°E., 60.0 ft. scribed "T27S R1W S18 CS BT"

New BT's- 10" Maple bears S.45°E., 50.5 ft. scribed T27S R1W S19 BT
6" Fir bears N.52°E., 43.6 ft. scribed T27S R1W S18 BT.

164

1/4 Corner for Sec. 19 only, T27-1.

Found - A 34" Fir, (Rec. 36") bears N.10°W., 10.6 ft. Blaze opened, old
scribing visible "1/4 S24 BT".

A 14" now 28" Fir bears S.37°E., 24.4 ft. (Rec. S.40°E.) No
scribing found, blaze is chopped out.

Set - 1" x 36" I.Pipe with brass cap attached at 1/4 Corner as det-
ermined in found trees. Cap is stamped "Douglas County Surveyor"
T27S R1W 1/4 S19 1977.

I reblaze old bearing tree, 28" Fir, bears S.37°E., 24.4 ft. scribed "1/4
S19 CS BT" on single blaze.

Corner lies on N-S cutting line. Timber is on east as the BT to the NW is
the only evidence remaining of the 1902 and 1911 surveys. I do Not remove
the scribing referring to Sec. 24, altho the 1911 notes indicate this is not 1/4 for 24.

165

RE-RENEWED, SEE CORNER NO. #216

Larry Monrean
Doug. Co. Surveyor
Office
Karen Cheney
Feb. 23, 1977
C.S. 59/29

166

CC for Secs. 13 and 24 only.

Set - A 2 1/2" I. Pipe with brass cap in rock mound stamped T27S
R2W CC S13 S24 S19 R1W L.S. 1005 1977.

New BT's- 7" Maple bears N.2°W., 52.2 ft. scribed "T27S R2W S13 CC BT".
8" Maple bears South, 45.9 ft. scribed "T27S R2W S24 CC BT".

Romanso E. Ware
For: U.S. Forest
Service
May 1977
M 65 - 19

167

1/4 Corner for Sec. 24 only. (EAST)

Set - A 2 1/2" I. Pipe with brass cap in rock mound stamped T27S R2W CC S24 R1W
OLS 1005 1977.

New BT's- 8" D. Fir bears N.43°W., 35.8 ft. scribed 1/4 S24 CC BT.
6" D. Fir bears S.62°W., 32.2 ft. scribed 1/4 S24 CC BT.

168

1/4 Corner for Secs. 19 and 20

Found - 1968 Douglas Co. Brass cap Ren. #116
16" Hemlock stump, S.26°W., 28.9 ft.

9" Cedar stump (down) S.42°E., 30.8 ft.

Set - 7" Cedar stump, N.62°E., 9.4 ft. mkd. 1/4 S20 T27S R2W B.T.

Thomas E. Shrum, Jr.
For: Champion Inter-
national Corp.
June 14, 1977
C.S. 58/146