

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 2 R.W.W.M.

ROSE-CHAPMAN CO., EUGENE, ORE. 21881

Dennis Gaylord
U.S.F.S.
Deputy, Doug. Co.
Surveyors Office
Witness: Lee Zink
Jan. 18, 1979
C.S. 60/24

185

Angle Point for Secs. 33; and Sec. 3 of T28-2
 Found - Orig. 30" Cedar is now a 52" Cedar, bears N.85°W., 42.24 ft. to face. Faint scribing visible on bark blaze.
 Orig. 36" Fir is a windfall. (Lying on face). Location of face of tree when standing bears N.65°E., 71.28 ft.
 Orig. 6" Fir BT is gone.
 Set - Measuring from face of Cedar and approx. face of Fir as determined from rootwad hole, I SET a 1 1/2" I.P. 36" Long 24" into ground.
 A 2 1/2" Brass cap attached is stamped County Surveyors Office A.P. T27S S33 T28S S3 R2W 1979.
 New BT's-A 20" D. Fir bears S.75°E., 70.5 ft. scribed "AP CS BT" on double blazes.
 A 14" D. Fir bears N.51°E., 65.6 ft. scribed "AP CS BT" on double blazes.
 Placed County BT signs on orig. and new BT's.
 This corner falls in the edge of a small creek. C.C. for Sec. 3 & 4 is a Brass cap and bears S.78°30'W., 112.4 ft. (Rec. West, 110 ft.).

1/18/79

Township corner for Sec. 31 and; Secs. 36 of T.27-3; Sec. 1 of T.28-3 and Sec. 6 of T.28-2

Found - 1" iron pipe with 1962 County brass cap. Ren. #20
 11" D. Fir, N.14°W., 19.7 ft. good scar
 14" Madrone snag, S.3°E., 17.0 ft. visible scribes
 22" Cedar, S.27°W., 72.8 ft. visible scribes
 New BT - 7" D. Fir, N.27°E., 35.3 ft. "T27S R2W S 31 BT".
 Set fiberglass post 3.0 ft. south. BT has brass washer RLS 1005 in face.

Ronald A. Quimby
BHW, Engineering
For: U.S. Forest Service
March 1980
M 79 - 37

187

Angle point for Sections 31; and Sec. 6 of T.28-2
 Found - 1" I.P. with alum. cap marked U.S.P.C. prop. cor. T27S R2W AP S31 S6 T.28S R2W RE 4287 1968. Ren. #133
 12" Fir, N.2°W., 33.3 ft.
 12" Fir, S.65°E., 11.1 ft.
 New BT's - 14" Cedar, S.14°W., 10.0 ft. marked "A.P. S6 BT".
 6" Fir, S.66°W., 34.5 ft. "AP S6 BT".
 Brass washers in BT faces.. Set fiberglass post and sign 2.0 ft. north..
 3/80

188

Center 1/4 Corner for Sec. 23
 Set - A 2 1/2" Iron pipe with brass cap mkd:"T27S R2W C1/4 S23 RLS 1654 1980".
 BT's - A 7" D. Fir bears S.54°W., 15.4 ft. scribed "C1/4 S23 BT".
 A 6" D. Fir bears N.22°W., 6.0 ft. scribed "C1/4 S23 BT".
 Set post and sign 4.0 ft. north. Brass washers marked RLS #1005 set in BT faces.

6/80

189

1/4 Corner for Sections 23 and 24 Ren. # 108
 Fd - County Surveyor's Office Brass Cap properly mkd. See Ren.#108
 6" Hemlock bears S.21°E., 20.7 ft. with visable scribes (down).
 10" Yew bears N.75°W., 154.6 ft. with visable scribes (down).
 18" Hemlock stump bears S.85°E., 21.1 ft. with visable scribes.
 News BT's - 8" Fir bears S.26°W., 52.3 ft. scribed "1/4 S23 BT".
 14" Madrona bears N.60°W., 225.0 ft. scribed "1/4 S23 BT".
 Brass washers marked RLS #1654 set in BT faces. Found post 1.0 ft. south.
 6/80

190

1/4 Corner for Sections 14 and 23 Ren. #129
 Fd - 1 1/2" Iron pipe with aluminum cap properly mkd. See Ren. #'s 129 and Ren. #37.
 20" D. Fir stump up root bears S.34°E., 17.8 ft. with visable scribe.
 18" D. Fir stump up root bears N.76°W., 10.4 ft. with visable scribe.
 22" D. Fir stump up root bears N.20°W., 4.6 ft. with visable scribe.
 New BT's - 12" Cedar bears N.80°E., 107.6 ft. scribed "1/4 S14 BT".
 7" Cedar bears S.82°E., 111.2 ft. scribed "1/4 S23 BT".

Ronald A. Quimby LS#1654
 Romano E. Ware LS#1005
 For: U.S. Forest Service
 May 1980 M 79 - 44