

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 27 S. T. S. R. 2 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

Ronald A. Quimby LS # 1654
For: U.S. Forest Service
May 1980 M 83 - 78

Ronald A. Quimby LS#1654
Romanso E. Ware LS#1005
For: U.S. Forest Service
May 1980
M 79 - 45

191

1/4 Corner to Sec. 25 only, T. 27S. R. 2 W.
Set - 2 1/2" Iron pipe with brass cap mkd: "T27S R2W 1/4 S25 only
 RLS 1005 1980."
BT's - 22" Hemlock bears N.8°W., 7.7 ft. scribed "1/4 S25 BT" with brass
 washer RLS 1005 in BT face.
 6" Yew bears N.44°W., 8.7 ft. scribed "1/4 S25 BT" with brass
 washer RLS 1005 set in BT face.
 10" Yew bears S.7°W., 35.7 ft. scribed "1/4 S25 BT" with brass
 washer RLS 1654 set in BT face.
Note - Set post and sign 4.5 ft. north.

6/80

192

1/4 Corner to Sec. 30 only, T. 27 S. R. 1 W.
Set - 2 1/2" Iron pipe with brass cap mkd: "T27S R1W 1/4 S30 only
 RLS 1654 1980".
BT's - 6" Cedar bears S.64°W., 15.8 ft. scribed "1/4 S30 BT" #250
 7" Hemlock bears N.9°W., 17.8 ft. scribed "1/4 S30 BT".
 16" Hemlock bears S.44°E., 19.9 ft. scribed "1/4 S30 BT."
Note - Brass washers marked RLS #1654 set in BT faces. Also set post
 and sign 4.5 ft. north.

6/80

193

Witness Corner for Secs. 30 and 31, T.27S. R.1W. See Ren. #12
Fd. - 30" Cedar bears S.36°E., 32.0 ft. to old 10' W.C. with visable
 scribes.
 36" Cedar bears N.51°E., 11.9 ft. to old 10' W.C. with visible
 scribes.
True corner is in White Creek - not found.
Set - 2 1/2" Iron pipe with 3" Brass cap mkd. "W.C. T.27S. R.2W. S.25
 R.1W. S.30, S.31 W36.5 RLS 1654 1980".
New BT's- 30" Cedar bears S.18°W., 30.2 ft. scribed "T27S R1W S31 W.C. BT".
 36" Cedar bears N.66°W., 18.5 ft. scribed "T27S R1W S30 W.C. BT".
Note - Set fiberglass post 2.0 ft. east. Brass washer RLS 1654 in BT
 face.
True Corner lies 36.5 ft. West of Witness Corner. 6/80

194

Angle Point btwn. Sec. 34, T27-2W. and Sec. 2, T28-2W Ren. #88
Fd.- Aluminum cap on 3/4" Iron Rod (unrecorded) mkd. "USPC Prop. Cor.
 T27S R2W S34, AP T28S R2W S2 RE#4287".
 10" Yew N.14°E., 18.0 ft. with visable scribe.
 20" Hemlock stump bears N.77°E., 40.1 ft. with visable scribe.
 24" Fir stump, original BT, down bears North 6.0 ft. (uproot)
 12" W. Fir snag bears S.81°E., 53.4 ft. with visable scribe.
New BT- 8" Fir bears South 66.0 ft. scribed "AP S2 BT", with brass washer
 mkd. RLS 1654 set in BT face.
Set post and sign 3.0 ft. east of corner.

6/80

195

Closing Corner to Secs. 34 and 35, T.27-2W. See Ren. #93
Fd. - Unrecorded aluminum cap on 3/4" iron rod mkd. "USPC PROP. COR. T27S
 S34, S35; T28S R2W S2 RE4287".
 16" Fir stump bears N.50°W., 22.7 ft. (unrecorded). #253
 15" Cedar snag bears S.76°E., 6.6 ft. (unrecorded).
 48" Cedar stump bears S.62°E., 25.6 ft. with visable scribe.
 12" Cedar bears N.41°E., 58.1 ft. with visable scribe.
 Original 30" Cedar stump bears N.45°E., 7.3 ft. shows bottom of
 face.
 Original 36" Fir bears N.78°W., 60.7 ft. shows axe work.
New BT's - 11" Yew bears S.76°E., 207.0 ft. scribed "T28S R2W S2 BT".
 11" Hemlock bears N.12°W., 184.0 ft. scribed "T27S R2W S34 BT".
Note - Set post and sign 6.6 ft. north of corner. Brass washer marked RLS
 1005 set in BT faces.

6/80