

Douglas County Surveyor's Record of
Government Corners Renewed

T27 T. S. R2 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

1/4 Corner to Sec. 34 only
Set - 2 1/2" Iron pipe with brass cap mkd: "T27S R2W 1/4 S34 RLS 1654 1980", at proportionate location.
BT's - 12" Cedar bears N.84°E., 19.9 ft. scribed "1/4 S34 BT".
18" Fir bears S.30°W., 50.7 ft. scribed "1/4 S34 BT".
Note - Set post and sign 2.0 ft. east of corner. Brass washers marked RLS 1654 set in BT faces.

6/80

Closing Corner to Secs. 33 and 34, T27-2W.
Fd. - Original 40" now 48" D. Fir bears N.42°30'W., 26.4 ft. with visible scribe.
Original 14" now 36" Hemlock bears N.1°30'E., 43.6 ft. with old scar. I rescribed "CC T27S R2W S34 BT".
Set - 2 1/2" Iron pipe with brass cap mkd: "T27S R2W CC S33 S34; S3 1980 RLS 1654."
Note - Brass washer mkd. RLS #1005 set in BT face. Also set post and sign 5.0 ft. north of corner.

197

Center 1/4 Corner for Sec. 34
Set = 2 1/2" Iron pipe with brass cap mkd: "T27S R2W C1/4 S34 RLS 1654 1980".
BT's - 8" Hemlock bears S.69°E., 95.2 ft. scribed "C1/4 S34 BT".
7" Hemlock bears S.56°W., 138.77 ft. scribed "C1/4 S34 BT".
Note - Brass washers marked RLS #1654 Set in BT faces. Set post and sign 4.0 ft. west of corner.

198

1/4 Corner to Secs. 27 and 34
Fd. - 1" Iron pipe with aluminum cap mkd. "USPC PROP. COR. 1/4 S27, S34 RE 4287". (NOT OF RECORD)
22" Fir Stump bears N.68°E., 9.2 ft. with visible scribe.
20" Fir stump rotted bears S.54°W., 22.4 ft. with visible scribe.
1 1/4" Iron pipe bears South 0.1 ft.
New BT's - 6" D. Fir bears N.32°E., 7.9 ft. scribed "1/4 S27 BT".
8" D. Fir bears S.22°W., 25.8 ft. scribed "1/4 S34 BT".
Note - Set post and sign 3.0 ft. north of corner. Brass washers marked RLD 1654 set in BT faces.

199

1/4 Corner to Secs. 33 and 34
Fd. - 3/4" Iron pipe with aluminum cap found of stone mkd: "USPC PROP COR T27S R2W S33 S34 RE 4287 Do Not Disturb". (NOT OF RECORD)
28" Fir bears N.48°E., 42.9 ft. with visible scribe.
38" Fir bears S.17°W., 82.3 ft. with healed blaze and "X" on tree.
Metal post and sign.

200
#262

Closing Corner to Sec. 2 and 3, T.28S. R.2W.
Fd. - 3/4" Iron rod with aluminum cap mkd: "USPC PROP COR T27S 34 S3 S2 T28S R2W RE 4287". (NOT OF RECORD).
30" Cedar stump bears N.18°E., 26.6 ft. with visible scribes.
11" Cedar stump bears S.50°E., 56.6 ft. with visible scribes down.
New BT's - 8" Fir bears S.74°E., 9.9 ft. scribed "T28S R2W S2 BT".
6" Yew bears S.16°W., 23.3 ft. scribed "T28S R2W S3 BT".
8" Cedar bears N.28°W., 50.5 ft. scribed "T27S R2W S34 BT".
Brass washer mkd. RLS #1654 set in BT faces and set post and sign 2.7 ft. West of corner.

201

Center 1/4 Corner to Sec. 35
Set - 2 1/2" Iron pipe with brass cap mkd: "T27S R2W c1/4 S35 RLS 1654 1980".
BT's - 14" Cedar bears S.7°W., 171.1 ft. scribed "C1/4 S35 BT".
10" Hemlock bears S.17°W., 177.5 ft. scribed "C1/4 S35 BT".
Note - Set post and sign 4.0 ft. North. Brass washer mkd. RLS #1005 set in BT faces.

202

Ronald A. Quimby LS# 1654
Romanso E. Ware LS# 1005
For: U.S. Forest Service
May 1980
M 79 - 45

Ronald A. Quimby
Romanso E. Ware
For: U.S. Forest Service
May 1980
M 79 - 46

6/80