

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 S T. S. R 2 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Romanso E. Ware - Ronald Quimby
For: U.S. Forest Service
May 1980
M 79 - 46

CONDITION REPORT ONLY See Ren. #82 203
Closing Corner to Secs. 1 and 2 (T28-2)
Fd. - 2" Iron pipe with brass cap mkd: "General Land Office Survey
T27S R2W S35 - T28S R2W S2, S1 CC 1923".
30" D. Fir bears S.5°W., 75.2 ft. with visable scribes.
18" D. Fir bears S.34°W., 5.0 ft. with good scar.
14" D. Fir bears S.73°W., 12.3 ft. with good scar.
24" D. Fir bears S.68°E., 147.2 ft. with visable face.
Set post and sign 3.0 ft. North.

1/4 Corner to Secs. 35 and 36. See Ren. #95 204
Fd. - 1 1/2" Iron pipe with brass cap properly mkd.
14" Hemlock bears S.63°E., 13.3 ft. with visable scribes.
18" Yew, dead and down, bears S.85°W., 11.9 ft. with visable
scribes.
3" x 3" wood post 1.0 ft. East of corner.
New BT - 20" Yew bears S.70°W., 155.0 ft. scribed "1/4 S35 BT".
Brass washer mkd. RLS #1005 set in BT face.

Sec. Corner to Secs. 25,26,35 and 36. See Ren. #75 205
Fd. - 1 1/2" Iron pipe with brass cap properly mkd.
27" Fir stump bears S.44°W., 6.4 ft. with visable scribes.
24" Fir stump bears N.18°E., 11.6 ft. with visable scribes.
18" Yew bears S.65 1/2°E., 26.7 ft. with visable scribes. #251
36" Fir stump bears N.60°W., 20.5 ft. with visable scribes.
New BT's - 8" Fir bears N.88°W., 52.2 ft. scribed "T27S R2W S26 BT".
14" Hemlock bears N.4°W., 39.6 ft. scribed "T27S R2W S26 BT".
Brass washers mkd. RLS #1654 set in BT faces.

1/4 Corner for Sections 29 and 32 206
Found - Alum. cap on 1" I.P. mkd. U.S.P.C. Prop. Cor. T27S R2W 1/4 S29
S32 RE 4287. Ren. #84
18" Cedar N.50°E., 11.2 ft. vis. scribe, dead & down.
12" Cedar S.36°W., 19.1 ft. Good scar, dead & down.
Metal post at corner.
New BT's - 7" D. Fir, S.64°E., 43.4 ft. "1/4 S32 BT".
7" D. Fir, N.12°E., 34.4 ft. "1/4 S29 BT".
Brass washers marked RLS 1005 set in BT faces.
Set - Post & sign 2.0 ft. North.

1/4 Corner for Section 32 only. (West) 207
Found - 1968 County Brass cap. Ren. #105
30" Fir stump, N.32°E., 21.6 ft. vis. scribe
18" Fir stump, S.44°E., 10.6 ft. Good scar
New BT's - 28" Fir, N.70°W., 45.4 ft. "1/4 S32 BT".
32" Fir, S.24°W., 36.5 ft. "1/4 S32 BT".
Brass washers marked RLS 1005 set in BT faces
No trees in Sec. 32. Set post & sign 5.0 ft. North.

Center 1/4 Corner for Section 32. 208
Set - 2 1/2" Iron pipw with brass cap marked: T27S R2W C 1/4 S32 RLS
1654 1980.
New BT's - 10" Fir, S.41°E., 15.1 ft. "C 1/4 S32 BT".
8" Hemlock, S.44°W., 34.4 ft. "C 1/4 S32 BT".
Set post & sign 3.0 ft. North. Brass washer marked RLS 1654 Set in BT faces.

1/4 Corner for Secs. 32 and 33. 209
Found - 1968 County brass cap. Ren. #125
42" Fir stump, N.58°E., 23.0 ft. vis. scribe.
14" Hemlock N.78°E., 14.6 ft. vis scribe.
14" Hemlock, S.45°E., 23.5 ft. vis. scribe. 243
42" Fir stump, N.18°W., 6.0 ft. vis. scribe.
Set - Post and sign 5.0 ft. North.

Romanso E. Ware and Ronald Quimby
For: U. S. Forest Service
July 1980
M 79 - 49