

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 27

T. S.

R 2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

**210**

Angle point for Secs. 31 and Sec. 6, T.28-2  
 Found - 1" I.P. with alum. cap marked U.S. P.C. Prop. Cor. T27S R2W  
           AP 31 6 T28S R2W RE 4287 1968.           Ren. #134  
           8" Madrone, N.3°W., 27.7 ft. vis. scribes  
           6" D. Fir, S.43°W., 23.1 ft. vis. scribes  
 Set -     Fiberglass post with signs 54.2 ft. and 54.4 ft. East.

**211**

Closing Corner for Secs. 6 and 5 only of T.28-2.  
 Found - 1 1/2" I.P. with brass cap marked County Surveyors Office  
           T27S S31 S6 S5 R2W C.C. T28S 1968.       Ren. #113  
           50" D. Fir, S.34°E., 55.5 ft. vis. scribes  
           44" D. Fir, S.45°W., 7.2 ft. Good scar  
           8" Madrona, S.1°W., 44.0 ft. vis. scribes  
 Set -     Fiberglass post & signs 4.0 ft. South.

**212**

Section corner for Secs. 31 and 32 only .  
 Found - 1968 County Brass cap properly marked.       Ren. #114  
           6" Madrona, N.78°E., 21.4 ft. vis. scribes  
           12" D. Fir, N.12°W., 14.7 ft. Good scar  
 Set -     Fiberglass post & sign 3.0 North of corner.

**213**

Angle Point for Secs. 32; and Sec. 5 of T28-2  
 Found - Unrecorded 3/4" Iron pipe  
           24" Cedar stump, S.18°E., 6.3 ft. vis. scribe       Ren. #140  
           20" Cedar stump, S.62°E., 5.3 ft. Good face  
           20" Cedar, N.35°E., 23.9 ft. vis. scribe  
 Set -     2 1/2" I.P. with brass cap marked T27S R2W AP S32 S5 T28S  
           RLS 1654 1980, over top of 3/4" I.P.  
 New BT's- 22" Cedar South 41.7 ft. "AP S5 BT". Brass washer set in BT face.  
 Set -     Post & Sign 4.0 ft. North.

**214**

1/4 Corner for Sec. 32 only (South)  
 Set -     2 1/2" I.P. with brass cap marked T27S R2W 1/4 S32 RLS 1654 1980.  
 New BT's- 7" W. Fir, N.47°W., 23.5 ft. "1/4 S32 BT".  
           12" W. Fir, N.28°E., 27.4 ft. "1/4 S32 BT".  
           Brass washer marked RLS 1654 set in BT faces.  
 Set -     Post & sign 5.0 ft. North.

**215**

Closing Corner for Secs. 5 and 4 only, T.28-2.  
 Found - 18" Madrona, S.68°W., 11.2 ft. vis. scribes       Ren. #139  
           32" D. Fir, S.62°E., 34.7 ft. Good scar  
 Set -     2 1/2" I.P. with brass cap over top of 3/4" I.P. Marked: T28S  
           R2W S5 S4 C.C. RLS 1654. 1980.  
 BT's -    Rescribed 32" D. Fir "CC T28S R2W S4 BT".  
           Brass washer marked RLS 1654 set in BT face.  
 Set -     Post & sign 3.0 ft. West.

**216**

Angle Point for Secs. 32 and Sec. 4 of T.28-2.  
 Found - 3/4" I.P.                               Ren. #138  
           30" D. Fir, N.45°E., 5.9 ft. vis. bark scribe  
           32" D. Fir, N.25°W., 3.3 ft. Good scar.  
           34" D. Fir, S.27°E., 11.4 ft. Good scar  
           13" D. Fir, N.17°W., 11.2 ft. Good scar.  
 Set -     2 1/2" I.P. with brass cap marked T27S R2W AP S32 S4 T28S RLS  
           1654 1980, over top of found I.P.  
 Set -     Post & Sign 54-9, 2.0 ft. East.