

Douglas County Surveyor's Record of
Government Corners Renewed

T 27

T. S.

R 2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

c o n t - -

(Center 1/4 Cor. Sec. 13)

228

New Accessories:

I set a 4" x 4" wood post, 6 ft. long, 2 ft. in the ground, as a guard post, bears S.89°E., 21.2 ft. with USFS signs #54-6, and #54-9 attached.

All available trees, as are existing BTs are scheduled to be cut (forty timber sale). Corner should be checked after timber is harvested for condition report. Corner is in USFS Rd. #2700-030, 2.9 miles from Little River Road. Tobacco Lid was placed at corner point as a memorial.

12/12/84

1/4 Corner for Section 7; and Sec. 12 of T.27-3

229

Found - 1968 County brass disk on a I.P. protruding 8" above a 2 1/2" dia. mound of stone, properly marked. Ren. #99

No visible evidence found of 1/2" I.R. noted in Ren. #8 and #99. No evidence found of 3/4" I.R. set in 1947. (per C.S. 40/56)

Found - 14" now a 28" dia. 3 ft. high rotted and burnt stump. No scribing found, bears N.36°W., 7.8 ft. to center. (rec. N.15°W., 5.3 ft. Original BT.

10" now a 16" D. Fir with a well healed single blaze bears S.55 1/2°W., 25.7 ft. which agrees with 1979 BLM resurvey. (Rec. S.57°W., 26.5 ft. per Ren. #8 and 99)

6" now a 14" D. fir with a well healed single blaze bears S.13°E., 20.8 ft. which agrees with 1979 BLM resurvey. (Rec. S.11°E., 21.0 ft. per Ren. #8 and 99)

New BTs- 8" D. fir double blaze and scribed "1/4 S7 CS BT" bears S.51°E., 25.6 ft.

13" D. fir double blaze and scribed "1/4 S 12 CS BT" bears N.25 1/2°W., 38.6 ft.

Corner lies approx. 50 ft. south of the left bank of Little River.

12/13/84

Closing Corner for Sections 19 and 30 (T27S R2W)

230

Set - Set a 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum, flared pipe; mkd. PLS 1988

BT's - 11" Fir, bears N.54°E., 15.2 ft. Scribed: T27S R2W S19 CC BT.
7" Fir, bears S.28°E., 20.6 ft. Scribed: T27S R2W S30 CC BT.

NOTE: An amended closing corner bears S.88°59'33"E., 14.38 ft. dist.
See Renewal #136

Sec. Corner to secs. 19-20-29-30

Ren. #49

Found - A 1964 DCSO Brass Cap, on a 1 1/2" iron pipe, and the following accessories;

BT's - 10" Fir snag, 15' tall bears N.31°W., 7.9 ft. No scribing visible. (Orig.)

18" Cedar, bears N.48°E., 23.7 ft. (Rec. 24.4 ft.) Closed face. (Orig.)

23" Fir, bears S.64°E., 17.8 ft. Closed face. (Orig.)

21" Cedar, bears S.62°W., 25.1 ft. (Rec. 26.4 ft.)

Closed face. (Orig.)

Down, and uprooted hamlock bears N.22°W., 36.0 ft. No scribing visible. (1964)

New BT - 10" Cedar, bears N.26°W., 32.0 ft. Scribed: T27S R2W S19 BT.

232

1/4 Corner for Sections 20 and 29

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum, flared pipe; mkd. PLS 1988

BT's - 4" Fir, bears N.22°W., 16.4 ft. dist. Scribed X BT.

4" Fir, bears S.34°W., 18.8 ft. dist. Scribed X BT.

233

East 1/4 Corner to Sec. 25 only, (T.27-3)

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum, flared pipe; mkd. PLS 1988.

BT's - 2" Hemlock, bears N.88°W., 11.1 ft. Scribed X BT.

3" Fir, bears S.18°W., 19.2 ft. Scribed X BT.

Larry E. Monrean
L.S. #1830
Randall Smith
Stephen Flause
Doug. Co. Surveyors
Office
Dec. 13, 1984
C.S. 62/21

Ronald G. Geisler,
Champion International
June/Aug 1985
M 90 - 71