

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 2 R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 21881

Ronald G. Geisler, Champion International Corporation.
June, 1985 thru August, 1985
M 90 - 71

West 1/4 Corner for Section 30 only. 234
Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe;
mkd. PLS 1988.
BT's - 7" Fir, Bears S.87°E., 45.6 ft.
7" Cedar, bears N.42°E., 21.9 ft.

Center 1/4 Corner for Section 30 235
Set - A 2 1/2" aluminum cap on a 1" x 30" iron pipe; mkd. PLS 1988.
BT's - 6" Cedar, bears S.76°E., 4.7 ft.
6" Fir, bears N.15 1/2°E., 12.0 ft.

1/4 Corner for Sections 29 and 30 RENEWAL #91 236
Found - A 1968 brass cap (DCSO) on an iron post, with following acces-
sories;
BT's - Original hemlock down and badly decayed. Root hole bears
N.10°E., 7.9 ft.
8" Yew bears S.37°E., 7.2 ft. Scribing visible (1968)
7" Yew, bears N.47°W., 51.3 ft. Scribing visible. (1968)
12" Fir, bears S.51°W., 38.8 ft. Closed face. (1968)
New BT - 5" Fir, bears S.89°W., 15.0 ft. Scribed: 1/4 S30 BT

Corner to sections 25 and 36 only, (T27-3) 237
Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe;
mkd. PLS 1988.
BT's - 14" Fir, bears S. 11° W., 11.0 ft. Scribed: T27S R3W S36 BT.
7" Fir, bears N.45°W., 18.9 ft. Scribed: T27S R3W S25 BT.

Closing Corner for Sections 30 and 31 238
Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe;
mkd. PLS 1988. An amended closing corner bears S.88°24'45"E.,
17.29 ft. SEE RENEWAL #239
BT's - 13" Fir, bears N.62°E., 6.15 ft. Scribed: T27S R2W S30 CC BT.
6" Hemlock, bears S.07°E., 19.7 ft. Scribed: T27S R2W S31 CC BT.

CORNER REPORT ONLY

Amended Closing Corner for Sections 30 and 31. RENEWAL #17 239
Found - A 1962 County Surveyor brass cap on an iron post, and the
following accessories; (This closing corner is now an amended
CC, See Ren. #238 for new corner)
BT's - Uprooted fir stump bears N.50°E., 18.5 ft. (Orig.)
30" Fir stump, bears S.75°E., 19.1 ft. Scribe marks visible.
(Original)
34" Fir stump, bears S.18°E., 59.4 ft. Scribing visible. (1962)
RM's - Also found a 1 1/2" iron pipe, N.80°W., 1.2 ft. from cap.
(1962 Record = N.80°E 1.2 ft.)

1/4 Corner for Sections 30 and 31. Renewal #109 240
Found - A 1954 truck axle set by Shrum, LS 1706, and the following
accessories;
BT's - Original Hemlock stump, bears N.46°W., 12.5 ft. No scribing found.
24" Fir stump, bears N.52 1/2°E., 36.1 ft. (Rec. 36.7 ft.)
Scribing visible. (1962)
13" Fir, bears N.57°E., 35.7 ft. (Rec. 36.0 ft.) Closed face.
(1968)
New BT - 9" Fir, bears S.48°W., 14.9 ft. Scribed 1/4 S31 BT.

Witness Corner to the West 1/4 Corner for Sec. 31 (T27-2) and Sec. 36 (T27-3) 241
Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe,
mkd. PLS 1988.
BT's - 8" Fir, bears N.28°W., 12.6 ft. Scribed; X BT.
10" Fir, bears N.81°E., 32.2 ft. Scribed; X BT.
NOTE: The true corner position falls in an existing dirt road. The witness
corner bears S.00°44'16"W., 51.09 ft. from the true point.