

Douglas County Surveyor's Record of
Government Corners Renewed

27 T.S. 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Ronald G. Geisler, Champion International
June, 1985 thru August, 1985
M 90 - 71

242

Township Corner for Sec. 31 (T27-2); Sec. 36 (T27-3); Sec. 6 (T28-2); and
Sec. 1 (T28-3). Renewal #186 (27-2)
Found - A 1962 County Surveyor brass cap on an iron post, and the following
accessories;
BT's - 27" Fir stump, bears N.40°E., 46.9 ft. (Rec. N.43°E., 46.2 ft.)
scribing partly visible. (Original)
44" Fir stump, bears N.52°W., 29.9 ft. (Rec. N.55°W., 30.4 ft.)
No scribing visible. (Original)
Badly decayed stump, bears S.25°W., 27.7 ft. (Orig.)
11" broken-top Fir, bears N.10°W., 19.7 ft. Closed face. (1962)
22" Cedar, bears S.27°W., 71.6 ft. (Rec. 72.0 ft.) Closed face
(1962)
16" Madrone snag, 17 ft. tall, bears S.06°E., 17.0 ft.
(Rec. S.03°E) Scribing visible. (1962)
9" down and uprooted fir bears N.87°E., 50.0 ft. No scribing
found. (1962)
10" Fir, bears N.27°E., 35.1 ft. (Rec. 35.3 ft.) Closed face,
(1980)
Set - 5" Fir, bears S.79°E., 5.9 ft. dist. Scribed: X BT.

Romanso E. Ware
L.S. #1005
For: U.S. Forest Serv.
May 1977
M 65 - 20

243

1/4 Corner for Section 18 only, T.27-1
Found - Alum. cap on 3/4" iron rod marked U.S.P.C. Prop. Cor. 1/4 S 18
only R.E. 42 87. Ren. #141
60" fir stump, N.69°E., 29.5 ft.
60" fir stump, S.22°E., 37.0 ft.
10" hemlock, S.18°E., 11.2 ft. (orig.)
New BTs - 8" D. fir bears East 131.5 ft.
8" D. fir bears S.02°E., 98.0 ft.
Both scribed W 1/4 S 18 BT.

5/77

244

1/4 Corner for Sections 13 and 24
Found - A 1968 County Surveyor's brass cap on a 1" I.P. exposed 12"
set under the original oak corner tree. (No scribes visible
on tree). Ren. #98
8" fir snag bears N.55°E., 8.0 ft. scribe visible.
18" fir bears S.05°W., 15.2 ft. scribe visible.
New BT - I marked a 32" fir BT which bears N.86°E., 57.1 ft. from the
corner, scribed 1/4 S13 BT. Nailed L.S. 944 brass washer to
BT scribe.

245

1/4 Corner for Sections 11 and 12
Found - A 2 1/2" alum. cap on 3/4" iron pipe with original corner stone
along side. Ren. Nos. 101 and 39
A 10" fir (down and dead) bears S.72°E., 34.3 ft. scribe
visible (OBT).
A 14" fir bears S.18°E., 3.9 ft. scar visible.
A 8" hemlock (down and dead) bears S.30°W., 26.3 ft. scribe
visible.
New BT - I marked a 12" cedar BT which bears S.28°W., 85.0 ft. from
the corner, scribed 1/4 S11 BT. Nailed A L.S. 944 brass
washer to BT scribe.

Loyd R. Moffit
L.S. 944
For: U.S. Forest Service
June, 1986
C.S. 62/30

246

1/4 Corner for Section 19 only of T.27-1
Found - A 1977 Douglas County 2" brass cap on a 1" iron pipe in a
rock mound. Ren. No. 165
A 40" fir stump bears S.38°E., 24.4 ft. scribe visible.
A 38" fir stump bears N.10°W., 10.6 ft. scribe visible.
New BT - I marked a 4" fir which bears S.64°E., 7.7 ft. scribed "X" BT.
a 6" fir which bears S.23°E., 36.7 ft. scribed
1/4 S19 BT.
I nailed a L.S. 944 brass washer to both BT scribes.