

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 2 R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

247

Loyd R. Moffit
L.S. 944
For: U.S. Forest Serv.
June, 1986
C.S. 62/30

Closing Corner for Sections 6 and 7 only of T.27-1
Found - A 2½" brass cap on a 1" iron pipe. Ren. No. 43
A 19" fir bears S.30°E., 40.8ft. scar visible.
A 23" fir bears S.12°E., 29.7 ft. bark scribe visible.
New BT - I marked a 12" fir BT which bears N.64½°E., 111.0 ft. from
the corner, scribed T27S R1W S6 CC BT. Nailed L.S.
944 brass washer to BT scribe.

248

Maurice E. Farr
For; U.S.F.S.
Witnesses: Leonard
Herzstein and Randy
Lopez
Nov. 5, 1986
C.S. 62/33

Center 1/4 Corner for Section 12
Found - 2" outside dia. iron pipe, firmly set, projecting 8" above ground.
9" Hemlock, N.23°E., 15.7 ft. with a healed blaze. Ren. #149
12" Red cedar, S.38°W., 4.4 ft. with scribe marks "C¼ S12 BT"
visible on a partially healed blaze.
An unrecorded rebar set by U.S. Plywood Corp. in 1956: a 5/8"
rebar firmly set, projecting 15" above the ground, bears
S.02°E., 26.8 ft.
A steel fence post bears South, 5.1 ft. with Forest Service signs
#54-2 and #54-9 as a guard post.
Set - I remove Baughman's iron pipe, which is 36" long, and in its
place I set a 2" x 32" long iron pipe, set 24" in the ground,
with brass cap marked: "T 27S R2W C 1/4 + S 12 L.S. 1181
1986."
I bury Baughman's iron pipe alongside, I raise a 2 ft. dia.
mound of stone flush to the brass cap.
I find the magnetic declination to be 19°E.,

11/5/86

249

Closing Corner for Sections 25 and 36.(Witness Point)
Found - A 1½" iron pipe with brass cap extending 14" above ground per
Ren. #90
An 18" cedar bears N.23°E., 12.0 ft. - visible scribing.
A 20" hemlock, dead and down, bears S.12°E., 40.0 ft.
New BT - 5 ft. D. Fir bears S.14°E., 30.7 ft. scribed "WC" on small upper
blaze and "BT" on small lower blaze. Set ½" brass washer in BT
face marked "LS 1035".
Bearing tree and monument signs were placed on all BTs without them and a
6" red band and face balzes were painted on all bearing trees.

10/13/88

250

1/4 Corner for Sec. 30 only. of T.27-1
Found - 2½" iron pipe with brass cap. Ren. #192
An 8" cedar bears S.64°W., 15.8 ft. - visible scribing
An 8" hemlock bears N.9°W., 17.8 ft. - visible scribing
A 16" hemlock stump bears S.44°E., 19.9 ft. - visible scribing.
New BT - A 7" cedar bears S.25°E., 14.9 ft. scribed "¼S30BT". Set ½" brass
washer in BT face marked "LS 1035".

10/12/88

251

Section Corner for Secs. 25, 26, 35 and 36.
Found - A 1" iron pipe with a 2½" alum. cap extended 6" above ground per
Ren. #205
A 27" fir stump bears S.44°W., 6.4 ft. - visible scribing.
A 24" fir stump, bears N.18°E., 11.6 ft. - visible scribing
An 18" yewood bears S.65½°E., 26.7 ft. - visible scribing.
A 36" fir stump bears N.60°W., 20.5 ft. - visible scribing.
A metal post 1 ft. north of corner.
An 8" fir bears N.88°W., 52.2 ft. - heal blazed.
A 14" hemlock snag bears S.4°E., 39.6 ft. - visible scribing.
(Record per Ren. #205, map No. M79-46, is N.4°W.)
New BT - A 12" D. fir bears S.34°W., 32.3 ft. scribed "T27S R2W S35 BT" and
set ½" brass washer in BT face marked "LS 1035".

10/19/88

Gerald V. Nygren, L.S. 1035
October 1988
C.S. 63/69