

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

252

South 1/4 Corner Section 34 only.

Found - A 2½" iron pipe with brass cap extended 8" above ground. Ren. #196
A 12" cedar snag bears N.84°E., 19.9 ft. - visible scribing.
An 18" fir, dead and down, bears S.30°W., 50.7 ft. - visible scribe
Brass washers marked "RLS #1654" are set in BT faces.
New BTs - A 10" yew bears S.85°E., 81.7 ft. scribed "1/4 S34 BT".
A 6" yew bears S.40°W., 136.0 ft. scribed "1/4 S34 BT".
Brass washer marked "LS 1035" and set in BT faces.

10/14/88

Section Corner for Sections 34 and 35 only.

253

Found - An alum. cap on a 3/4" iron rod. Ren. #195
A 16" fir stump bears N.50°W., 22.7 ft.
A 15" cedar snag bears S.76°E., 6.6 ft.
A 48" cedar stump bears S.62°E., 25.6 ft. visible scribing.
A 12" cedar bears N.41°E., 58.1 ft. visible scribing.
A 30" cedar stump bears N.45°E., 7.3 ft.
An 11" yew bears S.76°E., 207.0 ft. visible scribing.
An 11" hemlock snag bears N.12°W., 184.0 ft. visible scribing.
New BT - A 7" yew bears N.3°E., 39.2 ft. scribed "T27S R2W S35 BT". A ½"
brass washer was set in BT face marked "LS 1035".

10/20/88

Angle Point on South line of Section 35, T.27-2

254

(Point lies approx. 300 ft. East of North 1/4 Cor. for Sec. 1, T.28-2)
Found - A brass cap on iron pipe. Ren. #86
A 6 ft. high, 32" hemlock stump bears N.67°E., 13.9 ft. visible
scribing.
A 9" yew, dean and broken off 4 ft. above ground bears N.17°W.,
10.6 ft. visible scribing.
A 54" D. fir, 4 ft. high stump bears N.1°W., 13.2 ft. visible
scribing.
New BTs - 8" hemlock, S.20°W., 11.0 ft. scribed "AP BT".
18" double yew, S.70°W., 39.1 ft. scribed "AP BT".
Set ½" brass washers in BT faces marked "LS 1035".

10/20/88

1/4 Corner for Sections 16 and 21

255

Found - 28" now 40" dia. 4 ft. high Pine stump, we open and find scirbe
marks "1/4S" bears N.16½°E., 49.4 ft. (Rec. N.18°E., 48.8 ft.
dist. is a face slope measurement) Orig. BT.
18" now 24" dia. 5 ft. high D. fir stump with a previously
opened burnt out blaze, no scribing or blazes found. Corner
renewal request from BLM notes that Wayne Rogers opened BT
and found scribing in 1986, bears S.86½° W., 73.1 ft. (Record
S.88°W., 76.6 ft. dist. is a slope measurement) Orig. BT.

Both BT stumps found with metal caps on top of stumps and BT tags.

Original stake Not Found.

Set - A 2 3/8" DCSO brass cap on a 1 3/8" O.D. x 32" long iron pipe
protruding 7" above ground. Cap mkd. "Douglas County Surveyo
T27S 1/4 S16 S21 R2W 1989".

A position for corner based on record bearings and horizontal
distances was not possible. We find the most reasonable
position with 1½° rotated bearings and slope distances.

New BTs - 22" dia. 1½ ft. high burnt D. fir stump with boat spike set through
DCSO BT tag into top of stump, top of boat spike stamped "BO 1"
Boat spike bears S.30½°W., 28.6 ft.
23" dia. 2 ft. high burnt D. fir stump with boat spike set through
DCSO BT tag into top of stump, top of boat spike stamped "BO 2"
Boat spike bears N.61½°W., 10.8 ft.

8/11/89

Gerald V. Nygren
October, 1988
C.S. 63/69

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Aug. 11, 1989
C.S. 64/1