

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27 T. S. R 2 R. W. W. M.

ROBE-CHAPMAN CO., EUGENE, ORE. 91881

256

Section Corner for Secs. 2, 3, 10 and 11

Found - A 2½" x 30" galv. I.P. with a 3" dia. brass cap stamped "T27S R2W" 3 2 10 11, firmly attached to the top. The monument had been ran over by a cat during recent logging operations and was lying on its side in relatively good position to the bearing tree.

Glen Baughman  
For: U.S.F.S.  
Nov. 1989  
C.S. 63/85

- 13" hemlock bears S.22°W., 29.7 ft. (1962) Ren. #14
- 24" cedar bears N.59°W., 49.2 ft. (1905 rec. 49.5 ft.)
- 41" fir stump bears N.19°E., 56.0 ft. (1905 rec. 54.8 ft.)
- 30" fir stump bears S.47°E., 62.9 ft. (1905 rec. S.50°E., 62.0')
- 15" hemlock (rec. fir) bears N.57°30'W., 22.3 ft. (1957 rec. 21.8 ft. to face)
- 13" fir bears N.60°E., 57.6 ft. (1957 rec. 57.4 ft.)
- 15" cedar bears S.25°E., 19.8 ft. (1957 rec. S.28°30'E.)

Set - I RESET the monument 24" in the ground and built a 36" dia. stone mound to the top of the pipe.

11/89

1/4 Corner for Section 12 only. (East)

257

Found - A 2½" dia. brass cap on a 1½" O.D. iron pipe leaning south of plumb, protrudes 12" above ground.

Douglas County  
Surveyors Office  
Randall Smith  
Terrie Franssen  
July 1, 1991  
C.S. 64/17

12" now 16" dia. D. fir with a fully healed single blaze bears N.4°W., 18.6 ft. (Rec. N.4°W., 19.0 ft. dist. is a slope measurement) Ren. No. 150

6" now 9" dia. D. fir with a fully healed single blaze bears S.49°W., 46.8 ft. (Rec. S.49°W., 45.9 ft.) Ren. No. 150

Set - BC/IP returned to plumb position protrudes 2" above a 2 ft. dia. mound of stone.

New BTs - 5" dia. Cedar double blazed and scribed "¼ S12 CS BT" bears N.41½°W., 15.8 ft.

8" dia. D. fir double blazed and scribed "¼ S12 CS BT" bears S.63°W., 51.7 ft.

BC/IP is in a cut bank on the north side of a gravel road, 25 ft. from centerline.

7/1/91

RE-RENEWED SEE CORNER NO. #260

258

Section Corner for 3 and 4 only (South)

Found - A 1" Iron pipe by Gylord in 1977, firmly set, projecting 1" above ground with a 2½" brass cap. Ren. #171

36" rotted D.Fir stump bears N.53°45'W., 93.5 ft. with scribe marks and reverse scribe marks visible. (Rec. N.51½°W., 141 lks.) Original BT.

21" Cedar bears N.25°15'W., 81.4 ft. with a healed blaze. (Rec. N.24½°W., 81.0 ft.)

12" D.Fir snag bears N.23°15'E., 46.6 ft. with a healed blaze. (Rec. N.24½°E., 46.3 ft.)

1½" Iron pipe firmly set projecting 6" above ground bears N.26°E., 1.70 ft. Ren. No. 7

New BT - A 6" D.Fir bears N.47°45'E., 57.8 ft. scribed "T27S R2W S3 BT" All bearing trees have a 6" red band painted around the tree and the blazed face painted red. U.S.F.S. sign 54-3, BEARING TREE, and sign 54-9, LAND SURVEYING MONUMENT, are nailed to all bearing trees. All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown, and distances are measured to the root crown at the side and center of the tree. Bearings and distances were measured with a staff compass (Decl. 17°E.) and steel tape.

1/21/92

259

South 1/4 Corner for Section 4

Found - A 2½" Iron post by Peterson and Berry in 1971, firmly set, projecting 9" above ground with a 3½" U.S.B.L.M. brass cap.

12" x 4½ ft. high cut madrone stump bears N.49°30'W., 44.0 ft. with a healed blaze. (N.52°W., 67 lks.) Corbin, 1957

A 42" Cedar stump bears N.18°W., 34.9 ft. with a chopped open face. Unknown origin.

12" D.Fir bears N.20°E., 16.6 ft. with a healed blaze. (Record, N.18°E., 25½ lks.) Peterson/Berry, 1971

New BT - 14" D.Fir bears N.73°15'W., 100.0 ft. scribed "1/4 S4 BT".

All bearing trees have a 6" red band painted around the tree and the blazed face painted red. U.S.F.S. sign 54-3, BEARING TREE, and sign 54-9, LAND

Kristian DeGroot PLS #1941  
For: U.S.F.S.  
January, 1992  
C.S. File 63/138

FD OK David Edwards 3/2001 M 136-69  
CS 65/34-5