

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. R2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

259

Cont - -

Kris DeGroot  
Jan. 22, 1992

SURVEYING MONUMENT, are nailed to all bearing trees. All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown, and distances are measured to the root crown at the side and center of the tree. Bearings and distances were measured with a staff compass (Dec. 17°E) and steel tape.

1/4 Corner for Section 12 only (east)

Found - 2 1/2" dia. Brass cap. on a 1 1/4" O.D. iron pipe, protrudes 2" above a 2 ft. dia. mound of stone. **260**  
12" now 16" dia. D.Fir with a fully healed single blaze bears N.4°W., 18.0 ft. (rec. N.4°W., 18.6 ft.)  
5" now 5" dia. Cedar with a partially healed double blaze, scribed visible "1/4 S12 CS BT" bears N.41 1/2°W., 15.8 ft. see ren. #257

BT's in slide area -

6" now 10" dia. D.Fir with a fully healed single blaze, bears S.50 1/2°W., 48.6 ft. (rec. S.49°W., 46.8 ft.)  
8" now 8" dia. D.Fir with a partially healed double blaze, scribing visible "1/4 S12 CS BT" bears S.62°W., 54.2 ft.  
32" dia. D.Fir with BT tag on ground numerous axe mark and blazes or scribing dated by ring count approx. 30 yrs old. Tag marked "1/4 S12 only on new BT Hendrikson S.33°W., 56.8 ft" bears S.37 1/2°W., 66.5 ft. (unrecorded BT?)

New Accessories -

20" dia. D.Fir double blazed and scribed "1/4 S12 CS BT" bears N.82°W., 118.3 ft.  
10" dia. Cedar double blazed and scribed "1/4 S12 CS BT" bears N.43 1/2°W., 37.7 ft.

1/4 corner for section 7 & 8

Found - County Surveyors Office

261

T27S

1/4 S7|S8 R2W  
1968

2 1/2" Brass cap on a 1" iron pipe, from which a:  
36" D. Fir BT stump, scribes visible, bears N88°E., 63.4 ft.  
38" D. Fir BT, face overgrown, bears N.20°W., 44.2 ft.  
10" D. Fir BT, now a windfall, bears S.75°E., 15.2 ft.  
20" Pine BT, now down, bears S.75°W., 17.2 ft. (rec. 16.9ft.)  
Basalt stone, probable original corner, no mark visible (stone is 14"x12"x10") lies adjacent brass cap.

New Accessories

44" D. Fir BT, I scribed "1/4 S7 BT" bears S.14°W., 76.6ft.  
10" D. Fir BT, I scribed "1/4 S8 BT" bears N.70°E., 31.6ft.  
14" D. Fir BT, I scribed "1/4 S8 BT" bears S.83°E., 25.0ft.  
6 ft. steel post, I set, bears North, 1.0 ft.

Area was logged this year in sec. 7 to the West. Blm road ends N.60°W., 300 ft. from corner

262

1/4 Cor. Secs. 33 & 34

**262**

(Ren 200)

Fd. - 1 1/4" (O.D.) IP, firmly set, projecting 12" above a 18" x 36" mound of stone w/2 1/2" alum. cap, properly marked. From which the OBTs  
28" sawed Fir stump bears N.52°E., 42.1' w/ scribe marks "4 BT" visible. (Rec. N.47°50'E, 63 lks.)  
36" Fir bears S.17°W., 82.3' w/healed blaze (Rec. S.11°50'W., 123 lks)

New BT -

24" D. Fir bears S.77°30'E., 67.2', scribed "1/4 S34 BT" on a double blaze w/ brass washer "PLS 1941" nailed into lower blaze.

I paint a 6" red band & BT faces red & nail USFS "BEARING TREE" & "LAND SURVEY MONUMENT" signs to all BTs

Douglas County Surveyor's Office  
Randall Smith, Stephen Flause  
June 3, 1993 - C.S. File 64/43

Kristian DeGroot, PLS  
#1941  
June 1998  
C.S. File 65/20-31