

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 2 R. W. W. M.

FOX-CHAPMAN CO., EUGENE, ORE. 21881

Kristian DeGroot, PLS
#1941
June 1998
C.S. File 65/20-33

1/4 Cor. Secs. 32 & 33

(Len 209) 263

Fd. - 1 1/4" (O.D.) IP, firmly set, projecting 12" above a 36" dia. mound of stone w/2 1/2" brass cap properly stamped, from which the OBTs

42" sawed fir stump bears N.54°E., 23.8 ft. w/scribe marks "1/4 S33 BT" visible.
(Rec. N.53°40'E., 36 lks.)

42" sawed fir stump bears N.30°W. 5.3 ft. w/scribe marks "1/4 S 32" visible.
(Rec. N.30°10'W., 8 lks.)

21" Hemlock bears N.81°E., 13.9 ft. w/ healed blaze. (Rec. N.80°E., 14.6 ft.)

16" Hemlock snag bears S.44°E., 23.5 ft. w/scribe marks "1/4 S33 CS BT" visible.
(Rec. S45°30'E)

New BT -

13" Hemlock bears S.38°W., 21.2 feet scribed "1/4 S32 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into lower blaze.

I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees.