

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Thomas E. Shrum, Jr.
U. S. Plywood Corp.
January 1965
C. S. File No. 51/254

Thomas E. Shrum, Jr.
For U. S. Plywood Corp.
April 1964
C. S. File No. 51/254
Map File M 29 - 28

Vernon "Ray" Tracy
Jack Heritage & E. West
Dec. 29, 1966
C. S. File No. 54/40

C. C. Sections 10, 15 and 16. 50

Found - Cedar Snag 16" dia., S.55°W. 33.5 ft.
Set - D. Fir Snag 14" dia., S. 71° E. 38.5 ft.
W. Fir 12" dia., N. 34° E., 39.1 ft.
2 1/2" diam., ALUMINUM CAP.

RE-RENEWED, SEE CORNER NO. 121

North 1/4 Corner Section 10 only. (Prop. Measurement) 51

Set - 2 1/2" diam. ALUMINUM CAP.
Hemlock 7" diam., S. 08° E., 38.1 ft.

RE-RENEWED, SEE CORNER NO. #173

1/4 Section Corner, Sections 10 and 11. 52

Found - D. Fir Snag 30" diam., N. 13 1/2° W., 12.1 ft.
Set - 2 1/2" diam. ALUMINUM CAP. Dec. 1968 Fd. O.K. V.R.T.
Hemlock 7" diam., N. 31 1/2° W., 27.3 ft.
W. Fir 7" diam., S. 50° E., 38.6 ft. (See Shrum's Survey
M 37 - 18)

South 1/16 between Sections 11 and 12. 53

Set - 2 1/2" diam., ALUMINUM CAP.
D. Fir 7" diam., N. 76° W., 62.9 ft.
W. Fir 10" diam., N. 40° E., 46.6 ft.

1/4 Corner to Sections 15 and 16. 54

Found - D. Fir 26" diam., N.14°E. 23.1 ft.
D. Fir 16" diam., S.36°W. 10.6 ft.
Set - 2 1/2" diam. Aluminum Cap
Yew 16" diam., N.31 1/2°W. 30.0 ft.
D. Fir 8" diam. S.74 1/2°E. 21.9 ft.

1/4 Corner to Sections 15 and 22. 55

Found - D. Fir 24" diam., S.18°W., down.
Set - 2 1/2" diam. Aluminum Cap
D. Fir 8" diam., N.36 1/2°W. 25.2 ft.
Alder 13" diam., S.81 1/2°E. 25.0 ft.

North 1/4 Corner to Section 15 only. 56

Set - 2 1/2" diam. Aluminum Cap.
D. Fir 6" diam., S.14°E. 1.5 ft.

Center 1/4 Corner to Section 15. 57

Set - 2 1/2" diam. Aluminum Cap
D. Fir 19" diam., S.52°E. 7.2 ft.
D. Fir 9" diam., N. 8°E. 17.6 ft.

Closing Corner Sections 18 and 19 only, T27-2W. 58

Found - Very old, scribed Cedar Post, badly decayed.
Orig. 14", now 16" W. Fir, S. 8 1/2° E. 7.9 ft. Open & find
scribe @R2 W S". Alive.
Orig. 24", now 25" W. Fir, Alive, N. 62 1/2° E. 3.3 ft., shows
good scar. We do not open.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1966

R	T 27 S	R
3	S 18	2
W	S 19	W

New BT's: 8" W. Fir N. 50° E. 12.6 ft. mkd. T27S R2W S18 CC CS BT.
5" W. Fir S. 78° E. 12.5 ft. mkd. T27S R2W S19 CC CS BT.

Note - Brass Cap set 12" in ground & mound of stone 16" high.
This corner lies on flat, approx. 440 ft. S. of Standard Corner.
Dec. 29, 1966