

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

59

Section Corner to Secs. 13 & 24 only, T27-3W.

Found - Orig. 30", now 38" Fir, S. 38° E. 19.1 ft. This BT was  
Obliterated in 1911, retracement of range line, only  
fragmentary bark scribing remaining, " / // U".

N. E. & N.W. BT's, gone, no trace, found a large hole  
where S.W. BT. would have been, old blazes to N. of corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 27 S R  
(Set in mound of Stone) Office 3 S 13 | 2  
1966 W S 24 | W

New BT's: 8" W. Fir S. 67° W. 5.7 ft. mkd. T27S R3W S24 CS BT.  
8" W. Fir N. 70½° W. 15.9 ft. mkd. T27S R3W S13 CS BT.

Note - This corner lies on west slope approx. 440 ft. N. of  
Closing Corner.

Also find 36" Cedar West 38 ft., out of place, axe blazwd  
and fragmentary scribe with good "S". Does not look Orig.

Vernon "Ray" Tracy  
Jack Heritage & E. West  
Dec. 29, 1966  
C. S. File No. 54/40

60

¼ Corner to Sections 1 and 12.

Found - 1957 Co. Surv. Brass Cap & BT's., see Ren. #6.

10", now 11" W. Fir S. 14° W. 15.7 ft. Alive, blaze nearly  
healed.

14" Fir, now down, N. 30½° E. 17.4 ft., scribe visible.

Orig. 8", now 17" W. Fir, Alive, N. 50° W. 4.0 ft.,  
scribe visible.

New BT: 16" W. Fir N. 70½° W. 6.2 ft. mkd. ¼ S 1 CS BT.

Note - This corner lies 200 ft. west of Little River Road.

FOUND O.K. Nov. 1968 V.R.T. March 9, 1967

Sec. Corner to Secs. 1 & 2, T27-2W. & Secs. 35 & 36, T26-2W.

Found - Orig. 12", now 21" Fir, Alive, S. 30° W. 15.8 ft.,  
prev. opened, face burned, fragmentary scribe visible.

Orig. 10", now 19" Fir, Alive, N. 39½° E. 11.9 ft.,  
previously opened. We open all of upper blaze & find,  
@T26S R2W S36" scribe.

Orig. 24", now 30" Fir, Alive, N. 30° W. 34.3 ft., shows  
good scar. Do not open.

Orig. BT. obliterated by Mensch, 1916, alive & opened  
to axe blaze, bears N. 11° W. 9.2 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's T26S S 35 | S 36 R2W  
Office, 1967 T27S S 2 | S 1

New BT's: 16" D. Fir S. 79½° E. 88.7 ft. mkd. T27S R2W S1 CS BT.

14" D. Fir N. 4° E. 6.0 ft. mkd. T26S R2W S36 CS BT.

18" D. Fir S. 19° W. 19.7 ft. mkd. T27S R2W S2 CS BT.

No trace of any other Orig. BT's., nor Corner Stone.

March 9, 1967

FD OK 4/84 GEISLER  
M 90-55

61

¼ Corner to Sec. 31, T26-2W. & Sec. 6, T27-2W.

Found - Orig. 24", now 33" Fir, N. 78° E. 49.5 ft. Alive, shows good scar.

Orig. 24", now 36" Fir, sawed stump, S. 12° E. 26.4 ft. Open  
& find "S6BT" reverse scribe under 41 yrs. overgrowth.

(These BT's. were apparently rescribed about 1913 during the  
last retracement of the S. line of T26-2W.)

Set - Brass Cap at Cor. Mkd: County Surveyor's S 31 T26S R2W  
Office, 1967 S 6 T27S

New BT's: 17" Cedar S. 85° E. 83.3 ft. mkd. ¼ S 6 CS BT.

10" Cedar N. 23° E. 29.3 ft. mkd. ¼ S 31 CS BT.

62

Sec. Corner to Secs. 31 & 32, T26-2W. & Secs. 5 & 6, T27-2W.

Found - Old 3" sq. cedar post - Orig. 12", now 22" Cedar, alive,  
S. 80° W. 11.9 ft., shows good scar. do not open &  
Rescribe: "T27S R2W S6 CS BT".

Orig. 16", now 30" Cedar, alive, N. 45° W. 21.1 ft., shows  
scar, do not open. Rescribe "T26S R2W S31 CS BT".

Orig. 12", now 24" Cedar, N. 80° E. 23.8 ft., alive, prev.  
opened, face rotted, no scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's S 31 | S 32 T26S R2W  
Office, 1967 S 6 | S 5 T27S

New BT's: 11" Cedar N. 69° E. 36.5 ft. mkd. T26S R2W S32 CS BT.

18" Cedar S. 20° E. 24.8 ft. mkd. T27S R2W S 5 CS BT.

Note - This corner lies at cutting corner, cut off in section 6.

July, 1967

Vernon "Ray" Tracy  
Jack Heritage & E. West  
C. S. File No. 54/40

63