

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

RENEWED CORNER NO. #224

64

$\frac{1}{4}$ Corner to Sec. 35, T26-2W. & Sec. 2, T27-2W.
Found - No trace of corner stone nor S.E. BT. Call of 26 lks. on bluff 15' high on line, fits good.
Orig. 40", now 40" Fir Snag, 20' high, N. 4° W. 29.7 ft., shows "S35BT" on burned unhealed blaze, mkd. by Collier, 1913.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{1}{4}$ S 35 T26S R2W
(Set in mound of stone) Office, 1967 S 2 T27S
New BT's: 5" D. Fir N. 63° W. 9.2 ft. mkd. $\frac{1}{4}$ S35 CS BT.
2" D. Fir S. 11° W. 3.3 ft. mkd. $\frac{1}{4}$ S 2 CS BT.
Note - This corner lies on very steep, E. slope 225' W. of creek.

65

Section Corner to Secs. 34 & 35, T26-2W. & Secs. 3 & 2, T27-2W.
Found - 1957 Cadastral Brass Cap & Orig. Corner Stone.
13", now 15" Fir, N. 25 $\frac{1}{2}$ ° E. 25.7 ft. alive, healed blaze.
13", now 13" Fir, down, S. 43° E. 49.5 ft., scribe visible on unhealed blaze.
13", now 16" Fir, S. 29 $\frac{1}{4}$ ° W. 57.4 ft. alive, healed blaze.
10", now 14" D. Fir (not W. Fir) N. 76° W. 73.9 ft. alive, healed blaze.
29", now 15" Laurel, S. 82° E. 55.4 ft. alive, healed blaze., do not open healed blazes. Only orig. SE BT. standing.
New BT: 15" D. Fir S. 75° E., 20.2 ft. mkd. T27S R2W S2 CS BT.
Note - This corner lies on top of spur, ridge sloping south at old cutting corner, Sections 35 - 2 - 3 cut off.

66

$\frac{1}{4}$ Corner to Sec. 32, T26-2W. & Sec. 5, T27-2W.
Found - Orig. 20", now 22" Laurel, N. 35° W. 4.6 ft., alive, scribe visible on unhealed blaze.
Orig. 20", now 32" Fir, S. 35° E. 19.8 ft. alive, bark scribe, "B" in fair condition.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{1}{4}$ S 32 T26S R2W
Office, 1967 S 5 T27S
New BT's: 12" D. Fir N. 8° W. 12.8 ft. mkd. $\frac{1}{4}$ S32 CS BT.
20" W. Fir S. 8° W. 9.0 ft. mkd. $\frac{1}{4}$ S 5 CS BT.
Note - This corner lies on top of ridge, sloping South & E-W cutting line. Cut off to North.

67

Sec. Cor. to Secs. 32 & 33, T26-2W. & Secs. 4 & 5, T27-2W.
Found - Orig. 12", now 30" Cedar, N. 57° E. 23.8 ft. alive, shows good scar. We do not open.
Orig. 10", now 18" Fir, S. 67° E. 18.5 ft., alive, scribe visible on opened blaze.
Orig. 40", now 50" Fir, N. 30° W. 8.6 ft., alive, shows poor bark scribe "TS3 BT".
Orig. 8", now 12" Fir Snag, S. 40° W. (record S. 35° W.) 3.3 ft. Open & shows "T27S R2W S5" scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{1}{4}$ S 32 | S 33 T26S R2W
Office, 1967 S 5 | S 4 T27S
New BT's: 26" Cedar N. 36° W. 37.1 ft. mkd. T26S R2W S32 CS BT.
14" Cedar N. 24° E. 31.2 ft. mkd. T26S R2W S33 CS BT.
5" D. Fir S. 59° E. 25.6 ft. mkd. S 4 CS BT.
9" Cedar S. 21° W. 21.4 ft. mkd. T27S R2W S5 CS BT.
Note - This corner lies 20 ft. S. of creek, 2 ft. wide, course S.

68

$\frac{1}{4}$ Corner to Sec. 33, T26-2W. & Sec. 4, T27-2W.
Found - Orig. 20", now 38" Cedar Snag, S. 53° W. 18.5 ft. (not S. 57° W.) Scribe visible on opened blaze.
Orig. 36", now 48" Fir, N. 55° E. 18.5 ft. alive, bark scribe, poor.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{1}{4}$ S 33 T26S R2W
Office, 1967 S 4 T27S
New BT's: 8" W. Fir N. 45° E. 4.8 ft. mkd. $\frac{1}{4}$ S33 CS BT.
9" W. Fir S. 56° W. 43.1 ft. mkd. $\frac{1}{4}$ S 4 CS BT.
Note - This corner lies on old E-W cutting line, selective logging to south.

Vernon "Ray" Tracy
Jack Heritage & E. West
July, 1967
C. S. File No. 54/40

POK 4/88
BY GEISLER
M 90-55