

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

74

Section Corner to Sections 15 - 16 - 21 - 22.  
Found - Unrecorded 3/4" Iron Rod at Corner Point.  
Orig. 24", now 40" Cedar N.68°E. 3.5 ft. (Rec. 132.7 ft.) Alive,  
prev. opened, shows scribe marks, 55+ yrs. ring count.  
Orig. 18", now 24" Cedar, S.15°E. 46.2 ft. (Rec. S.25°E.). We open  
& find scribe under 55+ yrs. ring count.  
Orig. 12", now 21" Fir, alive, S.19°W. 46.9 ft., shows good scar.  
We do not open.  
Orig. 30", now 36" Fir, alive, N.47 1/3°W. (Rec. N.53°40'W.) 67.3 ft.,  
scribe visible on unhealed & decaying blaze.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W  
(Reset I.R. alongside) Office S 16 S 15  
1968 S 21 S 22  
New BT's: 11" W. Fir N. 69° W. 30.2 ft. mkd. T27S R2W S16 CS BT.  
11" W. Fir S. 52° W. 25.0 ft. mkd. T27S R2W S21 CS BT.  
12" W. Fir S. 81° E. 29.1 ft. mkd. T27S R2W S22 CS BT.  
11" Cedar N. 21° E. 23.2 ft. mkd. T27S R2W S15 CS BT.

SEPT 68

75

Section Corner to Sections 25 - 26 - 35 - 36.  
Found - U.S. Plywood Alum. Cap, properly marked, See Ren. #36.  
Orig. 26" Fir Stump S.49°W. 5.6 ft., good orig. scribe visible.  
Orig. 36" Fir Stump N.55°W. 20.0 ft. Rescribed: "S26 BT".  
Orig. 18" Yew S. 65 1/2° E. 26.7 ft., alive. Rescribed: "S35 BT".  
22" Fir Stump N. 15 1/2° W. 12.1 ft. mkd: "S25 BT". (Shrum's new BT)  
New BT: 15" Hemlock S.62°W. 32.7 ft. mkd: T27S R2W S35 CS BT.  
Set - 6' Steel Fence Post alongside alum. cap. No live trees N. of corner.  
This corner lies N.E. slope. Clear cut in sections 25, 26 and 35.

RE-RENEWED CORNER NO. #205

Vernon "Ray" Tracy  
Jack Heritage & V. Perron  
Sept. & Oct. 1968  
C. S. File No. 54/40

76

Section Corner to Sections 28 - 29 - 32 - 33.  
Found - 1 1/2" I.P. with U.S. Plywood Alum. Cap on 1" Pipe inside, See Ren. #21.  
Orig. 12", now 16" Cedar, alve, N.55°W. 27.7 ft., old scribe visible  
on open blaze, recorded in Ren. #21 as being 19.1 ft.  
9" Cedar N.26 1/2°E. 40.5 ft., nearly dead, scribe visible.)  
44" D.Fir Stump S.30°E. 61.5 ft., scribe visible. ) Shrum's BT's.  
16" D.Fir N.31°W. 24.9 ft. mkd: T27S R2W S29 CS BT" )  
Set - 6' steel fence post alongside aluminum cap.  
Corner falls in dense entanglement of greasewood & willow on S. side  
of old cat skid road.

77

1/4 Corner to Sections 27 and 28.  
Found - 2 1/2" Alum. Cap mkd: "1/4 S27/S28, should be S28/S27.  
with 1 1/2" I. P. alongside, See Ren. #22.  
Orig. 24" Fir, now 28" Stump, N.84 1/2°E. 14.5 ft., scribe visible on old blz.  
Original S.W. Bearing Tree gone.  
24" Fir Stump S.28°W. 34.5 ft. scribed "1/4 S28 BT" (U.S. Plywood BT)  
Set - 6 ft. steel fence post alongside Alum. cap.  
New BT's: 6" D.Fir S. 4° W. 103.3 ft. mkd: "1/4 S28 CS BT".  
48" Fir Stump N.13°E. 26.2 ft. mkd: "1/4 S27 CS BT. (8' high stump)  
10/16/68

78

Standard Corner to Sec. 36, T27-2W and Sec. 31, T27-1W.  
Found - No trace of Corner Stone or Mound of Stone called for.  
Orig. 16", now 38" Fir N.71°W. 40.9 ft., shows faint scar. We open  
& find scribe marks.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W S 36/S 31 R1W  
Office, 1968 T28S  
New BT's: 16" D.Fir N.61°E. 34.0 ft. mkd: T27S R1W S31 SC CS BT.  
Orig. 38" R.Fir N.71°W. 40.9 ft. mkd: T27S R2W S36 SC CS BT.  
This corner lies on very steep, southerly slope about 300 ft. S. of  
high rock bluff. The Cl. Cor. of T28S, R's. 1 & 2 W. bears west 413 ft.

79

1/4 Corner to Sec. 31, T27-1W. and Sec. 36, T27-2W.  
Found - Corner Stone mkd: "1/4" on west face, firmly set at corner point.  
Orig. 14", now 36" Hemlock, alive, S.49°E. 51.5 ft., shows faint  
scar. Recorded to be Fir. Rescribe: "1/4 S31 CS BT".  
Orig. 20", now 40" Hemlock, alive, N.78°W. 68.6 ft., shows "1/4" on open  
blaze. Rescribe: "1/4 S36 CS BT".

(continued over)