

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

Vernon "Ray" Tracy
J. Heritage & V. Perron
October, 1968
C. S. File No. 54/40

North $\frac{1}{4}$ Corner to Section 2 only, T28-2W. 85
Found - 1923 GLO Brass Cap, in place & properly marked.
40", now 46" Fir, dead, S. 41° E. 35.6 ft., scribe visible "S2 BT".
10", now 13" Yew, alive, S. 16° W. 18.5 ft., good condition, scribe vis.
New BT: 7" D. Fir S. 26 $\frac{1}{2}$ ° E. 25.0 ft. mkd: " $\frac{1}{4}$ S2 CS BT".
This corner lies on south slope about 310 ft. W. of Angle Point 148
on south line of Sec. 35, T27-2W, see corner below.

Angle Point on South Line of Section 35, T27-2W. 86
This corner lies on steep east slope approx. 310 ft. east of
N $\frac{1}{4}$ corner, Sec. 2, T28-2W, see corner above. # 254
Found - Orig. 24", now 28" Hemlock, alive, N. 67° E. 13.9 ft., scribe
vis. on unhealed blaze. Rescribe: "AP CS BT".
Orig. 7", now 9" Yew, dead & broken off 4' above ground,
N. 17° W. 10.6 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R2W A P
Office, 1968 T 28 S
New BT: 50" D. Fir N. 1° W. 13.2 ft. mkd: "A P CS BT". FOUND O.K. 6/28/72 V.E.T.

Standard Corner to Sections 35 and 36, T27-2W. 87
Found - Orig. BT's. by 40" Fir Snag, 40' high, N. 58° E. 36.3 ft., scribe vis.
10", now 16" Fir, alive, N. 84° E. 40.9 ft., shows scar.
Rescribe: "T27S R2W S35 SC CS BT".
7", now 22" Fir, alive, N. 1° W. 44.2 ft., scribe visible on open blaze
Rescribe: T27S R2W S36 SC CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S S 35 | S 36
Office, 1968 T 28 S R2W
This corner lies on east side of Red Butte Lookout Road.
Fd. OK 8/2/76 - L. LADIG - SURVEYORS OFFICE C.S. 59/18

Angle Point btwn. Sec. 34, T27-2W. and Sec. 2, T28-2W. 88
Found - Unrecorded U.S. Ply. Alum. Cap Mkd. A.P., set from Orig. BT's.,
both out of ground, scribing visible on N.W. Orig. BT.
No trace of new bearing trees.
Set - 6 ft. Steel Fence Post alongside Alum. Cap. # 194
New BT's: 6" Yew N. 14° E. 18.0 ft. mkd: "A.P. CS BT".
12" W. Fir S. 81° E. 53.4 ft. mkd: "A.P. CS BT".
This corner lies 120 ft. west of C.C. Secs. 34 & 35, T27-2W in flat
logged-off unit. (Rec. Dist. btwn. Cors. 112.3 ft.)

West $\frac{1}{4}$ Corner to Section 7 only, T27-1W. 89
Found - Corner Stone mkd: "X" on top & " $\frac{1}{4}$ " on W. face, firmly set.
Orig. 24", now 38" Pine, alive, S. 18° E. 42.9 ft., open & find scribe.
Orig. 24", now 30" Pine Stump, N. 31° W. 55.4 ft., shows scribe on open blaze.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W $\frac{1}{4}$ | S 7 R1W
(Set old Cor. Stone alonged) Office, 1968
New BT's: 13" W. Fir S. 24° E. 12.0 ft. mkd: " $\frac{1}{4}$ S7 CS BT".
11" W. Fir N. 52° E. 16.8 ft. mkd: " $\frac{1}{4}$ S7 CS BT".

Wit. Cor. Closing Corner Sections 25 and 36, T27-2W. 90
Found - No trace 1962 C.S. Brass Cap due to 1964 flood, Ren. #11.
Orig. 12" Hemlock, alive, N. 76° W. 25.1 ft., scribe visible.
Orig. S.W. BT. gone, due to logging
20" Hemlock, alive & O. K., S. 22° W. 42.3 ft.
19" R. Cedar, alive & O. K., N. 64° W. 23.0 ft.
We measure 25 ft. W. from true corner & at point set Witness Corner:
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W S 25 | CC R1W
Office S 36
1968 Wit. Cor. 25' E. to Corner.
Rescribed BT's: 20" Hemlock S12° E. 40.0 ft. mkd: W.C. T27S R2W S36 CCCSBT.
19" R. Cedar N23° E. 12.0 ft. mkd: WC T27S R2W S25 CC CS BT.
True corner falls in center of creek, 25 ft. E. of Wit. Cor.
This corner bears S. 19° W. 99.4 ft. from W.C. Secs. 30 & 31, T27-1W.