

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

104

Sec. Cor. to Secs. 2 & 1, T27-3 and Secs. 35 & 36, T26-3.
Found - 1958 Cadastral Brass Cap Mkd. & BT's., as follows:
20" Fir N. $51\frac{1}{2}^\circ$ E. 43.6 ft. alive & in good condition,
nearly healed blaze.
12" Cedar S. $73\frac{1}{4}^\circ$ E. 58.6 ft., alive & in good condition.
(recorded S. $73\frac{1}{4}^\circ$ W.)
20" D. Fir S. $30\frac{1}{4}^\circ$ W. 40.3 ft. alive & in good condition.
13" D. Fir, uprooted & dead, N. 34° W. 38.9 ft.
See Ren. #16 for BT's. mkd. in 1936, now stumps & snags.
New BT: 18" Cedar N. 45° W. 25.3 ft. Mkd: T26S R3W S35 CS BT.
Note- Corner lies in swampy area.

Vernon "Ray"
Tracy & Crew
Feb. 17, 1966
C. S. File
No. 54/7

105

Closing Corner to Sections 18 and 19 only, T27-2W.
Found - Very old, scribed Cedar Post, Badly decayed.
Orig. 14", now 16" W. Fir, alive, S. $8\frac{1}{2}^\circ$ E. 7.9 ft. Open
& find scribe "R 2 W S".
Orig. 24", now 25" W. Fir, alive, N. $62\frac{1}{2}^\circ$ E. 3.3 ft., shows
good scar. We do not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 27 S R
Office 3 CC S 18 2
1966 W S 19 W
New BT's: 8" W. Fir N. 50° E. 12.6 ft. mkd. T27S R2W S18 CC CS BT.
5" W. Fir S. 78° E. 12.5 ft. mkd. T27S R2W S19 CC CS BT.
Note - Brass Cap set 12" in the ground with Mound of stone 16" high.
This corner lies on flat, approx. 440 ft. S. of Standard Corner.
12/29/66

Vernon "Ray" Tracy
Jack Heritage & Elmer West
12/29/66
C. S. File No. 54/7

106

Section Corner to Secs. 13 and 24 only, T27-3W.
Found - Orig. 30", now 38" Fir, S. 38° E. 19.1 ft. This BT. was
obliterated in 1911 retracement of range line, only
fragmentary bark scribing remaining, " ^ // U".
N.E. & N.W. BT's. gone, no trace. Found a large hole where
S.W. BT. would have been, old blazes to N. of corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 27 S R
Office 3 S 13 2
1966 W S 24 W
New BT's: 8" W. Fir S. 67° W. 5.7 ft. mkd. T27S R3W S24 CS BT.
8" W. Fir N. $70\frac{1}{2}^\circ$ W. 15.9 ft. mkd. T27S R3W S13 CS BT.
Note - This corner lies on west slope approx. 440 ft. N. of C. C.
Also find 36" Cedar West 38 ft., out of place, axe blazed
& frag. scribe with good "S". Does not look like original
12/29/66

MICROFILM TO HERE 10/67

107

Sept. 68

$\frac{1}{4}$ Corner to Sec. 7, T27-2W. and Sec. 12, T27-3W.
Found - $\frac{1}{2}$ " I. Rod & BT's. as recorded in Ren. #62.
10", now 12" D. Fir, alive, S. 57° W. 26.5 ft. blaze nearly healed over
6", now 8" D. Fir, alive, S. 11° E. 21.0 ft. scribe visible on
partially healed blaze.
Orig. N.W. BT., now burned out stump, no scribe, only
opening facing corner point.
Set - Brass Cap at Cor. Mkd: County Surveyor's
(Reset I.R. alongside) Office, 1968 T27S R3W $\frac{1}{4}$ S12 | S 7 R2W
This cor. lies on N-S fence line 50' S. left bank Little River.

RE-RENEWED, SEE CORNER NO. #139

$\frac{1}{4}$ Corner to Sections 13 and 14. 108
Found - Mound of Stone but no marked stone as called for in Ren. #8.
Orig. 32", now 48" Fir, alive, N. 45° W. 19.8 ft., bark scribed.
Orig. 36", now 52" Fir, alive, S. 50° E. 19.1 ft., frag. bark scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 3 W
Office, 1968 $\frac{1}{4}$ S 14 | S 13
New BT's: 8" R. Fir S. 27° E. 10.5 ft. mkd: $\frac{1}{4}$ S13 CS BT.
8" R. Fir N. 57° W. 7.0 ft. mkd: $\frac{1}{4}$ S14 CS BT.
This corner lies on moderate S.W. slope approx. 200 ft. S. of Wolf
Creek access road.
11/4/68

FOB.C
W. Rogers
8/2001
2001-00924-5