

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

116

John M.  
Powell &  
Crew  
C.S. File No.  
54/40

$\frac{1}{4}$  Corner to Sections 3 and 10.  
Found - 16", now 23" D. Fir, N.20°E. 2.0 ft., faint bark scribe.  
14" D. Fir, now stob, S.60°W. 5.9 ft. (Dist. to face of BT's.)  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 3 W  
Office S 3  
1969 S 10  
New BT: 10" Cedar S.55°E. 14.5 ft. mkd: " $\frac{1}{4}$  S10 CS BT".  
Reblzd. & Resbd: 23" D. Fir N.20°E. 2.6 ft., to center, mkd: " $\frac{1}{4}$  S3 CS BT".

10/8/69

117

Section Corner to Sections 25 - 26 - 35 - 36.  
Found - 16" Laurel, now 18", burnt out, N.80°E. (Rec. N65E) 31.0 ft.  
has very good face, burnt off.  
14" Laurel, now 17", S.53°E. 43.6 ft. opened for faint but  
definite scribe marks on rotted face.  
No trace of S.W. or N.W. BT's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 3 W  
Office S 26 | S 25  
1970 S 35 | S 36  
New BT's: 39" D. Fir S.74°E. 65.0 ft. mkd: T27S R3W S36 CS BT.  
6" D. Fir S.58°W. 7.9 ft. mkd: T27S R3W S35 CS BT.  
6" Laurel N.49°W. 4.3 ft. mkd: T27S R3W S26 CS BT.  
8" Laurel N.33°E. 10.7 ft. mkd: T27S R3W S25 CS BT.

7/30/70

118

$\frac{1}{4}$  Corner to Sections 15 and 22.  
Found - 36", now 40" D. Fir, S.45°W. 33.0 ft., faint bark scribe " $\frac{1}{4}$ ".  
No trace of N. E. BT., 12" Laurel.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 3 W  
Office S 15  
1970 S 22  
New BT's: 7" D. Fir N.44°W. 11.2 ft. mkd: " $\frac{1}{4}$  S15 CS BT".  
7" D. Fir S.35°E. 7.9 ft. mkd: " $\frac{1}{4}$  S22 CS BT".  
As noted in calls, this corner lies 2 ch. E. of ridge top.

8/4/70

119

$\frac{1}{4}$  Corner to Sections 24 and 25.  
Found - 12" White Fir, now down, N.3°E. 15.4 ft., found fragments  
of reverse scribing.  
48" D. Fir, now 60" Snag, S.20°E. 23.1 ft., bark scribe visible " $\frac{1}{4}$  BT".  
No tree N.53°W. 28. lks. (18.5)  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 3 W  
Office S 24  
1970 S 25  
New BT's: 10" Cedar N.67°W. 14.8 ft. mkd: " $\frac{1}{4}$  S24 CS BT".  
9" Cedar S.22°W. 20.9 ft. mkd: " $\frac{1}{4}$  S25 CS BT".

8/5/70

120

Victor M.  
McLind  
For Mackey  
C. S. File  
No. 55/169

Center of Section 10.  
Set - 5/8" I. Rod at center of Section 10.  
Blazed and Scribed Bearing Trees, as follows:  
12" W. Fir bears N. 45° W. 14.4 feet  
9" W. Fir bears N. 63° E. 34.8 feet.

November, 1970

MARCH 71

121

Ronald E. Stuntzner  
For: Reservation  
Ranch  
May 12, 1975  
C.S. 58/53

$\frac{1}{4}$  Corner for Sections 5 and 4.  
Set - 3/4 Iron pipe for 1/4 corner  
From which I scribe:  
8" Madrone, bears N.56°W. 37.7 ft.  
6" Oak, bears N.65°E. 81.4 ft.  
8" Oak, bears S.68°E. 65.4 ft.

5/12/75

RE-RENEWED, SEE CORNER NO. #125

See BLM Opinion  
dated May 22, 2001  
CS 63/166