

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

1/4 Corner for Sec. 19 only. West boundary. 129  
Found - 1917 GLO brass cap on 1" I.P. 20" long loosley set alongside  
the broken lower portion of the 1917 I.P. B.C. properly mkd.  
A 40" D. Fir now 54" blowdown, bears N.13°E., 13.9 ft. We  
open well healed blaze and find plain scribe marks.  
The remains of a 50" D. Fir now 54" rotten snag 10 ft. tall,  
bears S.87°E., 34.3 ft. No markings found.  
Set - At the location of the found 1917 iron post we set a 1" x 30"  
I.P. 27" in the ground with brass cap attached marked:  
Douglas County Surveyor  
1977

T	27	S	
	S	19	R
		1/4	3
			W

and deposit remains of 1917 iron post alongside.  
New BT's-An 18" D. Fir double trunked at the base bears N.69°W., 39.2 ft.  
scribed "W 1/4 S19 R3W CS BT" on a double blaze.  
A 10" Hemlock bears N.53°E., 32.0 ft. scribed "1/4 S19 CS BT"  
on a double blaze.

Gary L. Langlitz  
Stephen J. Flause  
Doug. Co. Surveyors  
Office  
Sept. 19, 1977  
C.S. 59/40

9/19/77

Section corner for Secs. 7, 8, 17 and 18. 130  
Set - Brass cap  
BT's - 24" D. Fir bears S.5°E., 12.5 ft. scribed T27S R3W S17 BT.  
40" Cedar bears N.67°30'E., 131.0 ft. scribed T27S R3W S8 BT.  
12" Cedar bears S.81°15'W., 94.3 ft. scribed T27S R3W S18 BT.  
No trees in section 7. See Also Ren. #47

RE-RENEWED CORNER NO. #153

Glenn S. Baughman  
For: Teeco  
Sept. 1978  
M 73 - 56  
M 74-29

9/78

Township corner for Sec. 36; and Sec. 31 of T.27-2; Sec. 1 of T.28-3;  
and Sec. 6 of T.28-2. 131  
Found - 1" iron pipe with 1962 County brass cap. Ren. #67  
11" D. Fir, N.14°W., 19.7 ft. good scar  
14" Madrone snag, S.3°E., 17.0 ft. visible scribes.  
22" Cedar, S.27°W., 72.8 ft. visible scribes.  
New BT - 7" D. Fir, N.27°E., 35.3 ft. "T27S R2W S31 BT".  
Set fiberglass post 3.0 ft. south. BT has brass washer RLS 1005 in face.  
3/80

RE-RENEWED CORNER NO. #149

Ronald A. Quimby  
BHW, Engineering  
For: U.S. Forest  
Service  
March 1980  
M 79 - 37

132

1/4 corner for Sec.'s 23 & 24.  
Found - Brass Cap, firmly set, protruding 6" out of Ren. #25.  
the ground and marked: County Surveyors Office 1/4 S 23 24  
BT's - 36" Fir (Orig. 18"), alive, with well healed blaze, bears  
N.43°E., 19.1-ft. (REC 18.5-ft.).  
26" Cedar (Orig. 14"), now a snag, 7-ft. tall, hollow & burned  
with no face visible, bears N.78°W., 18.0-ft. (REC 16.5-ft.)  
Ground is very steep which could account for the discrepancies  
in the distances.  
New BT's- 6" Fir bears S.26°E., 20.7-ft., scribed 1/4 S24 CS BT.  
10" Fir bears N.13°E., 9.2-ft., scribed 1/4 S23 CS BT.  
7" Fir bears N.45°W., 18.9-ft., scribed 1/4 S23 CS BT.  
\*NOTE - All new BT's scribed on double blazes.  
\*NOTE - All BT's have DCSO BT tags.

Gregory E. Quibell  
Deputy, Doug. Cou.  
Surveyor  
Debbie Stewart,  
witness  
July 28, 1981  
C.S. 61 / 27

7/28/81

133

Center 1/4 for Sec. 23.  
Found - Brass Cap, firmly set, protruding 12" out Ren. # 29.  
of the ground and marked: County Surveyors Office C 1/4  
BT's - 13" Fir (Orig. 12"), down with well healed double S 23  
blaze bears S.28°W., 45.4-ft. (REC S.30°W., 44.4-ft.) to  
the stump hole. Ren. # 29.  
20" Fir (Orig. 10") stump, cut low with possible partial  
blaze bears N. 6° E., 46.1-ft., (REC N.3°E., 45.9-ft.)  
New BT's- 10" Fir bears N.14°W., 34.5-ft., scribed: C 1/4 S23 CS BT.  
12" Fir bears N.41°E., 41.4-ft., scribed C 1/4 S23 CS BT.  
10" Fir bears S.3°E., 12.0-ft., scribed C 1/4 S23 CS BT.  
14" Fir bears S.32 1/2 °W., 50.7-ft., scribed C1/4 S23 CS BT.  
\*NOTE - All new BT's scribed on double blazes.  
\*NOTE - All BT's have DCSO BT tags.

Gregory E. Quibell  
Deputy, Doug. Co.  
Surveyor  
Debbie Stewart,  
witness  
July 28, 1981

7/28/81

*Fl. by BENTE  
March, 1984 M 96-28  
7/90 M 110-37  
11/93 M 118-16  
8/95 1995-0102 A/B  
K. DeGroot*