

**Douglas County Surveyor's Record of
Government Corners Renewed**

T.27S. T. S. R.3W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

*FOOK M. Heimbarger 11/26-11
11/96*

134

1/4 Corner for Sections 26 and 27
 Found - 1963 Alum. cap and iron pipe set by RE 4287. Ren. #90
 50" fir stump bears S.51°E., 6.4 ft. (Rec. S.55°E. 3.3 ft. to face). No scribing found. (original)
 15" yew bears N.40°E., 36.6 ft. (Rec. 38.6 ft.) Scribe marks visible (1963)
 27" fir stump bears S.52°W., 22.0 ft. No scribing evident. (unrecorded)
 New BT - 8" fir bears N.82°W., 37.2 ft. scribed: 1/4 S27 BT.

135

1/4 Corner for Sections 26 and 35
 Set - 2 1/2" alum. cap set on a 1" x 36" iron pipe, properly stamped and with PLS 1988.
 New BTs - 23" fir bears N.81°W., 16.4 ft. scribed: 1/4 S26 BT.
 13" maple bears S.55°W., 33.8 ft. scribed: 1/4 S35 BT.

136

Section Corner for Secs. 27, 26, 35 and 34.
 Found - 1963 Alum. cap and iron pipe set by RE 4287. Ren. #81
 9" dead yew bears S.85°W., 63.7 ft. (Rec. 64.0 ft.) scribed S34 RE 4287 BT. (1961)
 36" cedar stump bears N.75°E., 85.6 ft. scribe marks visible.
 10" cedar snag, 12 ft. tall bears S.39°E., 89.3 ft. (Rec. S.34°E., 88.6 ft.) scribed S35 RE 4287 BT. (1961)
 12" yew bears N.45°W., 84.3 ft. scribed S27 RE 4287 BT. (1961)
 26" dead cedar bears N.18°W., 22.5 ft. (Rec. N.16°W.) Found a 1957, 4" x 6" alum. tag but no scribing)
 21" fir stump bears S.37°W., 42.0 ft. (Rec. S.39°W.) No scribing or alum. tag found. (1957)
 New BTs - 9" fir bears S.72°W., 48.1 ft. scribed: T27S R3W S34 BT.
 6" fir bears S.32°E., 80.3 ft. scribed: T27S R3W S35 BT
 6" fir bears N.81°E., 71.1 ft. scribed: T27S R3W S26 BT
 3/4" iron rod bears S.56°W., 0.28 ft. from the cap.

*FOOK D Edwards 137
2/2002 CS 65/4-4*

Section corner for Secs. 25, 26, 36 and 35
 Found - 1970 Douglas County brass cap on iron pipe. Ren. #117
 9" laurel bears N.33°E., 10.4 ft. (Rec. 10.7 ft.) scribed T27S R3W S25 CS BT.
 7" laurel bears N.49°W., 4.3 ft. scribed T27S R3W S26 CSBT.
 8" fir bears S.58°W., 8.2 ft. (Rec. 7.9 ft.) Closed face.
 43" fir stump bears S.74°W., 64.7 ft. (Rec. 65.0 ft.) Scribe marks visible.
 22" laurel, portion of the base burnt out, bears N.80°E., 29.8 ft. (Rec. N. 65°E., 31.0 ft) No scribing. (Original)
 20" laurel stump bears S.53°E., 42.7 ft. (Rec. 43.6 ft.) No scribing. (original).
 New BT - 7" canyon live oak bears S.71°E., 24.5 ft. scribed: T27S R3W S36 BT.

138

1/4 Corner for Sections 2 and 11.
 Not found - Rock mound, Ren. #23, no longer evident.
 3/4" iron bar, pin or pipe as recorded in Ren. #23, #33 and 1958 dependent resurvey is not found.
 Original BTs searched for, not found.
 BTs per Ren. #23, searched for, not found.
 Found - 1958 BLM 3 1/4" disk on a 2 1/2" I.P., properly mkd., is firmly set and protrudes 6" above ground.
 At west edge of BLM monument, a 5/8" dia. I.R. is firmly set and protrudes 18" above ground.
 10" W. Oak, now a 14" D.B.H. W. oak bears S.06 1/4°W., 119.6 ft. (Rec. S.08 1/4°W., 119.0 ft.) This tree has a well healed single blaze, no scribing visible. Ren. #33
 A 14" cedar, now a 15" dia. 4 ft. tall cedar stump with the scribing 1/4 cor 1 sec 2 BT visible in an opened single blaze, bears S.86°E., 64.5 ft. (Rec. S.89°E., 64.5 ft.) Ren. #33

Ronald G. Geisler LS #1988
 For: Champion International Corp.
 January 1984
 M 95 - 77 and C.S. 58/278

Stephen J. Flause
 R. W. Smith
 Douglas County
 Surveyors Office
 Dec. 7, 1984
 C.S. 62/21

*FOOK BY W. ROGERS
5/99 1999-0052*
*FOOK BY Mark Heimbarger
3/94 1118-54*
*FOOK BY BENTZ
3/95 Vol 18 P 41*
*FOOK BY K. DeGroot
10/2001 52E
2001-0083*
*Change Report
C.S. 63/34
2/5/86*