

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 3 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97401

Douglas Co. Surveyor's
Office
Randall W. Smith, &
Stephen J. Flause
July 9, 1985
C.S. 62/28

(CONF.--)

FD OK

11/1978
1999-12

K DeGroot

141

New BT's - 9" D. Fir, double blazed and scribed "1/4 S14 CS BT", bears
S.77 3/4°E., 57.5 ft.

6" D. Fir, double blazed and scribed "1/4 S11 CS BT", bears
N.13°W., 41.1 ft.

Corner is approximately 500 ft. west of Old Cavitt Creek Road.

FD OK - 10/97 = DeGeoot - 1997-0135A+B

142

Closing Corner for Sections 19 and 30, T27-2

Set - Set a 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum, flared pipe;
mkd. PLS 1988.

BT's - 11" Fir, bears N.54°E., 15.2 ft. Scribed: T27S R2W S19 CC BT.
7" Fir, bears S.28°E., 20.6 ft. Scribed: T27S R2W S30 CC BT.

NOTE: An amended closing corner bears S.88°59'33"E., 14.38 ft. dist.

SEE RENEWAL #110

East 1/4 Corner for Section 25 only.

143

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum, flared pipe;
mkd. PLS 1988.

BT's - 2" Hemlock, bears N.88°W., 11.1 ft. Scribed X BT.
3" Fir, bears S. 18° W., 19.2 ft. Scribed X BT.

144

West 1/4 Corner for Section 30 only, (T27-2)

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum, flared pipe;
mkd. PLS 1988.

BT's - 7" Fir, Bears S.87°E., 45.6 ft.
7" Cedar, bears N.42°E., 21.9 ft.

145

Corner to sections 25 and 36 only.

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe;
Mkd. PLS 1988.

BT's - 14" Fir, bears S.11°W., 11.0 ft. Scribed, T27S R3W S36 BT.
7" Fir, bears N.45°W., 18.9 ft. Scribed; T27S R3W S25 BT.

Closing Corner for Sections 30 and 31 (T27-2)

146

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe;
mkd. PLS 1988. An amended closing corner bears S.88°24'45"E.,
17.29 ft. SEE RENEWAL #147

BT's - 13" Fir, bears N.62°E., 6.15 ft. Scribed: T27S R2W S30 CC BT.
6" Hemlock, bears S.07°E., 19.7 ft. Scribed: T27S R2W S31 CC BT.

CORNER REPORT ONLY

147

Amended Closing Corner for Sections 30 and 31. Renewal #77

Found - A 1962 County Surveyor brass cap on an iron post, and the
following accessories; (This corner is now an amended closing
corner, See Renewal #146 for new corner info.)

BT's - Uprooted Fir stump, bears N.50°E., 18.5 ft. (Orig.)
30" Fir stump, bears S.75°E., 19.1 ft. Scribe marks visible.
(Orig)

34" Fir stump, bears S.18°E., 59.4 ft. Scribing visible. (1962)

RM's - Also found a 1 1/2" iron pipe, N.80°W., 1.2 ft. from cap.
(1962 Record = N.80°E., 1.2 ft.)

148

Witness Cor. to West 1/4 Corner to secs. 31 (T27-2) and 36 (T27-3)

Set - A 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum flared pipe,
mkd. PLS 1988.

BT's - 8" Fir, bears N.28°W., 12.6 ft. Scribed: X BT.
10" Fir, bears N.81°E., 32.2 ft. Scribed: X BT.

NOTE: The true corner position falls in an existing dirt road. The witness
corner bears S.00°44'16"W., 51.09 ft. from the true point.

Ronald G. Geisler, Champion International Co.
June, 1985 thru August, 1985
M 90 - 71