

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 S T. S. R 3 W R. W. W. M.

C O N T - - - -

Douglas County Surveyors Office
Randall Smith & Stephen Flause
September 16, 1987
C.S. 62/45

59.1 ft. per 1958 BLM Resurvey; S 15°E, 48.8 ft. per 1979 BLM resurvey.) Ren. #48 BT

152

A 14" now 27" dia. sugar pine with a fully healed double blaze bears N 26°W, 14.2 ft. (agrees with rec.) Ren. #48 BT.

12" now a 16" dia. Cedar with a partially healed double blaze illegible scribing visible bears N 68½°E, 60.2 ft. (N 70°E, 60.2 ft. per ren.#48; N 68½°E, 60.2 ft. per 1958 and 1979 BLM resurvey.)

36" fir bearing S.75°W., 5.0 ft. gone by recent cat work.

BTs found per 1958 BLM resurvey:

10" now 12" dia. Chinquapin with a fully healed single blaze; bears N 40°E, 71.3 ft. (agrees with record.)

8" now 11" dia. Chinquapin with partially healed single blaze, scribing visible "S R3W S28 BT" bears S 52½°W, 23.1 ft. (agrees with record).

6" now 8" dia. Douglas Fir with a fully healed single blaze bears N 14 3/4°W, 29.3 ft. (rec. N 14 3/4°W, 30.4 ft. possible slope measurement)

8" now 11" dia. broken 10" high Chinquapin stump no blazes or scribing found, bears S 22 1/2°E, 17.2 ft. (agrees with rec.)

BT a casualty of recent cat work, trunk pushed over bank.

Set - Position of corner reestablished by using bearing trees of record.

1957 Douglas County Surveyors brass cap with iron pipe straightened and set firmly in ground. 6" of BC/IP protrudes above ground, The stamping "Reset 1987" is added to brass cap.

Corner lies near top of a NE - SW running ridge in the middle of a recent cat road.

Section corner for Secs. 7, 8, 17 and 18.

153

Found - A 1958 BLM 3½" brass cap on a 2½" O.D. iron pipe firmly set flush in rocks.

A 2½" dia. brass cap on a 1½" O.D. iron pipe protruding 16" above a 2 ft. dia. mound of stone. This BC/IP bears S.77½°W., 20.5 ft. from 1958 BLM BC/IP. Ren. #130

(All original bearing trees gone. BT from Ren. #22 gone. Northeast and Northwest BTs from 1958 BLM resurvey are gone.)

23" now 40" dia. D. fir with a fully healed single blaze bears S.66°E., 40.9 ft. (Rec. S.71½°E., 40.9 ft.) 1958 BLM BT.

16" now 17" dia. 35 ft. high D. fir snag with a previously opened low blaze, scribe marks visible "27" bears S.54½°W., 22.7 ft. (rec. S.59°W., 25.1 ft. dist. is to center of trunk.) 1958 BLM BT

A recently marked 3" "X" in a high rock outcrop, bears N.42½°W., 60.1 ft. (Rec. from 1987 BLM tag found on rock outcrop N.40 3/4°W., 60.1 ft.)

Southeast BT found alive with a partially healed burnt over blaze, faint scribe marks visible, we axed out scribing and remove Baughman's BT tag. Ren. #130

Northeast BT found down and burnt. No scribing visible in open blaze, Baughman's BT tag removed. Ren. #130

Southwest BT found down with a partially healed single blaze, scribing visible, We axed out scribing and remove Baughman's BT tag. Ren. #130

Set - Marks on Ren. #130 brass cap are stamped out, with the exception of "1978 OLS 536".

New BTs- 24" dia. D. fir (formerly Baughman's SE BT" single blazed 6 ft. above ground "T27S R3W S18 CS BT" bears S.47°W., 24.4 ft.

3" dia. madrone bark scribed "X BT" bears N.87½°E., 20.3 ft.

Note: Corner lies at south edge of an excavated rock ridge, in a rock slide. A possible magnetic attraction in area of corner, large amount of rock around corner.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Sept. 8, 1988
C.S. 62/55

1/4 Corner for Section 6 and Sec. 1 of T.27-4

154

Found - 1964 DCSO 2½" brass cap on a 1½" O.D. iron pipe measuring 27" long Found laying loose on top of ground near position of cor. Ren.#96

Metal flanges to brass cap/IP found 6" below ground broken off metal fence post found along north edge of flanges.

9" now 17" dia. trunk of southeast tree in a 45" dia. cluster of W. oaks, SE trunk has a fully healed blaze and a partially healed previously opened lower blaze, no scribing visible, bears N.19°E. 437.6 ft. (agrees well with record.) Original BT.

Douglas County
Surveyors Office
R.W. Smith
S.J. Flause
Sept. 12, 1988
C.S. 62/55

see
158
Re-Newed