

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

154

C O N T - - - -

22" now 29" dia. D. fir with a fully healed single blaze, bears N.6°W., 551.6 ft. (Rec. N.6°W., 553.3 ft. is to center of trunk)
Per Ren. #96

Doug. Co. surveyors
Office
R.W. Smith-S.J. Flauser
Sept. 12, 1988
C.S. 62/55

Set - Brass cap iron pipe reset at plumb position of found flanges. Set flush with ground. The marks "RESET 1988" are added to BC.

New Accessory:

A white metal witness post and sign is set 1 ft. south of BC/IP. Corner is in a field. No trees within a reasonable distance.

9/12/88

Section Corner for Secs. 8, 9, 16 and 17

155

Found - A 1958 3½" dia. BLM disk marked correctly, on a 2½" O.D. galv. I.P. firmly set and protruding 5" above ground.

Evidence of four original bearing trees found:

A laurel, 16" now a 22" DBH madrone with fully healed double blaze bears N.47°E., 31.2 ft. (Rec. N.50°E., 30.4 ft. good to center of tree at blaze height)

A 30" fir, now a 48" dia. 4 ft. high fir stump with no scribing or blazes visible bears S.80°E., 49.7 ft. (Orig. Rec. S.88°E., 48.8 ft. BLM rec. S.83°E., 48.8ft. dist. is possible face meas.)

A 36" fir now a 41" dBH D. Fir with burned bark scribing "S" visible bears S.04°W., 14.5 ft. (orig. rec. S.4°W., 13.2 ft. dist. this is a possible face measurement)

A fir 40" now a 48" dia. 3 ft. high fir stump with no blazes or scribing visible bears N.42°W., 37.6 ft. (Orig. rec. N.42°W., 36.3 ft. this is a possible face measurement)

Evidence of 3 bearing trees from 1958 BLM dependent resurvey found:

(The NE cedar bearing tree is not found due to road work in area)

An 8" madrone now a dead 7" DBH madrone snag with a healed single blaze bears S.29½°E., 28.6 ft. dist. (Rec. S.31¼°E., 29.0 ft. this is a possible slope face measurement)

A 9" cedar now a dead 10" DBH cedar with a partially healed single blaze showing the scribing "27S R3W S17 B" bears S.48°W., 52.8 ft. dist. as per record.

A 10" chinquapin now a 10" DBH 8 ft. tall snag with a partially healed single blaze bears N.73½°W., 60.8 ft. dist. (Rec. N.73½°W., 62.0 ft. is a slope measurement)

New BTs - A 10" DBG madrone scribed "T27S R3W S17 CS BT" on a double blaze bears S.68½°W., 13.2 ft. dist.

An 8" DBH incense cedar scribed "T27S R3W S8 CS BT" bears N.66½°W., 28.0 ft. distant.

Monuments lies approx. ten feet southerly from centerline of a cat fire road near the top of a steep ENE slope at the west cutting line of a large clear cut. Clear cut extends up ENE slope from Jim Creek.

4/5/89

156

Section Corner Section 31; and Sec. 36 of T.27-4

Found - 3¼" dia. 1989 BLM brass cap on a 2½" dia. iron pipe protruding 8" above ground. (unrecorded 1989 survey)

¾" iron rod from Ren. #87 not seen.

Orig. 14" now 22" dia. madrone with a rotted out center, old blaze with possible reverse scribing visible, bears S.37½°W. 15.9 ft. (orig. rec. S.35°W., 14.5 ft.; BLM BT tag, N.37½°E. 14.5 ft.)

10" now 24" dia. madrone with a previously opened blaze, no scribing visible bears S.43°E., 12.6 ft. (Orig. rec. S.31°E., 11.2 ft.; BLM 1989 BT tags N.43°W., 13.8 ft.)

15" now 30" dia. madrone with a partially healed upper blaze scribing visible "27S R3W S3" lower blaze fully healed, bears N.48½°E., 13.9 ft. (Orig. Rec. N.40°E., 13.9 ft.; 1989 BT tag S.48½°W., 13.9 ft.)

14" now 20" dia. 7 ft. high madrone snag with a partially healed double blaze, scribing visible "T27S R4W S36 CS BT" bears N.24½°W., 12.5 ft. (Orig. rec. N.23°W., 11.9 ft.; BLM 1989 BT tag, S.24½°E., no dist.)

1989 BLM BT, a 7" dia. D. fir with a single blaze, scribing visible "T27S R4W S36 SC BT" bears N.41½°W., 24.8 ft. (agrees with BLM 1989 BT tag.)

5" dia. D. fir double blazed, marks visible "X BT" bears N.59°E., 16.1 ft. (1989 BLM BT tag N.59°E., 16.1 ft.)

Douglas County
Surveyors Office
Randall Smith
Stephen J. Flauser
Sept. 18, 1989
C.S. 64/3