

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 3 W. R. W. W. M.

FOKE-CHAPMAN CO. EUGENE, ORE. 91881

164

South 1/16 Cor. Sec. 27 & 28

Mon. FD.- 3 1/4" Brass cap on a 2 1/2" O.D. iron pipe. protrudes 4" above ground. Orig. Cor. U.S. CADASTRAL SURVEY
S 1/16
S28|S27

1958

BUREAU OF LAND MANAGEMENT

Bt's Fd.- 10" now 12" dia. 2' high rotted D.Fir stump with scribing "S 1/16 S27", bears N.13 1/4"E., 17.2'. (agrees with rec.) OBT.
8" now 14" dia. Dead Chinquapin, with a partially healed sing blaze, no scribing visible, bears S.15"W., 25.1' (Rec. S.13"W., 25.1') OBT.
New BT's- 11" dia. D.Fir, double blazed and scribed "S 1/16 S27 CS BT", bears N.5"E., 16.6'.
7" dia. Hemlock, double blazed and scribed "S 1/16 S28 CS BT", bears N.59"W., 34.4'.
10" dia. Madrone, bark scribed "S 1/16 S27 CS BT", bears N.81"E., 25'.

see previous ren. #74

165

Sec. 34 & 35 South Cor. Only

Mon. Fd.- 2 1/2" Dia. alum. cap on a 1" O.D. iron pipe 11" above ground. Set by Thomas Shrum date unknown.

U.S. P.C. PROPERTY COR.

T27S R3W

34|35

RE 4278

1958 BLM 3 1/4" Dia. Brass cap on an iron pipe is found 7" below ground along northerly edge of alum. cap/IP.

U.S. CADASTRAL SURVEY

T27S R3W

S34|S35

S2

BUREAU OF LAND MANAGEMENT

3/4" I.R. noted in ren.#74 is found flush with ground along north edge of alum. cap iron pipe.

BLM BC/IP is .3' north of alum. cap/IP.

Bt's Fd.- Brg. & Dist. taken from BLM BC/IP
16" now 32" dia. 2 1/2' high Cedar stump, with a small blaze showing illegible scribing and axe mark, bears N.58"E., 35'. OBT.
12" now 12" dia. 25' high Cedar snag, with an unhealed blaze, scribing visible "T27S R3W S34 SC BT", bears N.67 3/4"W., 102.3'. 1958 BLM
6" R.Fir? now 17" dia. Hemlock, with a fully healed double blaze, bears N.62"W., 83.8'.
11" now 9" dia. 12' high Cedar snag, with an unhealed single blaze, scribing visible "T27S R3W S35 CS BT", bears N.2 3/4"E., 197.3'.
24" dia. Cedar with a partially healed single blaze, scribing visible "C BT", bears N.6 3/4"E., 157.1'.

New Accessories -

2 1/2" Alum. cap on a 1" O.D. iron pipe protrudes 16" above ground marked as noted on this page under monument detail in C.S. file 64/71-8, Set by Thomas Shrum date unknown, bears West 40.9 which agrees with orig. rec.

13" dia. Hemlock, double blazed and scribed "T27S R3W S34 SC CS BT", bears N.87"W., 49.5'.

11" dia. Ash, double blazed and scribed "T27S R3W S35 SC CS BT" bears N.19 1/4"E., 62.7'.

Corner lies in an area that floods often. Set metal wit. post and sign 1' south of corner's.