

Douglas County Surveyor's Record of
Government Corners Renewed

27 T.S. 3 R. W. W. M.

Arthur Boyer D.C.E.
Wit. O. J. Noice
N. E. Richardson
T. V. Gurnee
Jno. Labonte

C.S. File 23/32

CORNER BETWEEN SECTIONS 1 and 2. **SEE CORNER NO. 32**
Identified location from Oak Summit the tree of which has been burnt. Jno. La Bonte and T. V. Gurnee testify that this is the original B.T. for Sec. 1. Set Fir Post and pile rocks for corner from which
A 40" Bark Blazed Fir bears N.51°E., 80.0 ft.
A 40" Bark Blazed Fir bears S.63°W., 46.2 ft.

18

SECTION CORNER BETWEEN 5, 4, 8, and 9.
Location identified from all four of the original Bearing Trees as follows
Fir 24" dia. N.45°W., 15 lks, instead of N10°W. as recorded
Laurel 16" dia. S.1°W., 50 lks.
Laurel 30" dia. S.55°E., 45 lks.
Fir 48" dia. N.10°E., _____ lks. instead of N.15°E., 30 lks.
Set a Yew Wood Post 3" x 3" x 48" for corner. The original Fir bearing trees were reblazed in the bark and scribed.
A Cedar 10" dia. bears S.30°E., 29 lks.
A Double White Fir 24" dia. bears S.50°W., 46 lks.

19

SECTION CORNER BETWEEN SECTIONS 5 and 8. **FAOK BY D. EDWARDS**
Location identified from both original bearing trees, one of which was chopped out and showed scribed marks in excellent shape. The trees are a Fir 18" dia. S.20°W., 4 lks. and a Fir 18" dia. N.20°E., 4 lks. Drove an Iron Pipe 1/2" diam. x 24" long 20" in the ground for the corner from which
A Fir 20" dia. bears N.65°E., 57 lks.
A Fir 18" dia. bears S20°W., 4 lks. (Original bearing tree)

20

SECTION CORNER BETWEEN SECTIONS 8 and 17.
Renewed from Original Bearing Tree in S.E. Quadrant. (Sec. 17.) Set 4 x 4 Post for Corner and marked new trees as follows
Madrone 24" dia. bears N.70°W., 34.0 ft. marked
S.B. C.S.B.T.

21

SEC. CORNER BETWEEN SECTIONS 7, 8, 17, and 18.
Set a new B.T. in Section 8 because the original B.T. a Laurel N.78°E., 54 lks. is gone. Marked a new B.T. as follows
A Laurel 36" dia. bears N.80°E., 97 lks. marked S.E.
T.27 S. R.3W. C.S.B.T. **47**

22

SECTION CORNER SECTIONS 2 and 11
Remarked old White Oak 24" dia. S.8°W., 91.1 ft. found old blaze and checked into Old Cavitt Creek Road B.T.s. Set 4" x 36" Iron Bar and Rock Mound from which
A Cedar 30" dia. bears S.37 1/2°E., 28.5 ft.
A White Oak 16" dia. bears S.30 1/2°W., 37.5 ft.
Note: Notes on this corner being reestablished found by Ben B. Irving J. 6, 1945 being used as book mark. B.B.I.

23

Ben B. Irving D.C.E.
Wit. Milo Godfrey
Lester S. Kershner
May 14, 1947
SECTION CORNER BETWEEN 22 And 23.
Rescribed old bearing trees, viz., Fir 35 ins. diam bears S 60°W 38.9 ft. and a Fir 30 ins. diam. bears S 35°E 24.4 ft. Set a 1" iron pipe with a brass cap, stamped "County Surveyor Office S 22 23" **Fnd. 1984 by BENTZ - M 96-28 A&B**
1193 M118-116

24

BEN B IRVING D.C.E.
WIT. Milo Godfrey
Lester S. Kershner
May 14, 1947
SECTION CORNER BETWEEN "23 and 24.
Reblazed and rescribed original bearing trees.
Fir 18 ins. diam (now 36") N 78° 25' E. 36" dia. Cedar 14 ins diam. (now 24") N 78° 25' E. 36" dia. 1 1/2" iron pipe with a brass cap, stamped "County Surveyor Office S 23 24"

25

B. B. Irving D.C.S.
Wit. N. E. Richardson
N. G. Williams
Bert. Delzene
August 12, 1939

C.S. 47/66

A. Boyer D.C.S.
Wit. Otto Rowe D.C.S.
Bert Delzine
June 12, 1942
son
June 13, 1942

C.S. File 47/66

A.C. Frear
J. Wolford
Sept. 27, 1943

C.S. File 36/32

W. B. P. Ed.

RE-RENEWED, SEE CORNER NO. #132
F.D. 6-19-77 B.L.M.