

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 3 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

G. Robert Lecklider
For-Wilbur Lbr. Co., Evans
Products, & U. S. Plywood
August 1960
Map File M 19 - 51

Section Corner to Sections 19, 20, 29 and 30.
Found - 30" Fir S.50°E. 4.6 ft., rescribed
36" Fir Stump S.85°W. 38.5 ft.
14" Fir N.10°W. Down.
Set - Steel Tube with Survey Cap
21" Fir N.62°E. 30.7 ft.
9" Cedar N.27°W. 22.5 ft.

RENEWED, SEE CORNER NO. #127

60

1/4 Section Corner to Sections 20 and 29.
Found - 22" Fir N.15°W. 15.1 ft.
22" Fir S.45°E. Down.
Set - Steel Tube with Survey Cap
42" Fir S.43°E. 43.1 ft.
14" Fir N.43°W. 19.0 ft.

61

1/4 Sec. Cor. to Sec. 12; T27S, R3W. & Sec. 7, T27S, R2W.
Found - 1/2" Iron Rod
20" D. Fir - N. 15°W. - 5.3 ft.
Set - 10" D. Fir - S.57°W. - 26.5 ft.
6" D. Fir - S.11°E. - 21.0 ft.

RENEWED, SEE CORNER NO. 107

62

Sec. Cor. to Secs. 12 - 13; T27-3W. & 7 - 18, T27-2W.
Found - 30" D. Fir - S.58°E. - 38.9 ft. (Windthrown)
Set - 3/4" x 36" Iron Rod
6" Cedar - N.19°30'W. - 45.7 ft.
24" D. Fir - S.37°W. - 81.7 ft.
18" D. Fir - S.73°30'E. - 35.8 ft.
8" Hemlock - N. 6°E. - 45.4 ft.

63

1/4 Section Corner to Sections 12 - 13:
This 1/4 corner was restored by the use of distance calls on two
creeks from the G.L.O. notes which read as shown on sheet in CS 51/174.
Original Corner not found.
Set - 3/4" x 36" Iron Rod
8" Hemlock - S.62°W. - 15.0 ft.
7" Hemlock - N.24°E. - 10.7 ft.

64

Center 1/4 Corner Section 12
Set - 3/4" x 36" Iron Rod
19" W. Oak - N.62°W. - 96.9 ft.
9" W. Oak - S.34°30'E. - 15.3 ft.

FNO. OK 1-95 BY DeGroot
1995-0028

FNO. OK 3/97
BY DeGroot
1997-0113

65

James W.
Byron
7/14/61
C. S. File
No. 49/67

Renewed Corner $\frac{R4W}{S36/S31}$ $\frac{R3W.}{S6}$ T27S

Found - All found Orig. BT's. The SW & NW Orig. BT's. show good
scribing. All check record.

Stake at Corner.
New BT's: 20"(Orig) Laurel bears N.22°W. 12.5 ft. scribed S36 T27S R4W CS BT.
32"(Orig) Laurel bears N.50°E. 13.0 ft. scribed S31 T27S R3W CS BT.

NO. 81

66

B.B. Irving,
Co.Surv.
A. Evans, Deputy
R.G. Irving &
E.B. Luther
C.S. File 44/61

1/4 Corner to Sec. 5, T27-3W. & Sec. 32, T26-3W
Set by Proportionate Measurement
Set - 1" I.P. with brass cap Mkd: County Surveyor's Office
T 26 S, R 3 W, 1/4 S32
T27 S, R 3W, 1/4 S 5
Blazed & Scribed 2 Bearing Trees:
8" W.Oak N. 60°W. 19.1 feet
8" W.Oak S.53° E. 53.6 feet

October 19, 1950

66-A