

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 3 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Township Corner. S36 | S31 T27S
R3W S1 | S6 R2W T28S

Found - All Orig. BT's. All are now stumps. N.E. BT. shows good scribing "3". Also find Rock Mound at Corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 S36 | S31 T27S #131
R3W S1 | S6 R2W T28W

New BT's: 16" Cedar bears S.27°W. 72.0 ft. scribed S1 T28S R3W CS BT.
17" Laurel bears S.3°E. 17.0 ft. scribed S6 T28S R2W CS BT.
4" R.Fir bears N.10°W. 19.8 ft. scribed S36 CS BT.
9" R.Fir bears N.87°E. 50.1 ft. scribed S31 CS BT T27S R2W

FOUND O.K. 11/28/68 V.R.T.

South $\frac{1}{4}$ Corner to Section 36 only.

Found - Both Orig. BT's. Orig. N.E. BT., now down.
Orig. 30", now 38" R.Fir S.53°E. 52.1 ft., shows good bark scrbing.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
South $\frac{1}{4}$ S66 T27S R3W.

New BT's: Rescribe O.B.T. 38" R.Fir S.53°E. 54.9 ft. $\frac{1}{4}$ S CS BT.
5" R.Fir bears N.66°W. 24.4 ft. scribed $\frac{1}{4}$ S36 CS BT.

Note - Corner is at Base of Laurel Steel.

$\frac{1}{4}$ Corner to Sections 30 and 31.

Found - Orig. 30", now 43" Fir Snag N.20°E. 2.6 ft., shows good bark scrbing.
Orig. S. W. Bearing Tree not found.

Note - Logging Road is 15 ft. E. & 15 ft. S. of Corner.

Set - $\frac{3}{4}$ " Iron Rod at Corner.

New BT's: 9" Cedar bears N.72°W. 34.6 ft. scribed $\frac{1}{4}$ S30 CS BT.
5" R.Fir bears N.32°E. 14.7 ft. scribed $\frac{1}{4}$ S30 CS BT.

Renew Corner S25 | S30
R4W S36 | S31 R3W T27S

Found - 1917 Brass Cap at Corner. All BT's, now dead.

New BT's: 5" Hemlock bears N.4°E. 92.0 ft. scribed S30 CS BT.
7" Hemlock bears N.10°W. 105.6 ft. scribed S25 T27S R4W CS BT.
8" Hemlock bears S.72°W. 94.3 ft. scribed S36 CS BT.

South $\frac{1}{4}$ Corner to Section 33 only.

Found - Orig. 30", now 72" Fir N.55°E. 19.8 ft., shows good old bark scrbing.
We do not find Orig. S. W. Bearing Tree.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
S $\frac{1}{4}$ S33 T27S R3W.

New BT: 12" Laurel bears N.11°W. 32.7 ft. scribed $\frac{1}{4}$ S33 CS BT.

Renew Corner to S32/S33 only.

Found - All Orig. BT's. Orig. 16", now 24" R.Fir N.16°E. 30.4 ft., good scrbing.
Orig. 30", now 36" Fir, not Laurel, N.25°W. 32.3 ft., shows good bark scrbing.
Orig. 14", now 24" Fir, S.30°W. 20.5 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

S32/S33 T27S
T28S R3W

Renew S 5/S 4 T27S
T28S R3W

Found - Both Orig. BT's. Orig. 12", now 20" Laurel S.44°E. 24.4 ft., shows good scrbing.
Orig. 5", now 10" Laurel S.37°W. 42.9 ft., old face rotted.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 S 5/S 4 T27S R3W
T28S

New BT: 13" Laurel bears S.10°W. 22.5 ft. scribed S5 T28S R3W CS BT.

Note - Sec. Corner S32/S33 T27S R3W bears N.76°W. 62.9 ft., not West 62.9 ft.

Renew Corner To S34/S35 T27S R3W

Found - $\frac{3}{4}$ " Iron Rod at Corner & Orig. 16", now 24" Cedar bears N.60°E.
33.0 ft., shows good scribing.

No other Orig. BT's. found.

New BT: 6" R.Fir bears N.61°W. 83.4 ft. scribed $\frac{1}{4}$ S34 CS BT.

James W. Byron, Deputy County Surveyor
John Powell and Wm. Stoffel
August 1962
C. S. File No. 49/28

67

68

69

70

71

72

73

74