

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27. S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

80

$\frac{1}{4}$  Corner between Sec. 7, T27-3W & Sec. 12, T27-4W.  
Found - I. Pipe with Brass Cap, pulled out of ground by uprooted tree.  
Fir Stump S.37°W. 56.8 ft., partial scribing visible (1917 BT)  
Fir N.31°E. 45.5 ft., tree uprooted & down, scars buried in mud. (1917 BT.)  
9" Fir S.55 $\frac{1}{2}$ °E. 9.2 ft., tree uprooted & down, scribing visible. (1958 BT.)  
11" Fir S.25 $\frac{1}{2}$ °W. 50.8 ft, tree uprooted & down, scribing visible. (1958 BT.)  
Reset Brass Cap in original position.  
New BT's: 16" D.Fir S.87°E. 34.1 ft. Mkd:  $\frac{1}{4}$  S7 CS BT.  
10" D.Fir N. 7°W. 38.2 ft. Mkd:  $\frac{1}{4}$  S12 CS BT.  
Note - Brass Cap set originally in cadastral resurvey of 1958.

Milo E. Godfrey, Deputy  
V. Tracy & M. Stone  
Jan. 2, 1963  
C. S. File No. 153/33

81

Section Corner: Sections 26, 27, 34, 35.  
Found: 26" Cedar, dead, N.16°W. 22.5 ft. 4"x6" Alum. ref. tag.  
21" D.Fir Stump, S.39°W. 41.0 ft. 4"x6" Alum. ref. tag.  
The 4" x 6" Alum. ref. tags were set by me in Oct. 1957 from the Orig. BT's. Subsequent logging destroyed the Orig. BT's. and the stake set on the corner. From the reference tags, I reset the corner and scribe the following new bearing trees:  
Set - 2 $\frac{1}{2}$ " Aluminum Cap  
10" Yew, S. 85° W., 64.0 ft. Mkd: S34 BT RE 4287  
14" Cedar, S. 34° E., 88.6 ft. Mkd: S35 BT RE 4287  
12" Yew, N. 45° W., 83.2 ft. Mkd: S27 BT RE 4287  
36" Cedar Stump, N. 75° E. 87.0 ft. Mkd: S26 BT RE 4287  
BT's. scribed 1/1961  
Alum. Cap set 2/1963

RE-NEWED SET CORNER NO. #136

Thomas E. Shrum, Jr.  
For U.S. Plywood  
C. S. File No. 51/254

82

$\frac{1}{4}$  Section Corner: Sections 33 and 34.  
Found:  $\frac{3}{4}$ " Iron Rod - This iron rod was set by me from the Orig. BT's. in 1955; subsequent logging destroyed all Orig. BT's. I now scribe new BT's. referring to the iron rod.  
Set: 22" Cedar Stump S. 78° W. 24.2 ft. Mkd:  $\frac{1}{4}$  S33 BT RE 4287  
5" Hemlock, S. 52° W. 52.6 ft. Mkd:  $\frac{1}{4}$  S33 BT RE 4287  
12" Cedar N. 19° E., 71.1 ft. Mkd:  $\frac{1}{4}$  S34 BT RE 4287  
Dec. 1962

Thomas E. Shrum, Jr.  
For U. S. Plywood Corp.  
Dec. 1962 - Jan. 1963  
C. S. File No. 51/254

83

$\frac{1}{4}$  Section Corner: Sections 27 and 34.  
Found:  $\frac{3}{4}$ " Iron Rod  
10" D. Fir, N. 10° W., 11.9 ft. (down)  
Set: 2 $\frac{1}{2}$ " Aluminum Cap  
8" D. Fir, S. 33 $\frac{1}{2}$ ° E., 22.4 ft. Mkd:  $\frac{1}{4}$  S34 BT.  
11" D.Fir, N. 65° E. 36.0 ft. Mkd:  $\frac{1}{4}$  S27 BT.  
Jan. 1963

RE-NEWED SET CORNER NO. 160

84

West  $\frac{1}{4}$  Section 30 only, (E. Line T27-4W.)  
Found - Brass Cap set in 1917.  
18" Fir Stump S.33 $\frac{3}{4}$ °E. 28.4 ft. Cut open & fd. good scbng. No trace of N. E. Tree.  
New BT's: 14" D.Fir N.12°E. 72.0 ft. Mkd:  $\frac{1}{4}$  S30 CS BT.  
18" D.Fir S.20°E. 42.3 ft. Mkd:  $\frac{1}{4}$  S30 CS BT.  
A 27" Doug. Fir (with aluminum Tag) is 2 feet south of corner.

Milo E. Godfrey, Deputy Co. Surv.  
Bill Stoffel and Crew  
October 1963  
C. S. File No. 53/33

84-A

West  $\frac{1}{4}$  Corner Section 18 only. (on E. Line T27S R4W)  
Found - Brass Cap set in 1917 survey.  
5" Cedar N.46°E. 27.7 ft., alive & in good condition.  
6" Cedar S.35 $\frac{1}{2}$ °E. 8.6 ft., down & broken up.  
New BT: 5" Red Cedar S.7°E. 21.2 ft. Mkd:  $\frac{1}{4}$  S18 CS BT.

85

Cl. Corner Sections 24 and 25. (on W. Line T27S R3W).  
Found - Brass Cap set in 1917 survey, still firmly set.  
38" Fir S.31 $\frac{3}{4}$ °W. 31.0 ft. Scar vis., Tree in good condition.  
Dead & Rotting Fir Snag N.65°W. 47.5 ft., shows good scar.  
New BT: 40" D.Fir N.77 $\frac{1}{2}$ °W. 67.8 ft. Mkd: T27S R4W CC S24 CS BT.