

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 3 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, OR., 97101

Corner to Sections 19 and 30 only. (on E. Line T27S R4W) 86  
 Found - Granite(?) Rock as called for in gov't. notes, 2 notches  
 on S. and 4 notches on N. sides.  
 36" Fir S. 61° E. 28.4 ft., has been opened previously, good  
 scribing visible "T27S R3W". Tree alive & in good condition.  
 42" Fir N. 67° E. 6.0 ft. Good axe scar visible. Did not open, Tree alive  
 Set - Brass Cap alongside Rock at Cor. Mkd: T27S R4W  $\frac{S}{S} \frac{19}{30}$  R3W  
 County Surveyor's Office, 1963  
 Did not mark any new Bearing Trees.

-----  
 T27S  
 Renewed Corner R4W  $\frac{S}{S} \frac{36}{6} \frac{S}{S} \frac{31}{6}$  R3W 87  
 T28S  
 Found - Wooden Stake & 20" Laurel N. 22° W. 12.5 ft. scribed "S36 T27S R4W CS BT  
 in 1961, alive & in good condition. See Ren. No. 66  
 32" Laurel N. 50° E. 13.0 ft. scribed in 1961, alive & in good condition  
 Other two Orig. BT's., no longer showing scribe marks.  
 Drive - 3/4" Iron Rod at Corner in place of Wooden Stake.

-----  
 Closing Corner Sections 13 and 24. (on W. Line T27-3W) 88  
 Found - Pipe with Brass Cap set in 1917 survey.  
 42" Fir Stump N. 20 1/2° W. 38.9 ft., shows very plain axe scar.  
 36" Fir Stump S. 77 1/2° W. 27.1 ft., shows very plain axe scar.  
 New BT's: 22" In. Cedar N. 40° W. 38.5 ft. Mkd: T27S R4W CC S13 CS BT.  
 12" Maple S. 47° W. 10.4 ft. Mkd: T27S R4W CC S24 CS BT.

-----  
 Section Cor. to Secs. 30 & 31, T27-3W. & Secs. 25 & 36, T27-4W. 89  
 Found - Brass Cap set in 1917 in Mound of Rocks.  
 5" Hemlock N. 4° E. 92.0 ft. (scribed in 1962, See Cor. No. 70)  
 7" Hemlock S. 72° W. 94.3 ft. (scribed in 1962, recorded)  
 6" Hemlock N. 10° W. 105.6 ft. (scribed in 1962, not recorded)  
 Rescribed Dead Cedar Snag, now 42", S. 45° E. 16.3 ft., Orig. BT.,  
 mkd: "T27S R3W S31 CS BT."

-----  
 1/4 Section Corner: Sections 26 and 27, T27S, R3W. 90  
 Found - 3/4" Iron Rod.  
 48" Doug. Fir Stump; S. 55° E. 3.3 ft. (Orig. BT) #134  
 4" x 6" Aluminum tag, 1952  
 Set - 27" Doug. Fir, S. 48° W., 19.0 feet, 4" x 6" Aluminum tag, 1952.  
 2 1/2" Aluminum Cap.  
 11" White Fir, S. 73° W., 18.1 feet, Mkd: 1/4 S27 BT.  
 6" Yew, N. 40° E., 38.6 feet, Mkd: 1/4 S26 BT.

-----  
 South 1/4 Section Corner to Section 34 only, T27-3W. 91  
 Found - 4" x 4" x 6' Cedar Post.  
 D. Fir Stump, N. 45° W., 24.0 feet (burned off)  
 D. Fir Stump, S. 40° E., 26.0 feet (burned off)  
 Set - 2 1/2" Aluminum Cap  
 10" Cedar, N. 34 1/2° W., 30.9 feet, mkd: 1/4 SC S34 BT.  
 8" Madrone, N. 63° W., 35.2 feet, Mkd: 1/4 SC S34 BT.

-----  
 Township Corner 92  
 T26S  
 R4W  $\frac{S}{S} \frac{36}{1} \frac{S}{S} \frac{31}{6}$  R3W #140  
 Found - I. Pipe with Brass Cap set by Richardson in 1947. (See Cor. No. 56.)  
 35" W. Oak N. 15 1/2° W. 24.5 ft., shows good scar. Tree alive, gd. cond.  
 10" W. Oak S. 81° W. 195.8 ft., now dead snag, all scribing visible.  
 Stump of 36" Fir S. 6° E. 543.8 ft., bark scribing visible.  
 New BT's: 12" D. Fir S. 28° E. 444.6 ft. Mkd: T27S R3W S6 CS BT.  
 26" W. Oak S. 76° W. 175.7 ft. Mkd: T27S R4W S1 CS BT. This tree was  
 marked as BT. in 1917 survey, scar previously opened &  
 old face rotted away, new scribing above old face.  
 Note - Corner is approximately 6" north of E. & W. fence line &  
 200 ft. East of Buckhorn Road.

Milo E. Godfrey, Deputy Co. Surveyor  
 Wm. Stoffell and Crew  
 October 1963  
 C. S. File No. 53/33

Thomas E. Shrum, Jr.  
 For U. S. Plywood, Inc.  
 April 1963  
 C. S. File No. 51/254

Milo E. Godfrey, Deputy  
 Wm. Stoffel & Mike Stone  
 October 22, 1963  
 C. S. File 53/33