

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 4 R. W. W. M.

M. B. Germond
Vol. 3, Pg. 46
Dec. 1918

N.E. CORNER OF D.L.C. #52
Renew from old B.T. and set in a 3" x 36" Galvanized Iron
Pipe from which
A 20" Fir bears N.60°W., 21 lks.
I also remarked old Government tree.

1

J.W. Cole Dep.
Sept. 23, 1920
C.S. Vol. 3, Page 14
F.B. 48

CORNER TO SECTIONS 4, 5, 8, and 9.
Renewed corner from old bearing trees and set a 1 1/2" x
30" Iron Pin and a 3" x 3" x 36' Oak Post.

2

H.L. Eppstein
Dep.
Wit.

CORNER BETWEEN SECTIONS 16 and 17.
Reestablished from one old B.T. which bears N.60°E. 150
links by setting a 4" x 4" x 36" Oak Stake from which
A 10" Black Oak bears N.46°30'W., 50 1/2 lks. C.S.B.T.
A 12" Black Oak bears S.28°00'E., 56 lks. C.S.B.T.

3

Shelby Mathews
J.R. Iler
Mar. 1920
F.B. 48, P. 5

N.E. CORNER D.L.C. # 44 (NNE)
Reestablished from old stone by
A 20" White Oak bears N.70°30'E., 572 lks. C.S.B.T.
A 24" Black Oak bears S.45°00'E., 661 lks. C.S.B.T.

4

F.C. Frear
11/18/1921
Wit. S.J. Jones
C.J. Ingram
Henry Weber
C.S. 118-43
R. R. 17, P. 290 64-67

S.W. COR. SECTION 32
I reestablished from one old B.T. viz. 18" Cedar bears
S.28°E., 11.2 ft. marks plain and other trees all destroyed.
I set a 2" x 12" Wagon Boxing from which
A 24" Cedar bears S82°W., 28.3 ft.

5

G. G. Stewart
D.C.S.
Witnesses
Bert Spring-
stead
W.S. CREARER
MAY 20, 1922

CORNER BETWEEN SECTION 21 and 28
Reestablished from two original bearing trees one of which
is rotten. I drove an Iron Pipe and marked the following
trees
Fir 12" dia. bears N.75°E., 50 ft. This tree was dead
in July 1943 and A. Boyer marked new B.T. as follows
White Oak 12" dia. bears N.27°E., 34.3 ft. It was
set in 1943 by Boyer, witnesses Jess and Harold Marr

6

G.G. Stewart
D.C.S.
Wit. Red Matt-
hews and Shelly
Matthews
W.S. Crear
June 26, 1922

SECTION CORNER BETWEEN 21, 22, 27 and 28
Reestablished from two original bearing trees and one
stump. Distances and bearings did not check. Set an Iron
Pipe according to distances. I marked the following trees
Black Oak 24" dia. bears N.72°W., 18.5 ft. (O.B.T.)
White Oak 18" dia. bears S.1 1/2°W., 135.6 ft.
18" Black Oak N89°E., 169.7 ft.
Black Oak 18" dia. bears N.75°E., 73 ft.
Note: Set Auto Axle for this corner in March 29, 1937
by Ben B. Irving.

7

S.W. CORNER OF D.L.C. # 43 J. MATTHEWS D.L.C.
Reset from old B.T. a Laurel that has been cut and was
rotten. Set an Iron Pipe for corner and marked the following
trees
White Oak 24" dia. bears S.85°W., 74.5 ft.
Remarked O.B.T. Laurel 14" stub S.40°W., 8 ft.

8

N.E. CORNER of D.L.C. # 44 (Ell Corner (ENE))
Reestablished from dead O.B.T. Set Iron Pipe for corner
and marked the following trees
White Oak 6" dia. bears S.15 1/2°W., 6.8 ft. This tree
was out, A. Boyer set a new tree in 1936 N.E. Richardson
was witnesses. They marked the following tree to re-
place the original
White Oak 15" dia. bears S.59°E., 36 ft.
Black Oak 18" dia. bears S.75 1/2°E., 53.5 ft.

9

S.E. CORNER D.L.C. # 43 J. MATTHEWS
Reestablished from 8" limb in Maple, the original B.T.
Set Iron Pipe for corner and marked the following trees
Fir 20" dia. bears N.28°E., 10 1/2 lks.
White Oak 6" dia. bears N.63°W., 32 lks.

10