

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 4 R. W. W. M.

<p>✓ SET INTERIOR "L" CORNER TO CLAIM # 39 Set corner from old stump and 2" Galvanized Iron Pipe and marked the following trees Black Oak 10" dia. bears S55°E., 56ft. White Oak 6" dia. bears N69°W., 42 ft.</p>	11	<p>H.L. Eppstein C.S. Wit. W.E. Chapman W.S. Crear Willard Smith R.L. Cannon Mer. 26, 1925.</p>
<p>✓ S.W. CORNER OF D.L.C. # 51 Set S.W. Corner of D.L.C. 51 from old tree found by me previously. Marked the following tree White Oak 16" dia. bears S.50°W., 50.8 ft.</p>	12	<p>Eppstein B.B. Irvine Wit. 4-3-31 W.S. Crear Wit. Herman Odem N.E. Richardson Ernest Keltz C.I. Branton Frank Odem Frank Strader</p>
<p>✓ 1/4 CORNER BETWEEN SECTIONS 28 and 29 Set corner from one old B.T. which was in good shape with scrip marks plain. Marked new trees as follows Red Fir 10" dia. bears N.13°W., 13 ft. Red Fir 6" dia. bears S.73°E., 17.9 ft.</p>	13	<p>C.F. Roberts Jan. 12, 1904 Mar. 19</p>
<p>✓ 1/4 CORNER BETWEEN SECTIONS 3 and 10. Location identified from one original B.T. and fence corner. B.T. chopped out and badly rotted. Set Pine limb for corner. New B.T.S as follows Black Oak 30" dia. bears N.66°30'W., 15 lks. White Oak 8" dia. bears S.13°45'E., 67 lks.</p>	14	<p>C.C. Boyer December 9, 1933 Ben B. Irvine D.C.C.S. Wit. N.E. Richardson J. S. Merr</p>
<p>✓ 1/4 CORNER BETWEEN SECTIONS 14 and 23 Marked the following trees Fir 15" dia. bears S.60°E., 122 lks. Fir 16" dia. bears S.1/2°E., 133 lks.</p>	15	<p>A. Boyer Mar. 22, 1936 Witness N.E. Richardson</p>
<p>✓ 1/4 CORNER BETWEEN SECTIONS 15 and 22. Marked the following trees Black Oak 24" dia. bears N.44°W., 22 lks. Fir 12" dia. bears S.30°W., 3 lks.</p>	16	<p>SEE CORNER NO. 117 SEE CORNER NO. 125 SEE CORNER NO. 119 SEE CORNER NO. 53 SEE CORNER NO. #19 SEE CORNER NO. #20</p>
<p>✓ 1/4 CORNER BETWEEN SECTIONS 22 and 27. Marked the following trees Fir 30" dia. bears N.72°W., 48 lks. Fir 8" dia. bears S.42°E., 52 lks.</p>	17	<p>SEE CORNER NO. 33</p>
<p>✓ N.W. CORNER OF J. SIMMONS D.L.C. # 41 Marked the following tree Ash 8" dia. bears N.87 1/2°W., 52 lks. marked C.41 C.S. B.T.</p>	18	<p>SEE CORNER NO. 36</p>
<p>✓ 1/4 CORNER SECTION BETWEEN 15 and 22 Location identified from stump of Fir B.T. as set by Roberts in 1904. Oak B.T. down. Original Laurel B.T. part of stump remaining. Set for corner Iron Pipe from which A Fir 18" dia. bears S.30°W., 43 ft. blazed and scribed 1/2 S. 22 C.S.B.T. A Fir 20" dia. bears N.76°W., 71.4 ft. blazed and scribed as follows 1/2 S. 15 C.S.B.T.</p>	19	<p>SEE CORNER NO. 33</p>
<p>✓ 1/4 SECTION CORNER BETWEEN 22 and 27. Location identified from B.T. as set by Roberts in 1904. Set a 1 1/2" Auto Axle from which Fir 36" dia. bears N.72°W., 48 lks. New B.T.s Fir 24" dia. bears S.55°W., 61.8 ft. blazed and scribed 1/2 S. 27 C.S.B.T.</p>	20	<p>SEE CORNER NO. 36</p>
<p>✓ (ONE) N.E. CORNER OF D.L.C. # 44. Marked a 15" White Oak N.59°E., 26 ft. to replace the 6" White Oak S.15 1/2°W., 6.8 ft. that has been cut down.</p>	21	<p>SEE CORNER NO. 36</p>

SEE ALSO REN #9

36 FT PER OLD REN Vol PG 84

111

No Roll Ed. C.S. File 37/41  
 C.S. File 37/41  
 Jan. 12, 1904  
 Mar. 19  
 December 9, 1933  
 Mar. 22, 1936