

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

SEE STATE MAP
MAP (1988) FOR
PINK CO. INFO.
(C.S. 8-6)
F. ok. 1/84
M 95-73

Section Corner to Secs. 1 & 12, T27-5W. and Secs. 6 & 7, T27-4W.
Set - Brass Cap Stamped.

1" Iron Rod bears N. 24° W. 32.5 ft.

Scribed - 6" Oak bears S. 14°E. 29.0 ft., scribed Sec. Cor. Sec. 7, T27-4W.

12" Oak bears S. 33° W. 94.0 ft.

8" Oak bears N. 86° W. 73.2 ft., scribed Sec. Cor. 1 & 12, T27-5W.

March 18, 1968

131

Baughman, G.
4 Star Dev.
12/30/67
H 35 - 54

1/4 Corner to Sec. 7, T27-4W. and Sec. 12, T27-5W. #139

Set - Brass Cap Stamped 1/4 Corner Sec. 12, T27-5 and Sec. 7, T27-4.

Scribed BT's: 36" Alder bears S. 33°W. 243.2 feet.

11" White Oak bears N. 68°E. 350.5 feet.

Aug. 1970

132

Baughman, Glenn
For: Snowbird Stone
Aug. 1970
Map File
M 41 - 7
Jan - 972

RE-RENEWED

1/4 Corner for Secs. 31 and 32

Found - Brass cap firmly set in E-W fence line & mkd. as described in Ren. #47. The Laurel snag noted as found in 1959 by Byron is now out of the ground and downhill from the corner, reverse scribe is still visible.

a 21" now 24" R. Fir mkd. by Byron in 1959 is alive and well-healed bearing S. 26 1/2° E., 32.4 ft. (Note: this tree will be cut in logging operations in the near future.)

A 15" now 18" Incence Cedar, mkd. by Byron in 1959 is alive & well-healed bearing S. 9° W., 49.7 ft.

New BT - 5" D. Fir, bears S. 58 1/2° E., 19.3 ft. scribed "1/4 S32 CS BT".

6/3/74

133

Gary Langlitz
Pete Earle
C.S. 56/51
6/3/74

Section corner, Secs. 17, 16, 20 and 21

Set - I. R. by proportionment from NW and NE corners of Cl. #44.

July 1975, Apr. 1976

135

H. L. Northcraft
For: Clifford &
Arnold Counts
M 59 - 64

1/4 Corner for Sec. 19 only of T. 27-3.

Found - 1917 GLO brass cap on 1" I.P. 20" long, loosley set alongside the broken lower portion of the 1917 I.P. Brass cap properly mkd.

A 40" D. Fir now 54" blowdown, bears N. 13° E., 13.9 ft. We open well healed blaze and find plain scribe marks.

The remains of a 50" D. Fir now 54" rotten snag 10 ft. tall, bears S. 87° E., 34.3 ft. No markings found.

Set - At the location of the found 1917 iron post we set a 1" x 30" I.P. 27" in the ground with brass cap attached marked:

Douglas County Surveyor T 27 S
1977 S 19 R
1/4 3
W

and deposit remains of 1917 iron post alongside.

New BT's - An 18" D. Fir double trunked at the base bears N. 69° W., 39.2 ft. scribed "W 1/4 S19 R3W CS BT" on a double blaze.

A 10" Hemlock bears N. 53° E., 32.0 ft. scribed "1/4 S19 CS BT" on a double blaze.

9/19/77

136

1/4 Corner for Secs. 4 and 9.

Found - No trace of orig. corner post.

Found a 1" I.P., firmly set, extending 6" out of ground with 1963 County brass cap. Ren. #107

No trace of orig. bearing trees.

Found an 8" D. Fir, now a 10" stump with well healed lower blaze on stump bears N. 19° E., 23.3 ft. (Rec. N. 17° E., 23.3 ft.)

An 18" D. Fir now a 20" stump with well healed lower blaze on stump bears S. 74° E., 47.4 ft.

New BT's - A 17" B. Oak, scribed "1/4 S4 CS BT" on a double blaze bears N. 79° W., 57.4 ft.

A 20" B. Oak scribed "1/4 S9 CS BT" on a double blaze bears S. 31° W., 61.9 ft.

7/19/78

Gary Langlitz
F. C. Silagy
Doug. Co. Surveyor
Office
July 19, 1978
C.S. 60/11

1-79