

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 4 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97101

Karen Reed, Deputy
Douglas Co. Surveyor
Office
Terrie Plouff
Aug. 7, 1980
C.S. 61/11

B.A. Shaner
OR LS. #430
For: J.A. Barnes
August 17, 1981
C.S. 58/229

Glenn Baughman
For: Kenneth L. Miller
Jan. 1984
M 95 - 73

L. E. Monrean, Deputy Douglas County Surveyor
Douglas County Surveyors Office
Janet Lundeen, Randy Smith
Feb. 10, 1984
C.S. 62/16

137

1/4 Corner for Section 31 and Sec. 6 of ~~T.26-4~~ ^{T.26-4} ~~T.26-4~~ ^{T.27-4}
Found - A 3/4" x 30" Iron rod buried 12" below the surface of the ground. Also found remnants fo wooden post in hole with iron rod. Ren. #29 and Ren. #33 of T.26-4
No orig. Pine found.
A 12" Oak, now 24" with healed over previously chopped out double blaze bears S.80 1/2°W., 221.8 ft. (Rec. S.82°10'W.)
A 7" Ash, now 29" with well healed blaze bears S.30°E., 92.7 ft.
A 15" W. Oak, now 25" with well healed blaze bears S.36°E., 48.0 ft.
A 12" W. Oak, now 16" with well healed double blaze bears N.30°W., 103.6 ft. (Rec. N.30°E., Ren. #29)
Set - We reference out the iron rod and set a 1 1/2" x 36" iron pipe stamped: "Douglas County Surveyor" T26S S31 S6 T27S 1/4 R4W 1980", in its position, then SET the iron rod along the west side of the cap. Put three rocks around the cap. Cap protrudes 0.2 ft. above ground.
No new accessories.
Cap lies North, 29.1 ft. of an E-W fence and 4.1 ft. West of westerly corral fence.

8/7/80

1/4 Corner on the ~~South~~ ^{NORTH} Tnsp. line, common to Sec.3 & Sec.34 of T26-4.
Found - 2-1/2" I.P. w/3" B.C. marked: "T26S R4W 1/4 S34 S3 T27S R4W 1975 U.S. Dept. of Interior B.L.M." from which:
BTs - 38" Oak, Orig. BT, w/healed face bears N.10°E., 63.4-ft.
14" Walnut BT, w/healed face bears S.61°E., 238.6-ft. (Rec. 239.6-ft.). Ren. #67
Note - 1" iron axle is set alongside B.C. 8/17/81

138

139

1/4 Corner for Sec. 7; and Sec. 12 of T.27-5
Found - 1 1/4" I.P. with 2 1/2" brass cap attached. Ren. #132
24" dbl. Ash (Rec. Alder) S.36°41'W., 243.2 ft. Scribe visible (Rec. S.33°W., 243.2 ft.)
12" W. oak stump, N.67°05'E., 352.1 ft. (Rec. N.68°E., 350.5 ft.)
Set - R.P. spike in PP & L pole No."6/99 R", S.34°05'E., 142.1 ft. 1/84

140

Section Corner for Sections 15,14,22, & 23. Ren:#130
Found - 2-1/2" I.P. w/properly mkd. B.C. protruding 8" above ground.
1-1/4" I.P. w/2-1/2", properly mkd., County Surveyors B.C., protruding 17" above ground, (set by Byron in 1959).
Byron's 2-1/2" cap bears N.1-1/2°W., 39.30-ft. from the B.L.M. cap, (B.L.M. Rec. = N.2°38'W., 39.6-ft.)
Byron's 32" cedar (now 32" w/partially healed dbl. blaze) bears N.9°E., 76.0-ft. from Byron's cap (Rec. N.9°E., 76.5-ft.) and also bears N.5°E., 115.5-ft. from B.L.M. cap.
Byron's 40" cedar (now 52" w/well healed dbl. blaze) fnd per Byron's rec., N.43°E., 52.7-ft. & bears N.24°E., 83.6-ft. from the B.L.M. cap.
Byron's 34" B.Oak (now 38" w/well healed dbl.blaze) bears S.89°E., 136.0-ft. from Byron's cap (Rec. S.89°E., 135.4-ft.) & bears N.74°E., 139.9-ft. from the B.L.M. cap. --NOTE:--Byron's scribing is for wrong section.--
Tracy's 30" B.Oak (now 31" w/well healed dbl.blaze on 4 trunk B. Oak) bears N.7°W., 254.70-ft. from Byron's cap (Rec. 252.6-ft.) & bears N.7-1/2°W., 294.0-ft. from the B.L.M. cap.
B.L.M.'s 7" cedar (now 8" w/well healed blaze on triple trunk) bears N.42-1/2°E., 39.0-ft. (B.L.M. Rec. N.40°E., 38.9-ft.) from the B.L.M. cap
B.L.M.'s 8" cedar (now 12" w/partially healed blaze) bears S.43-1/2°E., 15.7-ft. (B.L.M. Rec. S.40-1/2°E., 15.2-ft.) from the B.L.M. cap.
B.L.M.'s 10" cedar (now 14" w/well healed blaze) fnd. per B.L.M. Rec., S.1°W., 34.3-ft.
B.L.M.'s 6" cedar (now 12" w/well healed blaze) bears N.32-1/2°W., 87.8-ft. (B.L.M. Rec. N.37°W.) from the B.L.M. cap.
Set - We cut off 1-1/4" I.P. & place yellow plastic cap inside pipe which is stamped: "DOUG. CO. SUVEYOR" (sic) 2/84