

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 T. S. R 4 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91881

151

Cont. from prev. pg:

Doug. Co. Surveyors  
R. SMith & S. Flause  
April 12, 1989  
C.S. 62/63

New Accessories:

- The center of a cast iron water main access cover 8" in dia. marked "Water" set flush with surface of Buckhorn Rd. #17 bears S.62½°W., 9.3 ft.  
A power pole with a COPCO tag marked B6196 bears N.57½°W., 22.8 ft.

4/12/89

152

Section Corner Section 36; and Sec. 31 of T.27-3

- Found - 3½" dia. 1989 BLM brass cap on a 2½" dia. iron pipe protruding 8" above ground. (unrecorded 1989 survey)  
¾" iron rod from Ren. #81 not seen.  
Orig. 14" now 22" dia. madrone with a rotted out center old blaze with possible reverse scribing visible, bears S.37½°W., 15.9 ft. (orig. rec. S.35°W., 14.5 ft.; BLM BT tag, N.37½°E., 14.5 ft.)  
10" now 24" dia. madrone with a previously opened blaze, no scribing visible bears S.43°E., 12.6 ft. (orig. rec. S.31°E., 11.2 ft. ' BLM 1989 BT tags N.43°W., 13.8 ft.)  
15" now 30" dia. madrone with a partially healed upper blaze scribing visible "T27S R3W S3 " lower blaze fully healed, bears N.48½°E., 13.9 ft. (Orig. rec. N.40°E., 13.9 ft.; 1989 BT tag S.48½°W., 13.9 ft.)  
14" now 20" dia. 7 ft. high madrone snag with a partially healed double blaze, scribing visible "T27S R4W S36 CS BT" bears N.24½°W., 12.5 ft. (Orig. rec. N.23°W., 11.9 ft.; BLM 1989 BT tag, S.24½°E., no dist.)  
1989 BLM BT, a 7" dia. D. fir with a single blaze, scribing visible "T27S R4W S36 SC BT" bears N.41½°W., 24.8 ft. (agrees with BLM 1989 BT tag.)  
5" dia. D. fir double blazed, marks visible "X BT" bears N.59°E., 16.1 ft. (1989 BLM BT tag N.59°E., 16.1 ft.)  
2½" dia. brass cap on a 1½" dia. iron pipe protruding 14" above ground, marked "County Surveyors Office T27S S36 R4W S1 S6 CC T28S 1961" bears N.87½°W., 52.5 ft. (Rec. 52.0 ft. from Ren.#60)  
CORNER REPORT ONLY. NO NEW MONUMENT OR ACCESSORIES

9/18/89

153

Section Corner for Secs. 21, 22, 27 and 28

- Found - A 1 3/8" dia. axle protrudes 8" above ground. (Set by B.B. Irving in 1937. See Ren. #7)  
An "L" shaped iron rod, top measures 2" x 1", rod is 1" dia., protrudes 1" above ground, bears S.12°W., 0.7 ft. from axle. (Source unknown.)  
(No evidence of any original BTs found.)  
BTs from Ren. #7:  
24" B. oak, bearing N.72°W., 18.5 ft. is gone.  
18" now 28" dia. W. oak with a fully healed double blaze bears S.1½°W., 137.0 ft. (Rec. S.1½°W., 135.6 ft. dist. possible face measurement.)  
18" now 36" dia. B. oak no blazes visible bears N.75°E., 73.0 ft.  
18" B. oak bearing N.89°E., 169.7ft. is gone.  
BTs from Ren. #37:  
9" now 30" dia. D. fir with a fully healed double blaze, bears N.51°E., 25.6 ft. (agrees with record)  
5" now 25" dia. D. fir with a fully healed double blaze, bears N.47°W., 20.5 ft. (agrees with record)  
(Brass cap, iron pipe NOT set)  
New BT - 15" B. oak double blazed and scribed "T27S R4W S28 CS BT" bears S.6°W., 26.3 ft.  
Corner lies at north west corner of an open pasture.

10/9/89

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
C.S. 64/3  
Sept. 18, 1989

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Oct. 9, 1989  
C.S. 64/3