

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27

T. S.

R 4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

154

Section Corner for Sections 20, 21, 28 and 29

- Found - A 5/8" iron rod with yellow plastic cap marked "Bentz Survey Inc." protrudes 1" above ground. Ren. #146  
A 5/8" iron rod with metal washer attached on south side, marked "LS 1903" protrudes 3" above ground, bears N.23 3/4° W., 28.6' from Bentz iron rod. (agrees well with rec. from Ren. #146)  
This I.R. set as property cor. by Roderick Kimberling in Survey M 91 - 70.  
12" now 10" dia. madrone bark scribed "T29S R4W S21 BT" (Note T29S should be T27S) bears N.37°E., 35.4 ft. (Rec. N.40°E., 35.4 ft.) Ren. No. 146  
8" now 7" dia. D. fir with a partially healed single blaze w illegible scribing visible, bears N.42½°W., 29.3 ft. (Rec. N.44°W., 29.3 ft.) From Ren. No. 146  
10" now 10" dia. Cedar with a partially healed single blaze scribing visible "T29S R4W S28 BT" (note: T29S should be T27S) bears S.1°E., 62.3 ft. (agrees well with record) Ren.#146  
10" dia. D. fir with a partially healed single blaze scribing visible "T29S R4W B" (Note T29S should be T27S) BT not on Ren. #146. A yellow BT tag marked "N9E 66.0 T27S R4W Sec. 29 Bentz 3/21/86" is nailed on tree, BT bears S.8°W., 66.0 ft:

No new monument or accessories established.

10/11/89

Douglas County  
Surveyors Office  
Randall Smith  
Stephen flause  
Oct. 11, 1989  
C.S. 64/3

Hayden, For:  
Matthews  
Aug. 9, 1884  
Vol. 2 Page 35

E SE Cor. DLC #43

- Set - Post  
BTs - 15" Fir, N.28°E., 14 lks.  
16" Fir, S.52°E., .60 lks.

155