

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Sec. Cor. to Secs. 7 & 18, T27-4W. & Secs. 12 & 13, T27-5W.

Set - 1" Pipe & Brass Cap Mkd: County Surveyor's Office

FD OK PER R.M. 3-70A#B

Cor. Sec. 12 & 13, R5W

DEC. 1988

From Which:

Cor. Sec. 7 & 18, R4W

FD, B.C. 8-90 1990-0055

B. O. 30"; bears N.26°E. 33.0 ft. O.B.T., rescribed

B. O. 36" bears S.75°E. 30.8 ft. O.B.T., rescribed

B. O. 36", bears N.85°W. 60.8 ft. O.B.T., rescribed

B. O. (snag) 36" bears S.75°W. 29.7 ft.

New BT: 36" B.O. S.60°W. 81.8 feet.

69

Sec. Corner Sec. 18 & 19, T27-4W. & Sec. 13 & 24, T27-5W.

Set - 1" Brass Cap Mkd: Cor. Sec. 13 & 24, R5W - Sec. 18 & 19, R4W

from which: No trees available.

Not FD per M101-26 8/87
FD OK PER R.M. 3-70A#B
DEC-1988

70

1/4 Corner to Sec. 19, R4W & Sec. 24, R5W.

This corner is on the north side of the Co. Rd. No. 17 at the junction of the O.C. Brown (Co. #134) Road.

Set - 1" Brass Cap Mkd: 1/4 S19 & 24 from which:

LOD nail in a guy pole (C.O.P. Co. #B 6122) bears N.54°38'W. 21.4'

C.O.P. Co. Pole # B 6196 bears S.27°05'W. 41.0 ft.

LOD nail in top of anchor post bears N.33°49'E. 23.05 ft.

1" I.P.W. / Brass caps per CS file
FD OK 8/87
D. Bentz M101-26

RE-RENEWED SEE CORNER NO. #151

72

Sec. Cor. to Secs. 19 & 30, T27-4W. & Secs. 24 & 25, T27-5W.

Set - 1" Brass Cap 6" below ground from which:

LOD nail in top of anchor post bears N.40°36'E. 31.22 ft.

LOD nail in anchor post bears S.41°41'E. 12.53 feet. 28' FT. M.C. &

Metal 6 on C.O.P. Co. pole # B 6125 bears S.80°52'W. 12.53 feet.

73

1/4 Corner to Sec. 18; T27-4W. & Sec. 13, T27-5W.

Set - 1" Brass Cap Mkd: 1/4 S13 & 18 from which:

8" W. Oak bears S.18°W. 87.8 ft. (1/4 S18 CS BT) 1953 RENEWAL

18" W. Oak bears S.18°E. 86.4 ft. (1/4 S13 CS BT) 1958 RENEWAL BELOW.

FD OK PER RALIGH
R.M. 3-70A#B
12-27-85

Same Corner 1/4 Cor. Sec. 18, 4W. & Sec. 13, 5W.

Found - Brass Cap at Corner as set in 1953, (see CS File 45/150)

Both BT's. have been bulldozed out.

Measured record dist. S. from Sec. Cor. 12 | 7 Checks

R5W 13 | 18 R4W O.K.

Set - PK Nail 1' above ground in power pole N.2°W. 228.5 ft. (W. Pole)

PK Nail in top of Fence Corner Post N.12°E. 248.0 feet.

James W. Byron & Grew
May 1958
C.S. File No. 49/74

NEXT

PAGE