

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 5 R. W. W. M.

MEANDER CORNER BETWEEN SECTIONS 13, T.27S. R.6W. and 18
T.27S.R.5W. (SEARCHED FOR, NOT FOUND, JUNE 17, 1966 V.R.T.-C.R. 53/38) **9**
On Elks Island 3" x 3" Cedar Post and 3/4" Iron Rod 24"
long, from which
Ash 6" dia. bark blaze bears S.38°E., 23.8 ft.
Ash 6" dia. bark blazed bears S.87°W., 21.6 ft. marked
C.S.M.C. S. 13-18 B.T. (SEARCHED FOR, N.F. 8/25/87 C.S. 62/45 LGM)

MEANDER CORNER BETWEEN SECTIONS 24 T.27S. R.6W. and Section
19 T.27S.R.5W. - (SEARCHED FOR, NOT FOUND JUNE 17, 1966 - C.R. 53/38) V.R.T. **10**
On Elks Island 3" x 3" Red Cedar Post and 1" Bolt
30" long from which
A Balm of Gilead bears S.61°W., 39.8 ft.
A Balm of Gilead 15" dia. bears N.50°W., 30.5 ft.
marked T.27S. R.5-6 S.14 S.24

SECTION CORNER SECTION 13 and 24 T.27S. R.6W. and Section
18 and 19 T.27S. R.5W. **11**
On Elks Island. Set a 1/2" x 1/2" Iron Rod 27" long 15"
below ground surface for corner from which
A 30" Balm tree bears N.62°W., 155 ft.
A 14" Black Oak bears S.78°W., 101.7 ft.
A 30" Cherry, bark blazed, bears S.85 1/2°E., 255 ft.

N.E. CORNER CLAIM 49 T.27-5W. **12**
Iron Pipe 1/2" x 36"
Black Oak 15" dia. bears S.84°E., 11.3 ft. marked
Cl. 49 C.S. B.T.
White Oak 8" dia. bears S.27°W., 30.0 ft. marked
Cl. 49 C.S. B.T.

N.W. CORNER D.L.C. # 39 **13**
Set from original Black Oak B.T. which is still standing
but hollow and burned out mostly dead. Sam Sykes identifies
this as correct B.T. for corner. Corner is on river bank
about 375 ft. (N.50°E.) from end of Douglas St. Set a 2"
gas pipe 48" long for corner from which
A Black Walnut 24" dia. bears S.26 1/2°W., 75.7 ft.
(Bark blaze on walnut tree)
Original B.T. is N.10°E., 10 lks.

N.W. CORNER D.L.C. # 38 **14**
Found 2" Galvanized Iron Pipe referred to for 24 years, or
more, as corner. Set following ties; N.15°E., 55.3 ft. cross
on bottom of concret step. S.42 1/2°E., 5.4 ft. to tack in
15" Maple, which is bark blazed. S.10°17'E., 121.8 ft. to
Street Mon; Winchester and 2nd Ave. N. Pipe for Corner is
concreted in, Nov. 30, 1938. **FD OK PER BESTZ
JAN 1989 M107-47**

N.E. CORNER OF D.L.C. # 39 WHICH IS ALSO S.W. INT. "L" **15**
CORNER OF SIM. # 38 (On Fowler St. N. End Deep River Bridge) **54**
1 1/2" Pipe, (1" telescoped in it) from which a 30" Black
Walnut bears S.98°51'W., 172.7 ft. and cross on E. side of
Steel Bridge, on truss, just above floor level bears S.19°W.,
32.3 ft. Also cross on N.E. Bridge Pier side is 26.1 and
23 ft. E. of center of Fowler St. to corner.

S.E. INTERIOR "L" CORNER OF D.L.C. 39 **16**
On E. Side of S. Main St. near Mosher, set from remains of
B.T. which is S.35°E., 190 lks. from corner and is original
White Oak B.T. as certified to in a written, filed statement,
by Mr. E. L. Giles in V. E. Set a 1" Steel Auto
axle from which the street monument just south of 331 S. Main
Street bears S.50°W., 97 ft and a cross on curb at about
prip. line between 315 and 331 S. Main St. bears N.41°W.,
22.5 ft.

H. L. Eppstein
A. Boyer Wites.
N. E. Richardson
Sept. 27, 1936
Vol. 4, P. 51

A. Boyer Dep. Co. Sur.
Wit.
N. E. Richardson
P. D. Wolford
Sept. 27, 1936
Vol. 4, P. 51

A. Boyer D.C.S.
Wit. N. E. Richardson
Harvey Eppstein Jr.
Fred Fisher
Nov. 23, 1938
Vol. 4, P. 54-58

A. Boyer D.C.S.
Wit.
Ted Shellabarger
Fred Bowen
Nov. 30, 1938
Vol. 4, P. 58

A. Boyer
Wit.
Jan. 9, 1939
A. Boyer D.C.S.
Ted Shellabarger
Vol. 4, P. 57