

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

FND. OK 10-90 M111-35

106

$\frac{1}{4}$  Corner to Sections 14 and 13.  
Found - Iron Pipe at Corner, See Ren. #44.  
9" Oak, now 12", N. 10° E. 33.6 ft., Opened tree for scribe, "CS".  
Orig. 14" W. Oak, now down, S. 68° E. 104.2 ft.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966  
(alongside I.P.) T27S R5W S S 14 / S 13  
New BT: 8" W. Oak N. 18 $\frac{1}{2}$ ° W. 55.2 ft. scribed  $\frac{1}{4}$  S14 CS BT.  
Note - This corner lies 22.6 ft. East of N - S Fence Line.

107

$\frac{1}{4}$  Corner to Sections 11 and 12.  
Found - Orig. 24" W. Oak, now 48", N. 16 $\frac{1}{2}$ ° E. 159.1 ft., opened  
for scribing "BT".  
No trace of other tree.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966  
T27S R5W  $\frac{1}{4}$  S 11/S 12  
New BT's: 12" W. Oak N. 4° E. 143.8 ft. scribed  $\frac{1}{4}$  S12 CS BT.  
9" W. Oak N. 77° W. 88.6 ft. scribed  $\frac{1}{4}$  S11 CS BT.  
This corner lies about 160 ft. from top of hill on the south slope  
and 2.6 ft. East of N - S. Fence Line.

108

Sec. Cor. to Sections 11 - 12 - 13 - 14.  
Found - Stone, out of place, ties to fence Mkd: 11-12- CS 13-14,  
See Ren. #43.  
6" W. Oak, now 12", S. 37° W. 10.0 ft., shows scar.  
14" W. Oak, now 19", N. 30 $\frac{1}{2}$ ° W. 43.0 ft., shows scar.  
20" W. Oak, now 23", N. 45° E. 89.3 ft., shows car (dist. S.B. 81.3)  
Orig. 30" W. Oak S. 61 $\frac{1}{2}$ ° E. 297.0 ft. Had been opened for scribe.  
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966  
T. 27S R5W  
S 11 | S 12  
S 14 | S 13  
All BT's. in good condition. - Corner located 3.0 ft. West of  
N - S. Fence Line.

109

Sec. Cor. to Sections 9 - 10 - 15 - 16.  
Found - Steel Axle with gear attached flush with ground, Ren. #64.  
Orig. 14" B. Oak, now 35", N. 24 $\frac{1}{2}$ ° W. 64.0 ft., shows very  
slight scar.  
Orig. 16" B. Oak, now down, N. 34 $\frac{1}{2}$ ° E. 89.1 ft.  
Orig. 20" B. Oak, now down, S. 4 $\frac{1}{2}$ ° W. 342.1 ft.  
New BT's: 12" W. Oak N. 88° E. 14.0 ft. scribed T27SR5W S10 CS BT.  
11" Laurel S. 7° E. 48.9 ft., scribed T27SR5W S15 CS BT.  
Reblazed & Rescribed:  
35" B. Oak N. 24 $\frac{1}{2}$ ° W. 64.0 ft. scribed T27S R5W S 9 CS BT.  
This corner lies due north of fence corner, 4.5 feet.

110

$\frac{1}{4}$  Corner to Sections 4 and 9.  
Found - Scribed Stake at  $\frac{1}{4}$  Cor. Mkd: "1/4 S".  
Orig. 16" B. O., now 24", N. 55° W. 36.3 ft. Opened Tree, found  
bees, but could feel reverse scribing.  
14" B. O. S. 22 $\frac{3}{4}$ ° E. 58.7 ft., gone.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966  
T27S R5W  $\frac{1}{4}$  S 4  
S 9  
New BT's: 9" B. Oak N. 50° W. 9.0 ft. scribed  $\frac{1}{4}$  S4 CS BT.  
20" D. Fir S. 56° W. 38.0 ft. scribed  $\frac{1}{4}$  S9 CS BT.  
Note - This corner is in small draw, 2.6 ft. south of E. - W. fence.

111

Sec. Cor. to Sections 3 - 4 - 9 - 10.  
Found - 24" B. Oak, down; S. 17 $\frac{1}{2}$ ° W. 123.4 ft. Tree had been opened,  
(Orig. BT.) See Ren. #46 scribe visible "S".  
Orig. 11" Laurel, now 20", N. 77 $\frac{1}{2}$ ° W. 156.4 ft., no scar visible.  
Orig. 9" W. Oak, now 19", S. 23 $\frac{1}{2}$ ° W. 92.4 ft., not much scar for face.  
8" B. Oak, now , N. 7° E. 52.1 ft. Opened for scribe "3".  
(found Bear. to be N. 15° E.) T27S R5W  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966  
S 4 | S 3  
S 9 | S 10

(continued next page)

John M. Powell  
Frank Jones & Joe Brady  
March 1966  
C. S. File No. 53/38

Fd 6/90  
CS 63/108