

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

New BT's: 9" W. Oak N. 62° W. 45.2 ft. scribed T27S R5W S 4 CS BT.
11" W. Oak S. 56° E. 17.9 ft. scribed T27S R5W S10 CS BT.
(This tree is corner post for Fence Corner N. & W.)
5" B. Oak S. 87° W. 50.5 ft. scribed S 9 CS BT.

1/4 Corner to Sections 31 and 32.

Found - 24" Pine, now 34", S. 36° 45' W. 18.0 ft., shows good scar.
No Trace of Corner Stake. - See Ren. #28.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966
T27S R5W 1/4 S 31/S 32

All BT's. in good condition including:

12" D. Fir, now 19" S. 54° E. 22.0 ft., shows good scar.
This corner lies on top of ridge, running E. & W.

112

Fd. OK. by:
H. Pieske
June, 1966
see M 90-22
Fd 8/10 M 112-12

Sec. Cor. to Secs. 18 & 19, T27-5W. & Secs. 18 & 21, T27-6W. #168
Found - 1 1/2" x 1/2" I. Bar, 22" below surface of ground. (Ren. #11)

30", now 32" Cherry S. 85 1/2° E. 255.0 ft., shows faint "BT" bark
scribe, now almost dead.

Other BT's. now gone due to floods.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T27S R6W S 13 | S 18 R5W
S 24 | S 19

Set B.C. over Iron Bar 6" above ground & an 8' steel fence post
alongside Brass Cap 5.0 ft. above ground.

New BT: 13" B. Oak S. 2° E. 159.7 ft. Mkd: T27S R5W S19 CS BT.
No other trees close.

Beacon Tower on Mt. Nebo bears S. 64 1/2° W.

KPIC- TV Tower on Rose Mt. bears N. 39 1/2° E. Corner lies approx. 100 ft.
East of top of bank on west edge of Elk Island.

June 16, 1966

113

Meander Corner to Section 19, T27-5 and Sec. 24, T27-6W. #166

Found - No trace of Iron Bolt, See Ren. #10
20" Balm, now 33", S. 6 1/2° W. 39.8 ft., (find dist. to be 41.2 ft.)
15" Balm, now 19", N. 50° W. 30.5 ft., opened for scribe "S".

Set - Brass Cap at M. C. Mkd: County Surveyor's Office, 1966
T 27 S R6W S 24 / S 19 R5W

New BT: 25" Balm N. 43 1/2° W. 31.5 ft. scribed M.C. S24 CS BT.

Aug. 22, 1966

114

Meander Corner to Sec. 18, T27-5 & Sec. 13, T27-6. #167

Found - No trace of 1 1/4" Iron, N. 16° W. 62.0 ft. under fence.
3/8" I. Rod with small 3 cornered flange for M. C., Ren. #33.
14" W. Oak, now 17", S. 60 1/2° W. 117.4 ft., opened for scribe "S".
(Bearing Tree O.K., tagged with Yellow Flag.)

Iron Rod is now 7.0 ft. due South and 10.3 ft. due West of South Rail
of Railroad Track. Also, yellow location tags on Railroad Tie.
Telephone pole #4 N. 71° W. 31.3 ft.

Aug. 22, 1966

115

Sec. Cor. to Secs. 6 & 7, T27-5W. & Secs. 1 & 12, T27-6W. #156

Found - 5/8" Iron Bolt, 8" below surface of ground. See Ren. #38.
12", now 20" W. Oak, alive, N. 40° E. 75.6 ft., shows good
scar, we do not open.

20", now 26" W. Oak, alive, N. 46° W. 132.0 ft., shows good
upper scar, lower blaze shows "bt" scribe.

Set - Brass Cap at Cor. Mkd: County Surveyors Office, 1967
(Flush with Ground) R T 27 S R
6 S 1 | S 6 5
Reset Bolt alongside. 1967 W S 12 | S 7 W

Also set 6.0 ft. steel fence post 2.0 ft. south of corner.
This corner lies 75.0 ft. south of Newton Creek in open field.

Sept. 1, 1967

116

John M. Fowell & Crew
March 1966
Vernon "Ray" Tracy & Crew
June, 1966 C. S. File No. 53/38

John M. Powell
Frank Jones & Terry Connell
Aug. 22, 1966
C. S. File No. 53/38

"Ray" Tracy & Crew
Sept. 1, 1967
C. S. File No. 53/38