

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

150

S.E. Corner D.L.C. #37

Found - A 3/4" Iron rod, 1" above ground. Ren. #105
 A 8" now 22" White Oak bears N.15°W., 191.4 ft. with a single blaze, opened and rotted out. (OBT).
 A 12" now 15" White Oak bears N.53 1/2°W., (Rec. N.55°W) 119.6 ft. with visible scribing "3" in a well healed and opened blaze. (Ren. #42)
 A 10" now 13" White Oak bears N.12°W., (Rec. N.13 1/2°W) 168.0 ft. with faint scribe marks in a partially healed blaze.
 A 3/4" I.P. bears S.76°W., 1.8 ft. (Ren. #42)
 Set - A 1" x 36" I.P. with brass cap set over 3/4" Iron rod, 4" above ground marked: "Douglas County Surveyor" T 27 S R 5 W
 1977 S.E. Cor.
 D.L.C. 37

R. B. Kimberling
 S. J. Flause
 Doug. Co. Surveyors
 Office
 Dec. 29, 1977
 C.S. 59/42

No new accessories.

12/29/77

Section Corner for Secs. 6; Secs. 1, T27-6; Sec. 36, T26-6; Sec. 31, T26-5.

151

Found - A 1" O.D. Ironpipe, firmly set in a mound of stone. Ren. #40
 We find depressions in the ground and fragments of Oak roots at the approx. record positions of the orig. NE, SE, and NW bearing trees. There is no identifiable evidence at these positions.
 A 10" now 13" Fork of a W. Oak, alive with well healed double blaze bears S.63°W., 27.8 ft. (Measured to center of root crown at ground level) (Rec. S.55°W., 27.8 ft.). Ren. #40
 A 6" now 10" W. Oak, alive with well healed double blaze bears S.14°E., 15.4 ft. (Rec. S.14°E., 15 ft.)
 A 6" now 9" W. Oak alive with well healed double blaze bears N.70°E., 48.0 ft. (Rec. N.73°E., 48 ft.)
 A 10" now 17" W. Oak, alive with well healed double blaze bears N.48°W., 73.3 ft. (Rec. N.50°W., 74.1 ft.)
 Set - At the location of the found 1" O.D. Iron pipe we Set a 1" x 30" I. Pipe with brass cap attached 28 inches in the ground, surrounded with rock and the found Iron pipe alongside. We Mark the brass cap Douglas Co. Surveyor

Gary L. Langlitz
 S. J. Flause
 F. C. Silagy
 Doug. Co. Surveyors
 Office
 April 24, 1978
 C.S. 59/46

36 T 26 S
 S 26 S 31 R 5 W
 S 1 S 6
 T 27 S

Fd. OK
 9/24/79
 DC 50

(TYPE BREAK)
 CAP MKD.
 OK JR

No new accessories

4/24/78

SW Cor DLC #40

152

Found - Orig. post with raised mound and trench not found. Found 1950 Douglas County Brass cap. Ren. #82
 B. Oak 24" now 36" bears S.56 1/4°W., 13.0 ft. Tree has well healed single blaze.
 A B. Oak, 18" now 24" bears S.66 1/4°E., 15.8 ft. to center of base, 16.4 ft. to center of trunk (Rec. 16.4 ft.) Tree has well healed single blaze.
 Orig. B. Oak not found.
 Tagged found bearing trees.

Larry E. Monrean
 P.L. Earle
 Doug. Co. Surveyors
 Office
 October 31, 1978
 C.S. 60/17

10/31/78

Southeast corner DLC #37

153

Found - A 1" x 36" I. P. with brass cap marked "Douglas County Surveyor T27S R5W S.E. Cor. DLC 37 1977, over 3/4" I. Rod. Ren. #150
 A 3/4" I. Pipe bears S.76°W., 1.8 ft. Ren. #42
 A 8" now 22" W. Oak bears N.16°W., (Rec. N.15°W.) 191.4 ft. with a single blaze, opened and rotted out. (OBT)
 A 12" now 15" W. Oak bears N.53 1/2°W., (Rec. N.55°W.) 119.6 ft. with visible scribing "3" in well healed and opened blaze.
 A 10" now 13" W. Oak bears N.12°W., (Rec. N.13 1/2°W.) 168.0 ft. with faint scribe marks in partially healed blaze.
 Set - Placed brass cap over 3/4" I. pipe. Left 3/4" I. Rod in original position. 3/4" I. Pipe was set prior to 3/4" I. Rod.
 3/4" I. Rod bears N.76°E., 1.8 ft. (Ren. #105)

Karen Reed
 S.J. Flause
 Doug. Co. Surveyors Office
 March 12, 1979
 C.S. 60/24

3/12/79

L-79