

Douglas County Surveyor's Record of
Government Corners Renewed

27 T.S. 5 R.W.W.M.

17

S.W. EXTERIOR "L" CORNER OF D.L.C. # 38
On left or W. bank of Deer Creek. Set from Fleser, 1914, established B.T.s and from notes taken from surveys made when evidence was more distinct (by Fleser Mar. 1914 Book II, P. 46) than now and from survey of city (Barn) property, drove 1" Auto Rear Axle from which new trees as follows
Locust, on brow of hill, 18" dia. bears N.55°W., 51.5 ft. (on slope)
White Oak 24" dia. bears S13°W., 46.9 ft.
Trees by Fleser still standing but decayed.
Alder 24" dia. bears S.261°E., 42 ft.
Alder 16" dia. bears N.47½°W., 19 ft.
Willow gone

RE-NEWED, SEE CORNER NO. #159

Arthur Boyer D.C.S.
Jan 13, 1939
Ted Shellebarger
Vol. 4, P. 58

Vol 4 Page 58

18

S.W. CORNER OF D.L.C. # 38
On East Side of Fowler Street North of Douglas Street between 417 and 427 Fowler St. I found 1" Iron Pipe only, chiseled cross on concrete curb S.56°W., 21.7 ft. and cross on concrete curb N.34°W., 30.9 ft.

RE-NEWED, SEE CORNER NO. 122

19

CORNER BETWEEN SECTIONS 25 and 30 ON RANGE LINE 5 and 6
Set from old B.T.s. Corner set by placing ½" x 16" Galv. Iron Pipe form which new bearing trees
White Oak 8" dia. bears N.44°30'E., 8.2 ft.
White Oak 10" dia. bears N.46°W., 137.8 ft.

Vol 4 P. 55

20

CORNER SECTION BETWEEN 24, 19, 35, and 31
Set from White Oak original bearing tree S.36°E., 116.8 ft.
Set ½" x 30" Iron Bar and an Oak Stake under ground from which
White Oak 24" dia. bears S.36°E., 116.8 ft.
Street Monument Rice and Main St. bears S.67°06'W., 229.7 ft.
Street Monument Roberts and Main St. bears N.5°50'W., 230.7 ft.

Source

RE-NEWED, SEE CORNER NO. 68

21

Corner Section to 25, 30, 36 and 31.
This corner was gone, but was set by proportional distances between ¼ to 25 and 30 and the ¼ to 31 and 36. Set ¾" x 30" Iron Rod for corner from which new B.T.s were made as follows
White Oak 24" dia. bears N.30°E., 34.0 ft.
Laurel 4" dia. bears N87°E., 158.5 ft.
Black Oak 6" dia. bears S.2°E., 41.5 ft.
White Oak 18" dia. bears N.1°W., 146.0 ft.

Vol. 4 Pages 50-58

1934-1937-1938
Claude Crocker
Arthur Boyer
J. H. Wolford
E. A. Lane

22

CORNER BETWEEN SECTIONS 31 and 36. (R. 6 & R. 5)
From one old bearing tree I set a stake for corner from which the new bearing trees were made as follows
White Oak 10" dia. bears S.59°E., 24.6 ft.
White Oak 10" dia. bears S.57°30'W., 165.1 ft.

RE-NEWED, SEE CORNER NO. 74

23

SECTION CORNER TO SECTION 36 and 31. TOWNSHIP CORNER (R. 6 & R. 5)
Set corner from old B.T.s. Set ¾" x 36" round Bolt for corner from which new B.T.s were made as follows
White Oak 12" dia. bears N.22°W., 58.5 ft.
White Oak 14" dia. bears N.81°30'E., 20 ft.

RE-NEWED, SEE CORNER NO. #171

24

N.W. TOWNSHIP COR. OF T. 28S. R. 5W
Township corner between 1 and 6 was set from old B.T.s. A ¾" round iron bolt 30" in ground. New bearing trees were marked as follows
Black Oak 18" dia. bears S.62°15'E., 152.6 ft.
Black Oak 14" dia. bears S.86°20'W., 226.6 ft.

RE-NEWED, SEE CORNER NO. 84