

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 27      T. S.      R 5      R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

170

Section Corner for Secs. 7, 8, 17 and 18

Found - A 3/4" iron bar now found to be a 1" dia. iron bar with threaded end is firmly set and protruding 3" above ground. Ren 55  
 Above monument is set on SW edge of BC monument set in Ren. #137  
 This is a 2 1/2" dia. BC mkd. correctly, set on a 1 3/8" O.D. I.P. firmly set and protruding 15" above ground.  
 11" now 21" dia. W. oak with a fully healed previously opened blaze bears N.66°E., 39.9 ft. (Rec. N.64 1/2°E., 40.9 ft. to center of trunk near horizontal) Orig. BT.  
 16" Y. oak original BT is gone.  
 18" now 34" dia. W. oak with fully healed previously opened double blaze bears S.53°E., 62.0 ft. agrees well with rec. (Orig. BT)  
 14" now 23" dia. 9 ft. high broken top oak, with a fully healed previously opened blaze bears S. 36°W., 88.4 ft. (Rec. S.40 1/2°W., 88.4 ft. (Orig. BT)  
 12" now 10" dia. W. oak with a partially healed single blaze illegible scribe marks visible, bears S.37°W., 36.1 ft. Ren. #137  
 20" now double trunked B. oak (Rec. W. Oak) a fully healed double blaze is found on 10" north trunk, base of tree bears S.4°E., 33.8 ft. (Rec. S.4°E., 34.8 ft. to center of trunk) Ren. #137  
 15" now 15" dia. W. Oak with a fully healed single blaze bears N.44°E., 50.8 ft. (agrees with rec.) Ren. No. 137  
 22" now double trunked B. oak with previously opened partially healed blaze, no scribing visible, rescribing visible "R6WS" from Ren. #137.  
 All blazes and scribing found on 18" dia. 4 ft. high broken top southwest trunk base bears N.21°W., 102.4 ft. (Rec. N.23°W., 102.4 ft.) Per. Ren. #55 and rescribed in Ren. #137

Corner lies on a southeast slope approx. 125 ft. east from top of NE-SW running ridge.

6/2/89

171

Section Corner for Section 31; and Sec. 36 of T.27-6

Found - 3/4" dia. iron bolt protruding 6" above ground, bolt leans 4" west of plumb. Ren. #23  
 Orig. 20" W. oak now 41" dia. B. oak with a fully healed single blaze, tree is rotted in center on NW side shows evidence of previous axe work, bears N.24 1/2°E., 295.7 ft. (Rec. N.22 1/4°E., 291.1 ft.) Note: Tree is over a rise and not visible from corner.  
 Orig. 20" now 40" dia. 8 ft. high rotted oak snag with a previously opened blaze, reverse scribing visible "T S" bears N.50 1/2°W., 232.2 ft. (agrees with record)  
 12" now 12" dia. W.oak with a fully healed double blaze bears N.22°W., 58.5 ft. (agrees w/rec.) Ren. No. 23  
 14" now 18" dia. W. oak with a fully healed double blaze bears N.84°E., 20.6 ft. (Rec. N.81 1/2°E., 20.0 ft.) Ren. No. 23  
 Set - A 2 3/8" dia. DCSO brass cap on a 1 3/8" x 32" long iron pipe is set at referenced plumb position of Ren. No. 23 3/4" iron bolt. DCSO BC/IP protrudes 7" above ground and mkd.

Douglas County Surveyors

T27S

R6W      R5W

S36 | S31

T28S R6W

S 1

1989

3/4" dia. iron bolt from Ren. #23 measures 30" long is set along north side of DCSO BC/IP, protrudes 5" above ground.

New BT - 7" dia. W. oak double blazed and scribed "T27S R5W S31 CS BT" bears N.1 1/2°E., 27.7 ft.

9/21/89

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Linda Rigutto  
June 2, 1989  
C.S. 62/63

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Sept. 21, 1989  
C. S. 64/1