

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 5 R. W. W. M.

35

1/4 CORNER BETWEEN SECTIONS 13 and 18 R. 5 & 6 W.
Corner set by proportional distance by setting 1" x 48" pipe inside 2" x 48" pipe. About 250 ft. South and west of Horace Burg's house from which
A White Oak 10" dia. bears S57°W., 223.5 ft. marked 1/4 S. 13 C.S. B.T.
A White Oak 18" dia. bears S.24°10'W., 242.3 ft. Marked 1/4 S. 13 C.S.B.T.

36

CORNER BETWEEN 12, 7, 13, and 18. R. 5 & 6 W.
Set by proportional measurement by placing 10" x 10" x 14" Sandstone 12" underground 3" under road ditch. X on top C.S. with two notches on North face from which S.W. corner of lot 15 Fruitvale bears S.1°58'E., 1026.1 ft. N.E. corner of D.L.C. # 56 T.27S.R.6W. bears S.28°24'E., 857.7 ft.

37

1/4 CORNER SECTIONS 7 and 12 R. 5 and 6 W.
Set by proportional measurement by driving machine gun barrel 10" underground, tin collar one brick on top three bricks placed around, 4" x 4" x 48" post 24" in ground marked 1/4 S. on North Face, C.S. on South face, S. 7 on East Face and S.12 on West Face from which N.E. Corner D.L.C. 37 T.27S.R.5W. bears N.75°12'E., 924.9 ft.

38

CORNER BETWEEN SECTIONS 1, 6, 12, and 7.
Set by proportional measurement by driving 5/8" x 42" Iron Botl 15" under ground with Oak chunk 4" x 6" on top from which
A White Oak 12" dia. bears N.40°E., 75.6 ft. marked 12/7
T.27S.R.5W. Sec. 6 C.S.B.T.
A White Oak 20" dia. bears N.46°W., 132 ft. marked V.R.T.
T.27S.R.6W. Sec. 1 C.S.B.T. 116 COR. FOUND O.K. July, 1967
No other trees near.

39

1/4 CORNER BETWEEN SECTIONS 1 and 6 R. 5 and 6 W.
Set by proportional measurement drove 1" x 24" machine gun barrel 23" in ground and set a yellow pine stake 3" sq. x 36" long with R.5" on East face, 1/4 S. on north face, R.6W. on West face, C.S.T.27S. on South face from which
White Oak 14" dia. bears S.68°45'E., 59.5 ft. marked 1/4 S. 6 C.S. B.T.
White Oak 20" dia. bears S.83°10'W., 77.7 ft. marked 77.7

40

TOWNSHIP CORNER 36, 31, 1 and 6 T.26 and 27 S. R. 5 and 6 W.
Set from stump, scribe visible, in S.E. and stump hole in S.W. set 1" x 48" pipe 42" in ground with pile of Rock 20" square base, 12" high from which
White Oak 10" dia. bears S.55°W., 27.8 ft. marked 36/31
T.27S.R.6W. S.1 C.S.B.T. 1/6
White Oak 6" dia. bears S.14°E., 15 ft. marked
T.27S.R.5W. S.6 C.S.B.T.
White Oak 6" dia. bears N.73°E., 48 ft. Marked # 151
T.26S.R.5W. S.31 C.S.B.T.
White Oak 10" dia. bears N.50°W., 74.1 ft. marked
T.26S., R.6W. S.36 C.S.B.T.

41

1/2 CORNER BETWEEN SECTIONS 7 and 18.
Set from stumps of old B.T.s amrks visible on N.E. stump. Marked new B.T.s as follows
Black Oak 8" dia. bears N.88°W., 47.6 ft. marked 1/2 S. 7 C.S.B.T.
White Oak 6" dia. bears S.53°30'W., Marked 1/4 S.18 C.S.B.T.
Also U.S.C. and G.S. triangulation Sta. Rose. bears N.55°01'30"E., 3175.6 ft.

FEB. 1970 - NOT FOUND V.R.T. C.S. FILE 53/38

NOV. 1971 - NOT FOUND - J.M.P. C.S. FILE 53/38

J. H. Wolford
B. A. Lane
N. E. Richardson

1934
Ben B. Irving
N. E. Richardson
Ernest Brown

Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52
Vol 4 P. 52

RE-RENEWED CORNER NO. 116

SEE CORNER NO. 69

SEE CORNER NO. # 151