

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 5 R. W. W. M.

42
S.E. CORNER TO D.L.C. # 37
Set from O.B.T. N.15°W., 291.4 ft. scribe marks plain.
Set for corner $\frac{3}{4}$ " Galvanized Iron Pipe from which 195
White Oak 12" dia. bears N.55°W., 119.6 ft. marked
Cl. 37 C.S.B.T.
White Oak 10" dia. bears N.13 $\frac{1}{2}$ °W., 168 ft. marked
Cl. 37 C.S.B.T.

43
SECTION CORNER 11, 12, 13 and 14.
Location identified from one original B.T.
White Oak 30" dia. bears S.61 $\frac{1}{2}$ °E., 450 lks. 108
also an old stamp hole N.56 $\frac{1}{2}$ °E., 137 lks. Set a rock
6" x 12" x 24" in ground for corner marked with X on top,
11 on N.W. face, 13 on S.E. face, and 14 on S.W. face. Also
4 notches on the South and 1 notch on the East corners from
which
White Oak 6" dia. bears S.37°W., 10 ft.
White Oak 14" dia. bears N.30 $\frac{1}{2}$ °W., 43 ft.
White Oak 20" dia. bears N.45°E., 89.3 ft.
White Oak 30" dia. bears S.61 $\frac{1}{2}$ °E., 297 ft. (original
B.T.)

44
SECTION CORNER SECTIONS 13 and 14.
Location identified from an original tree which was chopped
out and found to be in excellent shape S.68°E., 173 lks.
and the stump of a Oak B.T. S.6°W., 36 lks. showing the
reverse of the original scribe marks B.T. Drove an Iron
pipe $\frac{3}{4}$ " dia. and 36" long 30" in the ground from which an
Oak 9" dia. bears South 24.3 ft. and an Oak 9" dia. bears
N.10°E., 33.6 ft.

S.E. CORNER D.L.C. # 56. T.27S., R.6W.
This was previously set for "Bud" Criteser who says it
is N.40 $\frac{1}{2}$ °E., 77.5 ft. from a 12" Ash Tree which is scribed.
Set a $\frac{3}{4}$ " Steel Bar here and rocks. Note: Flood has bent
Ash tree down stream. 7-27-1 (OLD COR. REN. VOL. PG. 91)

45
CORNER BETWEEN 18 and 17. See Vol. 2 Pg. 91 ^{MAY 1900}
Renewed from B.T. 7" Black Oak N.38°W., 71.3 ft. Set
2" Iron Pipe from which REN #3
A Black Oak 8" dia. bears S.87°E., 140.2 ft. slope
measure
A Black Oak 14" dia. bears S.76°W., 73.3 ft. level

46
SECTION CORNER 3, 4, 9 and 10.
Set Oak Post for corner. Found all O.B.T.s except one
in Section 3. Marked new B.T.
Black Oak 8" dia. bears N.7°E., 79 links. 111

47
CORNER BETWEEN 3 and 4.
Set Oak Post for corner from original bearing tree to
S.W. New B.T.
Fir 12" dia. bears N.80°E., 212 lks. 136

48
N. E. CORNER S. HARKNESS D. L. C. 41 T. 27 S., R. 5 W.
Found evidence of old 4" x 4" post set in concrete.
Found stump and roots of 10" Ash which shows evidence of
being old bearing tree, located near center of creek and
had been washed out and displaced in falling down. Mag. Var.
used 21°15'E.

Vol 4, Page 53

C.S. FILE

53/58

C.S. FILE 36/52

C.S. FILE 38/25

Ben B. Irving D.C.S.
N.E. Richardson
Ernest Brown
1934

N.E. Richardson
R. L. Irving
H. L. Epstein Jr.
Sept. 30, 1939

A. Boyer D.C.S.
Ivan Norris
Bud Criteser
3-20-43

June 8, 1944
A Boyer D.C.S.
Darlley Ware
Gordon Ware

August 6, 1946
Charles S. Collins
W.K.
B. McNamee
Ed Boyer
C.S. 38/136

2/85
Ed. OR
of Bloom
M 95-43 +
M 98-31