

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 5 R. W. W. M.

ROYE-CHAPMAN CO., EUGENE, ORE. 97100

By O. Thiel
Re: Short & Dixon
May 17, 1900
1 vol 2 Pg 87

⁽²⁶⁻⁵⁾
1/4 sec. cor. bet. 36 and 1
Set post and raised mound of stone from which
A bl. oak 8" diam. bears S 42° E-29 lks distant.
A bl. oak 18" diam bears N 1° E-62 lks distant.
May 14, 1900. Present. James Short, W. Dixon, and Charles,
Patterson.
The original B T in the S E is standing but dead, the N W
B T is fallen down.

49

S W Cor. C 1 set post and Brick by stump of B T.
Set by Wm. Thiel Oct. 31, 1885
New B T W. Oak 30" N. 86° W 3.18 chains
B. Oak 30" S. 43° W 2.71 chains

POSTED IN ERROR 50
POSTED IN 26-5

1/4 COR. BETWEEN 35 & 36
Reset from Old B. T. bearing S 8 1/2° E, 309 lks.
Marks visible, other tree gone
Set a 36" truck spring from which
12" B. O. bears East 81.0 ft.
14" W. O. bears S 72° E, 52.7 ft. c.s. 53/38

RE-RENEWED, SEE CORNER NO. 145

51

C OR OF 35 - 36, T 27 S, R 5 W, and 1 - 2, T 28 S, R 5 W.
Reset from one old B. T. stump, marks plain, S 85 1/2° E, 450 lks.
I set a 1 1/2" x 1 1/2" x 36" angle iron from which
9" Pine bears N 86° E, 185.3 ft.
12" B. O. bears S 60 1/2° E 59.5 ft.
8" Y-W. O. bears S 34 1/2° W 63.3 ft.
5" W. O. bears N 75 1/2° W 113.5 ft.

angle iron knocked out by graders replaced with 1 1/2" x 1 1/2" Ask 1952

52

1/4 COR. BETWEEN 14-23
Reset from O. B. T., stump, N 23° E 94.4 ft., and rock for corner
found. Drove 2" x 36" G. I. P. beside rock and marked new B. T.'s.
24" B. Oak bears N 12° 37' W 179.7 ft.
14" W. Oak bears S 72° 56' E 197.6 ft.

FD 3/85 K. DeGeant 11 28.73

53

NE COR. AARON ROSE DLC #39
Set 2 1/2" x 6 ft. steel shaft.
Set from Art Boyers B. Ts. and two B. O's., his pipe had been
destroyed. - REN # 15

RE-RENEWED, SEE CORNER NO. 121

54

SEC. COR. 7-8-17-18
Found 4 O. B. T.'s, standing, NW B. T. broken off and dead.
Set 3/4" inch iron bar for corner from which new B. T.
Y. Black Oak 22" N 23° W 102.4 ft.

RE-RENEWED, SEE CORNER NO. 137

55

SECTIONS 7, 8, 18 and 19
Set 3/4" Iron Bar
22" Black Oak which bears N. 23 degrees West, 102.4 Ft.

8666 The Following Corners Were Set On A Job For The
California Oregon Power Co. in April Of 1953
By Ben B. Irving, County Surveyor
SEE File 150 Drawer 45

FOOK PER RM 3-70A&B
DEC 1988 BY RALEIGH
FD B.C. 8-90 1990-0055

Sec. Cor 12 & 13, T 27 S, R 5 W &
7 & 18, T 27 S, R 4 W

56

Set 1 in. pipe & brass cap M'k'd. County Surveyors Office
Corner Sec 12 & 13, R 5 W
Corner Sec 7 & 18, R 4 W
From Which;
A B. O. 30" bears N 26° E, 33.0 ft. O. B. T., Rescribed
A B. O. 36", Bears S 75° E, 30.8 ft. O.B.T., Rescribed
A B. O. 36", bears N 85° W, 60.8 ft. O.B.T., Rescribed
A B. O. (snag) 36" bears S 75° W, 29.7 ft
Blazed & Scribed New B. T. 36" B. O. S 60° W, 81.8 ft.

Floyd C. Frear
Witness-Durwood Owens
Roy Hatfield
March 31, 1948
c.s. 46/151

N.E. Richardson
Surveyor
M. E. Godfrey
F. D. Smith
Witnesses
Feb. 8, 1949
Vol 8 Pg 54

Richardson
Surv.-
Godfrey
Smith
10/26/49
C.S. FILE 49/159

A. R. Evans
Surv.
R. L. Clinton
J. I. Clinton
2/19/50
C.S. FILE 45/35

A.R. Evans
Feb. 1950
C.S. FILE 45/150