

Douglas County Surveyor's Record of
Government Corners Renewed

27 S T. S. 5 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97195

1/4 Sec. Cor. Sec 13, T 27 S, R 5 W &
Sec. 18, T 27 S, R 4 W Set 1" Brass cap Mkd. 1/2 s 13 & 18 57
from which;
an 8" W. Oak bears S 18°W, 87.8 ft. (1/2 s 18 C. S. B.T.)
an 18" W. Oak bears S 18°E, 86.4 ft. (1/2 s 13 CS BT) 70

Sec Corner Sec 13 & 24, T 27 S, R 5 W &
Sec 18 & 19, T 27 S, R 4 W Set 1" brass cap mkd. cor sec 13 & 24, R 5 W 58
from which;
/121/ No Trees Available Sec 18 & 19, R 4 W

1/4 Sec. Cor. 19 R 4 W &
24 R 5 W This Corner Is On The North Side of The County Rd.
17 at the junction of the O. C. Brown (Co. #134) Rd.
Set 1" brass cap Mkd 1/2 S 19 & 24 59
from which;
10D nail in a guy pole (C.O.P.Co. # B 6122 bears N 54°38'W, 21.4 ft
C.O.P.Co. Pole # B 6196 bears S 27°05'W, 41.0 ft.
10D nail in top of anchor post Bears N 33°49'E, 23.05 ft.

Sec Corner Sec 19 & 30 T 27 S, R 4 W 60
Sec 25 & 26 T 27 S, R 5 W Set 1" brass cap 6" Below ground
from which;
/10/ 10D nail in top of anchor post bears N 40°36'E, 31.22 ft.
10D nail in anchor post bears S 41°41'E, 12.53 ft. - 28° FT. 7 1/2 E. S.
Metal 6 on C.O.P.Co. pole # B 6125 bears S 80°52'W, 12.53

1/4 sec cor. 24 & 25 Set 1" brass cap from O. B. T. 61
Set 2 new BTs.
20" W oak S 82°W, 68.9 ft.
10" W Oak N 16°30'E 63.7 ft.

1/4 Sec Cor. 23 & 24 Fd. Pitch Pine Post, Ren No. 4 62
Set 1" brass cap along side 71

S. W. Cor. Edwin Morgan D.L.C.#50 Set 3/4" Iron Rod 63
from Which;
the SW corner of The Dixonville Store Bears N 46°21'E, 57.33
the NW corner of Dixonville Sub Bears S 25°16'E, 41.26'
the SE corner of The E. E. Hatfield Blacksmith Shop bears
N 36°55' 52'W, 50.45 ft.

Sec. Cor. 9, 10, 15 & 16 64
Set steel Axle with gear attached. File 154
Drawer 45
Corner set from 3 old B. T.s found: 20" Y. Oak, S. 41°W., 488 lks.
14" Y. Oak, N. 24°W., 97 lks. 16" Y. Oak, N. 34°E., 135 lks.

N.E. Cor. Cl. 46 Vol. 2 Pg. 285 65
12" B. O. W. 16 lks. Briggs Aug. 1853
12" B. O. N 12° W, 10 lks

1/4 section corner to secs, 7 & 8. 66
Black Oak B. T. to Southeast still standing - has been chopped out and
rotting but scribe marks still visible. White Oak stump to Northwest
hollow but reverse of scribe marks visible inside.
Set 1" x 30" steel shaft for corner.
Old B. Ts:
Y. Oak, 16", S. 30°E., 497 lks.
W. Oak, 8" N. 16°W., 192 lks. (Stump now).
Mark new B. T.:
22" B. Oak, N. 81°W., 33.5 feet.
The west pole of C.O.P.Co. tower No. 17, (Winchester - Roseburg line) bears
N. 19°E., 7.5 feet from corner.

These Corners were set on a survey for
G.O.P.Co. in April 1953
Drawer 45 File 150

E. S.
Woodford
April 1953
Witness:
Art Nelson

Edwin S. Woodford
November, 1955.
C. S. File No. 42/64.

I.P.W./B.C.
P.P.C.S.
F.D. OK
S/107 D.G. 10/1-24

Not FO.
PER
M101-24
8/87

FO OK PER RALEIGH
DEC 1983 RT73-DAB

SEE CORNER NO. 70

RE-RENEWED SEE CORNER NO. #169

SEE CORNER NO. 71

SEE CORNER NO. 109

RE-RENEWED SEE CORNER NO. #174

FOUND O.K.
TAGGED NW.BT.
J.N.P.
C.S. 54/23